THE COMPLETE BEGINNER’S GUIDE TO DRONE BUILDING

An Easy Guide for Students, Hobbyists and Innovators

EASY TO UNDERSTAND | STEP-BY-STEP BUILD GUIDE | PRACTICAL EXAMPLES | EXPERT INSIGHTS | AUTONOMOUS TECHNOLOGY

BY

MOKSHITH SHARMA T P

DEPARTMENT OF AERONAUTICAL ENGINEERING

NITTE MEENAKSHI INSTITUTE OF TECHNOLOGY

2026

The Complete Beginner's Guide to Drone Building

An Easy Guide for Students, Hobbyists and Innovators

Author
Mokshith Sharma T P

Department of Aeronautical Engineering
Nitte Meenakshi Institute of Technology (NMIT)
Bengaluru, Karnataka, India

First Edition – 2026

Copyright Notice

Copyright © 2026 Mokshith Sharma T P

All rights reserved.

No part of this publication may be reproduced, distributed, transmitted, stored in a retrieval system, or translated into any language in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the author, except for brief quotations used in reviews, educational references, or academic citations.

Disclaimer

This book is intended for educational and informational purposes only.

Drone operation, design, construction, and testing involve inherent risks. Readers are responsible for complying with all applicable laws, regulations, safety standards, and operational guidelines in their respective countries and regions.

The author and publisher shall not be held liable for any injury, damage, loss, legal issues, or consequences resulting from the use of information presented in this book.

Always follow local aviation regulations and practice safe drone operation.

Author
Mokshith Sharma T P
Aeronautical Engineering Student
Nitte Meenakshi Institute of Technology
Bengaluru, Karnataka, India

Book Information

Title:
The Complete Beginner's Guide to Drone Building

Subtitle:
An Easy Guide for Students, Hobbyists and Innovators

Edition:
First Edition (2026)

Language:
English

Suggested Citation

Mokshith Sharma T. P. (2026). *The Complete Beginner's Guide to Drone Building: An Easy Guide for Students, Hobbyists and Innovators*. First Edition.

Message from the Author

Dear Readers,

My name is **Mokshith Sharma T P**, and I am an Aeronautical Engineering student at **Nitte Meenakshi Institute of Technology (NMIT), Bengaluru**.

Since my childhood, I have been fascinated by aircraft, drones, and the technologies that enable machines to fly. During my academic journey, I realized that many beginners are interested in learning drone technology but often find it difficult because the available resources are either too technical, scattered across different sources, or difficult to understand.

This book was created with a simple objective: to make drone technology easy, practical, and accessible for everyone.

Whether you are a student, hobbyist, researcher, innovator, or aspiring drone developer, this book will guide you through the fundamental concepts of drones, component selection, design principles, electronics, flight systems, safety practices, and practical drone-building methods in a structured and beginner-friendly manner.

The content presented in this book is based on my learning experiences, research activities, practical observations, and continuous exploration of drone technology. Every effort has been made to explain complex topics in a simple way using diagrams, tables, examples, rules, and practical references.

I believe that drones will play a significant role in the future of agriculture, logistics, surveillance, mapping, disaster management, environmental monitoring, scientific research, and autonomous transportation. The next generation of engineers and innovators will shape that future, and I hope this book contributes to that journey.

Thank you for choosing this book. I sincerely hope it helps you learn, build, innovate, and explore the exciting world of drone technology.

Wishing you success in your drone-building journey.

Mokshith Sharma T P
Aeronautical Engineering Student
Department of Aeronautical Engineering
Nitte Meenakshi Institute of Technology (NMIT)
Bengaluru, Karnataka, India
2026
mail : mokshithsharma1411@gmail.com

Page	Main Section
1–4	Front Matter: Cover, Copyright, Message from the Author
7–11	Drone Basics: What is a Drone, Applications, Types, Flight Forces, Motions, Stability
12–16	Drone Frames and Frame Selection
17–20	Drone Motors, KV Rating, and Thrust Rules
21–24	ESC Fundamentals and ESC Selection
25–29	Propellers and Propeller Selection
30–37	Batteries, LiPo Basics, and Battery Selection
38–56	System Integration, Common Errors, and Drone Design Formulae
57–82	Flight Controllers, Sensors, GPS, and Telemetry
83–100	Radio Transmitter and Receiver Systems
101–158	Assembly, Wiring, Mission Planning, and Autonomous Flight Setup
159–176	Troubleshooting, Calibration, and Software Tools
178–183	Obstacle Avoidance Systems and Sensor Placement
187–217	Computer Vision Drones and AI Drone Systems
219–228	Swarm Drones and Multi-Drone Coordination
229–244	DGCA Rules, Airspace Zones, Safety, and Legal Compliance
245–255	Beginner Drone Projects and Comparison Table
256–289	Reference Tables, Wiring Guides, ESC Charts, Pre-Flight Checklist, and Appendix Material
290	References

Q.What is a Drone ?

A drone is an unmanned aircraft that can fly without a pilot on board. It is controlled by a remote controller, smartphone, or onboard computer. Drones are used for photography, surveillance, mapping, agriculture, delivery, and many other applications.
DRONE means Dynamically Remotely Operated Navigation Equipment

Applications of Drones

Agriculture: Drones help farmers monitor crops, spray fertilizers and pesticides, and check field conditions quickly and efficiently.

Delivery: Drones can transport small packages, medicines, and essential supplies to different locations in a short time.

Mapping: Drones capture aerial images and data to create accurate maps, 3D models, and land surveys.

Defense : Drones are used for surveillance, reconnaissance, border monitoring, and various military operations while keeping personnel safe.

Photography : Drones capture high-quality photos and videos from unique aerial viewpoints for events, films, and inspections.

Types of Drones



Quadcopter: A quadcopter has four motors and four propellers. It is the most common type of drone and is easy to build and fly.

Tricopter : A tricopter has three motors and three propellers. It is lightweight and uses a special mechanism for steering.

Hexacopter: A hexacopter has six motors and six propellers. It can carry heavier payloads and offers better stability than a quadcopter.

Octocopter: An octocopter has eight motors and eight propellers. It is used for professional applications that require high lifting capacity and reliability.

Fixed-Wing Drone: A fixed-wing drone looks like an airplane and uses wings to generate lift. It can fly longer distances with lower power consumption.

Hybrid VTOL Drone : A Hybrid VTOL (Vertical Take-Off and Landing) drone combines the features of a multirotor and a fixed-wing aircraft. It can take off vertically and fly efficiently over long distances.

How Drones Fly

Basic Aerodynamics: Aerodynamics is the study of how air interacts with a flying object. A drone flies by balancing four main forces: Lift, Weight, Thrust, and Drag.



Lift: Lift is the upward force that helps a drone rise into the air. It is produced when the propellers push air downward.

Weight: Weight is the downward force caused by gravity. The drone must generate enough lift to overcome its weight and fly.

Thrust: Thrust is the forward or upward force produced by the motors and propellers. It moves the drone in the desired direction.

Drag : Drag is the force that opposes the drone's movement through the air. It slows the drone down and increases power consumption.

Drone Motions

A drone moves in the air using four basic motions: Roll, Pitch, Yaw, and Throttle. These motions help the drone change its position and
direction.



Roll: Roll is the side-to-side movement of a drone. It makes the drone tilt left or right.

Pitch: Pitch is the forward and backward tilting movement of a drone. It helps the drone move forward or backward.

Yaw: Yaw is the rotation of a drone around its vertical axis. It changes the direction the drone is facing without moving its position.

Throttle : Throttle controls the speed of the motors. Increasing the throttle makes the drone climb, while decreasing it makes the drone descend.

Flight Principles: Flight principles explain how a drone remains balanced and flies smoothly in the air.

Clockwise (CW) Motors: Clockwise motors rotate in the clockwise direction. They are paired with clockwise propellers and help balance the rotational forces of the drone.

Counter-Clockwise (CCW) Motors: Counter-clockwise motors rotate in the opposite direction. They use counter-clockwise propellers and work together with CW motors to maintain stable flight.

Stability Concept

A drone remains stable when the lift produced by all motors is balanced. The flight controller continuously adjusts motor speeds to keep the drone level and prevent unwanted movements.

Common Stability Problems

1. Drone Tilts to One Side

- Cause: Unequal motor thrust, bent propeller, or unbalanced weight.
- Solution: Check motors, propellers, and weight distribution.

2. Excessive Vibration

- Cause: Damaged propellers, loose frame, or bent motor shaft.
- Solution: Replace damaged parts and tighten all screws.

3. Drone Spins Continuously (Yaw Drift)

- Cause: Wrong propeller installation or motor rotation direction.
- Solution: Verify motor directions and propeller positions.

4. Drone Drifts While Hovering

- Cause: Poor calibration or wind effects.
- Solution: Calibrate the flight controller and compass before flight.

5. Oscillation or Wobbling

- Cause: Incorrect PID tuning.
- Solution: Tune PID values or use default flight controller settings.

How Stability is Achieved ?

- Use correctly installed CW and CCW propellers.
- Ensure all motors produce equal thrust.
- Keep the center of gravity near the middle of the frame.
- Calibrate the flight controller, accelerometer, and compass.
- Use balanced propellers and a rigid frame.
- Properly tune PID settings.

Beginner Tip

A stable drone depends on three things:

1. **Balanced hardware**
2. **Correct wiring and setup**
3. **Proper flight controller calibration**

If any one of these is wrong, the drone may not fly properly even if all components are working. This is why most drone crashes during initial testing are caused by setup errors rather than component failures.

Drone Frames

Drone Frame: A drone frame is the main structure of the drone that holds all components such as motors, flight controller, battery, ESCs, and other electronics. It provides strength, stability, and protection during flight.

F330 Frame: The F330 is a small quadcopter frame with a motor-to-motor distance of approximately 330 mm. It is lightweight, affordable, and suitable for beginners who want to learn drone building and flying.

F450 Frame : The F450 is a popular quadcopter frame with a motor-to-motor distance of approximately 450 mm. It offers better stability, can carry larger batteries, and is ideal for learning autonomous drone development.

S500 Frame : The S500 is a larger quadcopter frame with a motor-to-motor distance of approximately 500 mm. It provides more space for electronics, supports higher payloads, and is commonly used for aerial photography, research, and advanced drone projects.



ComparisonTable

Frame	Size	Payload Capacity	Stability	Best For
F330	Small	Low	Moderate	Beginners
F450	Medium	Medium	Good	Learning & Autonomous Drones
S500	Large	High	Very Good	Research & Payload Applications

Beginner Tip: If you are building your first drone, the **F450** is often the best choice because it offers a good balance of cost, stability, durability, and upgrade options.

How to Select a Drone Frame?

The drone frame should be selected based on the mission or application. A larger frame can carry more weight, while a smaller frame is lighter and more agile.

1. Based on Payload

Payload includes cameras, sensors, batteries, delivery packages, and other equipment.

- **0–500 g Payload:** Small frames (250–330 mm)
- **500 g–2 kg Payload:** Medium frames (450–550 mm)
- **2 kg and Above:** Large frames (650 mm and above)

Rule: Higher payload requires a larger and stronger frame.

2. Based on Flight Time

- Small frames use smaller batteries and generally have shorter flight times.
- Large frames can carry larger batteries for longer endurance.

Rule: Longer flight time usually requires a larger frame.

3. Based on Application

Racing Drone

- Small frame
- Lightweight
- High speed and agility

Photography Drone

- Medium to large frame
- Stable flight
- Supports cameras and gimbals

Agriculture Drone

- Large frame
- High payload capacity
- Supports spray tanks

Mapping and Surveying

- Medium to large frame
- Long flight endurance
- Can carry GPS and mapping sensors

Delivery Drone

- Large frame
- Strong structure
- High lifting capability

Research and Autonomous Drone

- Medium to large frame
- Space for sensors, computers, and additional electronics

4. Based on Material

Plastic

- Cheap
- Lightweight
- Less durable

Carbon Fiber

- Very strong
- Lightweight
- Low vibration
- Most preferred material

Aluminum

- Strong
- Easy to manufacture
- Slightly heavier

Custom Drone Frame : A custom drone frame is a frame designed specifically for a particular mission instead of using ready-made frames.

Why Use a Custom Frame?

- To carry unique payloads
- To improve flight time
- To reduce weight
- To fit special sensors or equipment
- To optimize aerodynamics

Steps to Design a Custom Frame :

1. Define the mission.
2. Determine payload weight.
3. Select battery size.
4. Choose motor and propeller size.
5. Calculate required arm length.
6. Select frame material.
7. Design using CAD software.
8. Manufacture and test.

Common Mistakes in Frame Selection

- Choosing a frame that is too small for the payload.
- Ignoring battery weight.
- Using weak materials.
- Insufficient space for electronics.
- Poor center of gravity placement.

Beginner Design Rule

Before selecting a frame, answer these four questions:

1. What is the drone's mission?
2. How much payload will it carry?
3. How long should it fly?
4. What is the available budget?

The answers to these questions will determine the ideal frame size, material, and configuration for the drone. This is the first step in every professional drone design process.

Drone Frame Selection Based on Application

Application	Recommended Frame Size	Payload Capacity	Priority	Typical Frame Type
Learning & Practice	250–450 mm	Low	Low Cost, Easy Repair	Quadcopter
Racing	180–300 mm	Very Low	Speed & Agility	Quadcopter
Aerial Photography	450–650 mm	Medium	Stability & Camera Support	Quadcopter / Hexacopter
Mapping & Surveying	500–800 mm	Medium	Flight Time & Coverage	Quadcopter / Fixed-Wing
Agriculture Spraying	800–1800 mm	High	Payload Capacity	Hexacopter / Octocopter
Package Delivery	650–1500 mm	High	Payload & Reliability	Hexacopter / Octocopter
Search & Rescue	500–1000 mm	Medium	Endurance & Sensors	Quadcopter / Hexacopter
Industrial Inspection	450–800 mm	Medium	Stability & Precision	Quadcopter
Research & Development	Depends on Mission	Varies	Flexibility & Upgradability	Custom Frame

Autonomous Drone Projects	450–700 mm	Medium	Space for Electronics	Quadcopter
Long-Range Surveillance	1000 mm and Above	Medium	Endurance & Efficiency	Fixed-Wing / VTOL
Heavy-Lift Operations	1200 mm and Above	Very High	Maximum Payload	Octocopter
Custom Mission Drone	Calculated from Requirements	Varies	Mission-Specific Optimization	Custom Frame

Frame Selection Formula

Mission → Payload → Battery → Motors → Propellers → Frame Size

Professional drone designers always select the **frame last**, after defining the mission requirements and choosing the major components.

Drone Motors : Drone motors convert electrical energy from the battery into mechanical rotation. They spin the propellers to generate thrust and lift the drone into the air.

KV Rating : KV Rating indicates how many revolutions per minute (RPM) a motor will spin for every 1 volt applied without load.

Example:
A 1000 KV motor supplied with 11.1 V can theoretically spin at:

1000 × 11.1 = 11,100 RPM

Key Point:

- High KV = Higher speed, lower torque
- Low KV = Lower speed, higher torque

Brushless Motors

Brushless motors are the most commonly used motors in drones. They are efficient, powerful, reliable, and require less maintenance than brushed motors.

Advantages:

- High efficiency
- Long lifespan
- Low maintenance
- Better performance

Motor Selection Guide

Application	Recommended KV Range	Propeller Size
Racing Drone	1800–2800 KV	Small (3–6 inch)
Beginner Drone	800–1200 KV	Medium (8–10 inch)
Photography Drone	700–1000 KV	Medium to Large
Mapping Drone	600–1000 KV	Large
Agriculture Drone	100–500 KV	Very Large
Heavy-Lift Drone	80–400 KV	Very Large

Beginner Tip*

Low KV motors + Large propellers = More lifting power and longer flight time

High KV motors + Small propellers = More speed and agility

How to Select a Drone Motor ?

A drone motor should be selected based on the **drone weight, payload, propeller size, battery voltage, and application**.

Understanding Motor Codes

Example: **2212 Motor**

- **22** = Motor diameter (22 mm)
- **12** = Motor height (12 mm)

Larger motors generally produce more thrust and can spin larger propellers.

Motor Code	Size	Typical Use
1806	Small	Mini Racing Drones
2205 / 2207	Medium	FPV Racing Drones
2212	Medium	Beginner Drones
2216	Medium-Large	Photography Drones
2814	Large	Heavy-Lift Drones
4114 and Above	Very Large	Agriculture Drones

Motor Selection Steps

Step	What to Determine
1	Total Drone Weight
2	Required Payload
3	Battery Voltage
4	Propeller Size
5	Required Thrust

6	Motor KV Rating
7	Motor Size

Thrust Rule

For safe flight:

Total Thrust ≥ 2 × Total Drone Weight

Example:

Parameter	**Value**
Drone Weight	1 kg
Required Total Thrust	2 kg
Number of Motors	4
Thrust per Motor	500 g minimum

This ensures stable flight and good Flexibility

Motor Selection by Application

Application	**Motor Size**	**KV Range**
Beginner Drone	2212	920–1000 KV
Photography Drone	2216–2814	700–1000 KV
Mapping Drone	2814–3508	500–900 KV

Delivery Drone	3508–5010	300–700 KV
Agriculture Drone	6215–10020	80–300 KV



Simple Selection Rule

- **Light drone → Small motor → High KV**
- **Heavy drone → Large motor → Low KV**
- **Large propeller → Low KV motor**
- **Small propeller → High KV motor**

Beginner Tip

When selecting a motor, never look only at the motor code or KV rating. Always check the **manufacturer's thrust table**, which shows:

- Recommended propeller
- Battery voltage
- Current consumption
- Maximum thrust

The thrust table is the most reliable way to choose the correct motor for your drone.

ESC (Electronic Speed Controller)

An ESC is an electronic device that controls the speed of a brushless motor. It receives commands from the flight controller and adjusts the motor speed accordingly.

Purpose of an ESC

- Controls motor speed
- Starts and stops the motor
- Helps the drone perform roll, pitch, yaw, and throttle movements
- Converts battery power into controlled power for the motor
- Protects the motor from electrical issues

ESC Selection: The ESC should be selected based on the motor's maximum current consumption.

Selection Rule

ESC Current Rating > Motor Maximum Current



Example:

Motor Maximum Current	**Recommended ESC**
15 A	20–30 A ESC
20 A	30 A ESC
30 A	40 A ESC

40 A	50–60 A ESC

Always keep a safety margin of **20–30%** above the motor's maximum current.

Important ESC Specifications

Parameter	**Description**
Current Rating (A)	Maximum current the ESC can handle
Voltage Rating (S)	Supported battery voltage
Firmware	Software controlling ESC operation
BEC	Provides power to electronics (if available)
Weight	Important for drone performance

ESC Selection by Application

Application	**Typical ESC Rating**
Small Racing Drone	20–35 A
Beginner Drone	30–40 A
Photography Drone	30–60 A
Mapping Drone	40–60 A

Agriculture Drone	80–200 A

Beginner Tip

Before buying an ESC, check:

1. Motor maximum current
2. Battery voltage
3. ESC current rating

If the ESC rating is too low, it may overheat and fail during flight. Choosing the correct ESC Improves safety, reliability, and overall drone performance



Application	Typical Motor Size	KV Range	Battery	Recommended ESC
Mini FPV Racing Drone	1806–2207	1800–2800 KV	3S–6S	20–45 A
Beginner F330 Drone	2212	920–1000 KV	3S	20–30 A
Beginner F450 Drone	2212–2216	800–1000 KV	3S–4S	30 A
S500 Drone	2216–2814	700–1000 KV	4S	30–40 A
Photography Drone	2216–3508	500–900 KV	4S–6S	40–60 A
Mapping Drone	2814–3508	500–800 KV	4S–6S	40–60 A
Long-Endurance Drone	2814–4006	300–700 KV	4S–6S	40–80 A
Delivery Drone	3508–5010	200–700 KV	6S–12S	60–100 A
Industrial Inspection Drone	2814–4006	400–800 KV	4S–6S	40–80 A
Agriculture Drone (10–20 L)	6215–8017	100–300 KV	12S	80–120 A
Heavy-Lift Drone	6215–10020	80–250 KV	12S–14S	100–200 A
Custom Research Drone	Depends on Mission	Depends on Design	Depends on Design	ESC ≥ Motor Max Current + 20% Margin

Remember: Always choose an ESC with at least **20–30% higher current rating** than the motor's maximum current draw for safe and reliable operation.

Propellers

A propeller is a rotating blade attached to a motor. It pushes air downward to generate lift and thrust, allowing the drone to fly.

Propeller Size

Propeller size refers to the diameter of the propeller from one tip to the opposite tip. It is usually measured in inches.

Example:
A **10-inch propeller** has a diameter of 10 inches.

Key Point:

- Larger propellers produce more lift and efficiency.
- Smaller propellers provide higher speed and agility.

Propeller Pitch

Pitch is the distance a propeller would move forward in one complete rotation through a solid material.

Example:
In a **10×4.5 propeller**:

- **10** = Diameter (10 inches)
- **4.5** = Pitch (4.5 inches)

Key Point:

- Higher pitch = More speed, higher power consumption
- Lower pitch = Better efficiency and longer flight time

Propeller Selection Guide

Application	Typical Propeller Size	Typical Pitch
Mini Racing Drone	3–6 inch	3–5 inch
Beginner F330 Drone	8–9 inch	4–5 inch
Beginner F450 Drone	9–10 inch	4.5–5 inch
S500 Drone	10–12 inch	4.5–5.5 inch

Photography Drone	10–15 inch	4–6 inch
Mapping Drone	12–16 inch	4–6 inch
Long-Endurance Drone	12–18 inch	3–5 inch
Delivery Drone	15–24 inch	5–8 inch
Agriculture Drone	24–40 inch	6–12 inch
Heavy-Lift Drone	28–50 inch	8–15 inch

Quick Selection Rule

Requirement	**Recommended Choice**
More Flight Time	Large Diameter + Low Pitch
More Payload	Large Diameter + Medium Pitch
More Speed	Small Diameter + High Pitch
Beginner Drone	Medium Diameter + Medium Pitch



Beginner Tip: A propeller must always be selected according to the **motor manufacturer's recommendation**. Using a propeller that is too large can overheat the motor and ESC, while a propeller that is too small may produce insufficient thrust.

Motor KV vs Propeller vs Frame vs Application

Motor KV Range	Typical Propeller Size	Typical Frame Size	Common Applications
2500–3500 KV	2–4 inch	100–180 mm	Tiny Whoop, Micro Racing Drone
1800–2800 KV	4–6 inch	180–300 mm	FPV Racing, Freestyle Drone
1200–1800 KV	6–8 inch	250–350 mm	Sport Drone, Lightweight Camera Drone
900–1200 KV	8–10 inch	330–450 mm	Beginner Drone, F330, F450

700–1000 KV	10–12 inch	450–550 mm	S500, Photography Drone
500–800 KV	12–15 inch	500–700 mm	Mapping, Surveying, Autonomous Drone
300–600 KV	15–18 inch	650–900 mm	Long-Endurance, Industrial Inspection
200–500 KV	18–24 inch	800–1200 mm	Delivery Drone, Heavy Payload Drone
100–300 KV	24–40 inch	1000–1800 mm	Agriculture Sprayer Drone
80–200 KV	30–50 inch	1200 mm and Above	Heavy-Lift and Industrial Drones

Common Beginner Combinations

Frame	**Motor**	**KV**	**Propeller**
F330	2212	1000 KV	8×4.5 or 9×4.7
F450	2212	920–1000 KV	10×4.5
S500	2216	880–920 KV	10×4.5 or 11×4.7
650 mm Frame	2814	700–800 KV	12×4.5 or 13×5.5
Agriculture Frame	6215	170–300 KV	24–32 inch

Quick Rule

If You Need	Choose
More Speed	High KV + Small Propeller
More Flight Time	Low KV + Large Propeller
More Payload	Low KV + Large Propeller
Beginner Drone	920–1000 KV + 10-inch Propeller
Autonomous Research Drone	700–1000 KV + 10–15 inch Propeller

Easy Formula:
Higher KV → Smaller Propeller → Higher Speed
Lower KV → Larger Propeller → Higher Lift & Flight Time

Battery

The battery is the power source of a drone. It supplies electrical energy to the motors, ESCs, flight controller, and other electronic components.

LiPo Basics

LiPo (Lithium Polymer) batteries are the most commonly used batteries in drones. They are lightweight, provide high power output, and can be recharged many times.

Advantages:

- Lightweight
- High energy density
- High discharge rate
- Suitable for drone applications

Cell Count (S Rating)

The cell count indicates the number of cells connected in series inside a battery.

Voltage per LiPo Cell = 3.7 V (Nominal)

Battery	Voltage
1S	3.7 V
2S	7.4 V
3S	11.1 V
4S	14.8 V
6S	22.2 V
12S	44.4 V

Example:

A 3S LiPo battery contains 3 cells connected in series and provides 11.1 V nominal voltage.

Battery Safety

LiPo batteries must be handled carefully because they can catch fire if damaged or used incorrectly.

Safety Rules

- Never overcharge the battery.
- Never discharge below the recommended voltage.
- Use a LiPo-compatible charger.
- Store batteries in a cool and dry place.
- Stop using a swollen or damaged battery.
- Avoid puncturing or crushing the battery.
- Use a LiPo safety bag while charging.



Battery Configuration (S-Rating)	Nominal Voltage (V)	Typical Cell Count	Typical Capacity (mAh)	Discharge C-Rating	Recommended Drone Application	Estimated Flight Time Range (mins)	Compatible Motor KV Range
2S	7.4	2	850	30C	Biginner Series	10–20	100–180
3S	11.1	2–4	2200	50C	FPPV Racing Drone	10–40	120–130
4S	14.8	4	1500	75C	Aerial Photography Drone	14–60	150–160
6S	22.2	6	5000	60C	Delivery Drone	37–70	150–200
10S	37V	10+	0000	25C	Brushless Drone	53–80	200–200
12S	44.4	12+	16000	15C	Agricultural Drone	90–100	400–550

Battery Selection Guide

Application	Battery Type	Typical Cell Count
Tiny Drone	LiPo	1S–2S
FPV Racing Drone	LiPo	4S–6S
F330 Drone	LiPo	3S
F450 Drone	LiPo	3S–4S
S500 Drone	LiPo	4S
Photography Drone	LiPo	4S–6S

Mapping Drone	LiPo	4S–6S
Delivery Drone	LiPo / Li-Ion	6S–12S
Agriculture Drone	LiPo	12S–14S

Beginner Tip

When selecting a battery, consider:

1. **Voltage (Cell Count)**
2. **Capacity (mAh)**
3. **Discharge Rating (C Rating)**

A larger battery provides longer flight time but also increases the drone's weight. Always choose a battery recommended for your motor and propeller combination.

Drone Battery Selection Reference Table

Application	Frame Size	Typical Motor	KV Range	Propeller Size	Recommended Battery	Capacity (mAh)
Tiny Whoop Indoor	65 mm	0802	18000–25000 KV	31–40 mm	1S LiPo	300–550
Micro FPV	75 mm	1102	10000–15000 KV	2 inch	2S LiPo	450–650
Micro FPV	85 mm	1103	8000–12000 KV	2.5 inch	2S LiPo	450–850
Cinewhoop	95 mm	1404	3500–4500 KV	3 inch	4S LiPo	650–850
FPV Racing	210 mm	2205	2300–2700 KV	5 inch	4S LiPo	1300–1800

FPV Racing	220 mm	2207	1700–2100 KV	5 inch	6S LiPo	1000–1500
FPV Freestyle	250 mm	2306	1700–2500 KV	5 inch	4S–6S LiPo	1300–1800
FPV Long Range	280 mm	2507	1200–1800 KV	7 inch	6S Li-Ion	3000–5000
Lightweight Trainer	300 mm	2212	1000–1400 KV	8 inch	3S LiPo	2200–3000
Beginner Trainer	330 mm	2212	920–1000 KV	8–9 inch	3S LiPo	2200–4500
F330 Quadcopter	330 mm	2212	920–1000 KV	9 inch	3S LiPo	2200–4500
Compact Camera Drone	350 mm	2216	800–1000 KV	9–10 inch	4S LiPo	3000–5000
Educational Drone	380 mm	2212	920 KV	10 inch	3S LiPo	3000–5000
DIY Research Drone	400 mm	2216	800–950 KV	10 inch	4S LiPo	4000–5200
F450 Drone	450 mm	2212	920–1000 KV	10 inch	3S–4S LiPo	4500–5200

F450 Autonomous Drone	450 mm	2216	800–920 KV	10–11 inch	4S LiPo	5000–6000
S500 Drone	500 mm	2216	880–920 KV	10–12 inch	4S LiPo	5000–7000
Survey Drone	500 mm	2814	700–900 KV	12 inch	4S LiPo	6000–8000
Mapping Drone	550 mm	2814	700–800 KV	12–13 inch	4S LiPo	6000–10000
Inspection Drone	550 mm	3508	600–700 KV	13 inch	4S–6S LiPo	6000–12000
Thermal Camera Drone	550 mm	3508	580–700 KV	13 inch	6S LiPo	8000–12000
Search and Rescue	600 mm	3508	580–700 KV	13–15 inch	6S LiPo	8000–16000
Industrial Inspection	650 mm	4006	380–600 KV	15 inch	6S LiPo	10000–16000
Research UAV	650 mm	4008	380–520 KV	15–16 inch	6S LiPo	10000–22000
LiDAR Mapping Drone	680 mm	4008	380–520 KV	15 inch	6S LiPo	12000–22000

Long Endurance Quadcopter	700 mm	4114	320–480 KV	16–17 inch	6S Li-Ion	12000–30000
VTOL Prototype	700 mm	4114	320–450 KV	16 inch	6S LiPo	12000–22000
Heavy Camera Drone	750 mm	5010	300–400 KV	17–18 inch	6S LiPo	12000–22000
Delivery Prototype	800 mm	5010	280–400 KV	18 inch	6S–8S LiPo	16000–30000
Hexacopter Survey Drone	800 mm	5010	280–400 KV	18 inch	6S LiPo	16000–22000
Cargo Drone	900 mm	6215	170–300 KV	20–22 inch	8S LiPo	16000–30000
Heavy Inspection Drone	900 mm	6215	170–300 KV	21 inch	8S LiPo	22000–32000
Medical Delivery Drone	950 mm	6215	170–300 KV	22 inch	8S LiPo	22000–32000
Large Mapping Drone	1000 mm	6215	170–280 KV	22 inch	8S LiPo	22000–32000
Industrial Cargo Drone	1100 mm	7215	120–220 KV	24 inch	12S LiPo	16000–30000

Agricultural Drone 5L	1100 mm	6215	170 KV	24 inch	12S LiPo	16000–22000
Agricultural Drone 10L	1200 mm	7215	120–170 KV	28 inch	12S LiPo	22000–30000
Agricultural Drone 16L	1300 mm	8120	100–140 KV	30 inch	12S LiPo	22000–32000
Agricultural Drone 20L	1400 mm	8120	100–120 KV	32 inch	12S LiPo	30000
Agricultural Drone 30L	1500 mm	10020	80–120 KV	34 inch	14S LiPo	30000–32000
Agricultural Drone 40L	1600 mm	10020	80–120 KV	36 inch	14S LiPo	32000
Heavy Lift Drone	1200 mm	8017	100–170 KV	30 inch	12S LiPo	22000–32000
Heavy Lift Drone	1400 mm	10020	80–120 KV	34 inch	14S LiPo	30000–32000
Cinema Drone	1000 mm	6215	170 KV	22 inch	12S LiPo	16000–22000
Drone Taxi Prototype	1800 mm+	12030	60–100 KV	40 inch+	14S–18S LiPo	30000+
Fixed-Wing Trainer	1000 mm Wingspan	2216	900–1400 KV	9×6	3S LiPo	2200–3000

Fixed-Wing Mapping UAV	1500 mm Wingspan	2814	700–900 KV	10×6	4S LiPo	5000–10000
Fixed-Wing Long Range UAV	2000 mm Wingspan	3520	500–700 KV	12×8	6S Li-Ion	10000–30000
VTOL Mapping UAV	1800 mm Wingspan	3508 + VTOL Motors	500–700 KV	13 inch	6S LiPo	10000–22000
Autonomous Research UAV	Custom	Mission Dependent	Mission Dependent	Mission Dependent	Mission Dependent	Mission Dependent

Important Note

This table provides **practical starting values** used by hobbyists, researchers, and industry developers. Final battery selection should always be verified using:

1. Total drone weight
2. Required flight time
3. Motor thrust data
4. ESC current rating
5. Payload weight
6. Manufacturer recommendations

A professional drone designer selects the battery **after** choosing the frame, motor, propeller, and mission requirements.

Problems Caused by Wrong Component Selection

Component	Wrong Selection	Problems Faced
Frame	Too Small	Components do not fit, poor stability, overheating due to congestion
Frame	Too Large	Unnecessary weight, reduced flight time, higher cost
Motor	KV Too High	Excessive current draw, overheating, shorter flight time
Motor	KV Too Low	Insufficient thrust, poor maneuverability
Motor	Undersized Motor	Cannot lift payload, motor overheating, possible crash
Motor	Oversized Motor	Increased weight and cost, lower efficiency
ESC	Current Rating Too Low	ESC overheating, burnout, sudden power loss
ESC	Voltage Rating Too Low	ESC failure and possible damage
ESC	Oversized ESC	Extra weight and cost
Propeller	Too Large	Motor overheating, ESC overload, excessive current consumption
Propeller	Too Small	Low thrust, poor payload capacity
Propeller	Wrong Pitch	Reduced efficiency, unstable flight

Propeller	Unbalanced	Vibrations, poor flight stability, sensor errors
Battery	Voltage Too High	Motor and ESC damage if unsupported
Battery	Voltage Too Low	Poor performance and low thrust
Battery	Capacity Too Small	Very short flight time
Battery	Capacity Too Large	Excessive weight, reduced efficiency
Battery	Low C Rating	Voltage drop, battery heating, poor performance
Flight Controller	Incorrect Configuration	Unstable flight, crashes, poor control
Flight Controller	Wrong Orientation	Roll, pitch, and yaw errors
GPS Module	Poor Placement	Weak signal, inaccurate navigation
GPS Module	Magnetic Interference	Compass errors and fly-away risk
Receiver	Poor Signal Range	Loss of control and communication
Power Distribution Board	Underrated Current Capacity	Overheating and power failure
Landing Gear	Too Weak	Damage during landing
Frame Material	Too Flexible	Vibrations and unstable flight

Frame Material	Too Heavy	Reduced flight time and payload capacity
Payload	Too Heavy	Motor overload, reduced endurance, crash risk
Center of Gravity	Off-Center	Continuous drifting and instability
Wiring	Undersized Wires	Heating, voltage loss, fire risk
Wiring	Poor Connections	Intermittent failures and crashes

Common Symptoms and Likely Causes

Symptom	**Possible Cause**
Drone Cannot Take Off	Low thrust, small propeller, weak battery
Drone Wobbles in Air	Unbalanced propellers, poor PID tuning
Motors Become Hot	Wrong propeller, high KV motor, overload
ESC Becomes Hot	Underrated ESC, oversized propeller
Very Short Flight Time	Heavy battery, inefficient motor-prop combination
Drone Drifts While Hovering	Poor calibration, off-center weight
Sudden Crash During Flight	Battery sag, ESC failure, signal loss
Excessive Vibrations	Bent propeller, damaged motor, weak frame

Poor Payload Capacity	Small motors, small propellers
Slow Response	Low battery voltage, low thrust setup

Golden Rule of Drone Design

A drone is only as good as the **combination** of its components.

Motor + Propeller + ESC + Battery + Frame + Payload must all be matched correctly. Even one poorly selected component can reduce performance, shorten flight time, cause instability, or lead to a crash. This matching process is called **system integration**, and it is one of the most important skills in drone engineering.

Mathematical Formulas Used in Drone Design

Understanding these relationships helps beginners select compatible components and avoid trial-and-error design.

1. Total Thrust Requirement

A drone must produce more than its weight to fly.

$$T_{total} \geq 2\,W$$

Where:

- (T_{total}) = Total thrust of all motors
- (W) = Total drone weight

Proportionality

- Weight ↑ → Required Thrust ↑
- Payload ↑ → Required Thrust ↑

Example 1: Beginner Drone

Parameter	**Value**
Drone Weight	1 kg
Required Total Thrust	2 kg
Motors	4

Thrust per motor:

500 g per motor

Example 2: Delivery Drone

Parameter	**Value**
Total Weight	6 kg
Required Total Thrust	12 kg
Motors	6

Thrust per motor:

2000 g per motor

2. Motor KV and RPM

Motor speed depends on KV and battery voltage.

$$RPM = KV \times V$$

Where:

- KV = Motor KV Rating
- V = Battery Voltage

Proportionality

- KV ↑ → RPM ↑
- Voltage ↑ → RPM ↑

Example 1

1000 KV Motor + 3S Battery

11.1 × 1000

RPM ≈ 11,100

Example 2

800 KV Motor + 6S Battery

22.2 × 800

RPM ≈ 17,760

3. Battery Energy

Battery energy determines available flight energy.

$$E = V \times A\text{h}$$

Where:

- E = Energy (Wh)
- V = Voltage
- Ah = Capacity

Proportionality

- Capacity ↑ → Flight Time ↑
- Voltage ↑ → Available Energy ↑

Example 1

3S 2200 mAh

11.1 × 2.2

Energy = 24.42 Wh

Example 2

4S 5200 mAh

14.8 × 5.2

Energy = 76.96 Wh

4. Flight Time

Approximate flight time:

$$Flight\ Time = \frac{Battery\ Capacity}{Average\ Current} \times 60$$

Example 1

2200 mAh Battery

Current = 10 A

Flight Time

≈ 13.2 minutes

Example 2

10000 mAh Battery

Current = 20 A

Flight Time

≈ 30 minutes

5. ESC Selection

ESC current rating must exceed motor current.

Formula:

ESC Rating ≥ Motor Maximum Current × 1.3

Proportionality

- Motor Current ↑ → ESC Rating ↑

Example 1

Motor Current = 20 A

ESC

20 × 1.3 = 26 A

Use 30 A ESC

Example 2

Motor Current = 40 A

ESC

40 × 1.3 = 52 A

Use 60 A ESC

6. Propeller Size and Thrust

General Relationship:

Thrust ∝ Propeller Diameter²

Proportionality

- Larger Propeller → More Thrust
- Larger Propeller → Lower Efficiency Loss
- Larger Propeller → Lower Required RPM

Example 1

10-inch Propeller

Produces more thrust than 8-inch propeller at same RPM.

Example 2

28-inch Agriculture Propeller

Produces much more thrust than 10-inch propeller.

7. Payload and Flight Time

Relationship:

Payload ↑ → Current Consumption ↑

Payload ↑ → Flight Time ↓

Example 1

1 kg Drone

Payload = 0 g

Flight Time = 20 min

Example 2

Same Drone

Payload = 500 g----------> Flight Time = 14 min

8. Frame Size and Propeller Size

Relationship:

Frame Size ↑ → Larger Propeller Possible

Example 1

F330

Suitable Propeller

8–9 inch

Example 2

Agriculture Frame

Suitable Propeller

28–40 inch

Component Relationships Summary

Component Increases	**Effect**
Payload	Required Thrust Increases
Payload	Battery Consumption Increases

Payload	Flight Time Decreases
Motor KV	RPM Increases
Battery Voltage	RPM Increases
Propeller Diameter	Thrust Increases
Battery Capacity	Flight Time Increases
Frame Size	Larger Propellers Possible
Propeller Size	Motor Current Increases
Motor Current	ESC Rating Must Increase
Battery Weight	Total Weight Increases
Total Weight	Required Thrust Increases

Complete Drone Design Chain

Mission → Payload → Required Thrust → Frame Size → Motor Selection → Propeller Selection → ESC Selection → Battery Selection → Flight Time Estimation

This is the same design sequence followed in professional drone engineering. Every component affects the others, so no component should be selected independently. A change in payload, battery, motor, or propeller will influence the entire drone system.

Component Relationships and Proportionalities in Drone Design

Drone design is a system engineering problem. Every component affects multiple other components. Understanding these relationships helps you design efficient drones instead of randomly selecting parts.

1. Payload ↔ Motor

Relationship

Payload ∝ Required Motor Thrust

(Payload increases → Motor thrust requirement increases)

Payload Increases	**Effect**
More Weight	Larger Motors Needed
More Weight	Higher Current Draw
More Weight	Larger Propellers Needed
More Weight	Bigger Battery Needed



Example

Payload = Camera (200 g)

Motor: 2212 1000KV

Payload = Spray Tank (5 kg)

Motor: 6215 170KV

2. Payload ↔ Battery

Relationship

Payload ↑ → Flight Time ↓

because more power is required.

Payload	**Current Consumption**
Low	Low
High	High

Real Example

Same Drone:

- No Payload → 25 min
- 1 kg Payload → 16 min

3. Payload ↔ Frame

Relationship

Payload ↑ → Frame Size ↑

Payload	**Frame Requirement**
200 g	F330
500 g	F450
2 kg	650 mm

10 kg	Agriculture Frame

4. Motor KV ↔ Propeller Size

Relationship

KV ∝ 1 / Propeller Size

(Inverse Relationship)

Motor KV	**Propeller**
High KV	Small Propeller
Low KV	Large Propeller

Why?

High KV motors spin very fast.

Large propellers create heavy load.

Combining both can burn the motor.

Example

2200 KV → 5 inch

920 KV → 10 inch

170 KV → 32 inch

5. Motor KV ↔ Torque

Relationship

KV ∝ 1 / Torque

KV	**Torque**
High	Low
Low	High

Example

2207 2400KV

Very fast

Low torque

6215 170KV

Slower

Very high torque

6. Motor Size ↔ Thrust

Relationship

Motor Size ↑ → Thrust ↑

Motor	**Typical Thrust**
1806	500 g
2212	1000 g
2814	2000 g
6215	7000+ g

7. Propeller Diameter ↔ Thrust

Relationship

Propeller Diameter ↑ → Thrust ↑

Propeller	**Thrust**
5 inch	Low

10 inch	Medium
30 inch	Very High

Result

Bigger propellers move more air.

More air moved = More lift.

8. Propeller Diameter ↔ Current Consumption

Relationship

Propeller Diameter ↑ → Current Draw ↑

Propeller	**Current**
Small	Low
Large	High

Example

10 inch prop : Motor current = 12 A

15 inch prop : Motor current = 22 A

9. Propeller Pitch ↔ Speed

Relationship

Pitch ↑ → Speed ↑

Pitch	**Result**
Low	Efficient
High	Fast

Example

10×4.5

Better endurance

10×8

Higher speed

10. Motor Current ↔ ESC Rating

Relationship

Motor Current ↑ → ESC Rating ↑

Motor Current	ESC
20 A	30 A
30 A	40 A
40 A	60 A

11. Battery Voltage ↔ Motor RPM

Relationship

Voltage ↑ → RPM ↑

Battery voltage directly affects the speed of a drone motor. As voltage increases, the motor spins faster, producing higher RPM and more thrust. The relationship is given by:

RPM = KV × Voltage (V)

From:

RPM=KV\times V

Example

1000 KV + 3S

≈11100 RPM

1000 KV + 6S

≈22200 RPM

Note: Higher voltage provides greater speed and power but also increases current consumption, heat generation, and mechanical stress on the motor and propeller. Always ensure the motor, ESC, and propeller are rated for the selected battery voltage.

12. Battery Capacity ↔ Flight Time

Relationship

Battery Capacity ↑ → Flight Time ↑

Capacity	**Flight Time**
2200 mAh	Low
5200 mAh	Medium
22000 mAh	High

13. Battery Capacity ↔ Weight

Relationship

Battery Capacity ↑ → Weight ↑

This creates a tradeoff.

Capacity	**Weight**
Small	Light
Large	Heavy

Engineering Problem

Large battery gives:	But also:
✓ More flight time	✗ More weight

14. Frame Size ↔ Propeller Size

Relationship

Frame Size ↑ → Propeller Size ↑

Frame	**Propeller**
F330	8–9 inch
F450	10 inch
S500	10–12 inch
1200 mm	24–30 inch

15. Frame Size ↔ Payload

Relationship

Frame Size ↑ → Payload Capacity ↑

Because larger frames:

- Use larger motors
- Use larger propellers
- Carry larger batteries

16. Total Weight ↔ Flight Time

Relationship: **Weight ↑ → Flight Time ↓**

Weight	**Flight Time**
Low	High
High	Low

17. Weight ↔ Required Thrust

Relationship : **Weight ↑ → Required Thrust ↑**

From: $T_{total} \geq 2W$

Master Drone Design Dependency Chain

Payload ↑

↓

Required Thrust ↑

↓

Motor Size ↑

↓

Propeller Size ↑

↓

Current Consumption ↑

↓

ESC Rating ↑

↓

Battery Size ↑

↓

Battery Weight ↑

↓

Total Drone Weight ↑

↓

Required Thrust Further ↑

This loop is the core of drone engineering. Every professional drone designer continuously balances **payload, thrust, battery weight, flight time, cost, and efficiency** to achieve the desired mission.

Flight Controller

A flight controller is the **brain of the drone**. It receives data from sensors, processes pilot commands, and controls the motors to keep the drone stable and flying safely.

Functions of a Flight Controller

- Controls motor speed
- Maintains drone stability
- Processes sensor data
- Executes autonomous missions
- Controls GPS navigation
- Manages flight modes
- Records flight data

Flight Controller

A flight controller is the **brain of the drone**. It receives data from sensors and pilot commands, then controls the motors to keep the drone stable and flying correctly.

Types of Flight Controllers

Type	**Purpose**
Basic Stabilization Controller	Manual flying and stabilization
GPS Flight Controller	Position hold and navigation
Autonomous Flight Controller	Waypoint missions and automation
FPV Flight Controller	Racing and freestyle drones
Educational Flight Controller	Learning and research
Industrial Flight Controller	Commercial and professional applications
Open-Source Flight Controller	Custom development and experimentation

AI Flight Controller	Autonomous and intelligent drones

Popular Flight Controllers (35+)



Flight Controller	**Best For**
KK2.1.5	Absolute Beginners
MultiWii	Learning Drone Basics
Naze32	Basic FPV Drones
CC3D	Beginners
SP Racing F3	FPV

Omnibus F4	FPV
Matek F405	FPV & Fixed Wing
Matek F722	Advanced FPV
SpeedyBee F405	Budget FPV
SpeedyBee F7	FPV & GPS
Kakute F4	FPV
Kakute F7	FPV
Kakute H7	Professional FPV
Pixhawk 2.4.8	Students & Researchers
Pixhawk 4	Autonomous Drones
Pixhawk 4 Mini	Compact UAVs
Pixhawk 5X	Professional UAVs
Pixhawk 6C	Research
Pixhawk 6X	Advanced Research
Cube Orange	Industrial UAVs
Cube Orange+	Professional Applications

Cube Purple	Research
Cube Blue	Enterprise Drones
CUAV V5+	Autonomous UAVs
CUAV V5 Nano	Compact UAVs
CUAV X7	Research UAVs
CUAV X7+	Industrial UAVs
Holybro Durandal	Research
Holybro Pix32	Educational Projects
Holybro Pixhawk 6X	Advanced UAVs
Radiolink Crossflight	Beginners
DJI Naza M Lite	Hobby Drones
DJI Naza M V2	Camera Drones
DJI A3	Professional UAVs
DJI N3	Commercial Drones
DJI WooKong-M	Industrial UAVs
DJI Ace One	Helicopters

Vector Flight Controller	Fixed Wing UAVs
Eagle Tree Vector	Mapping UAVs
Ardupilot Boards	Open Source UAVs
Navio2	Raspberry Pi UAVs
VOXL Flight Deck	AI Drones
Skynode	Autonomous UAVs
ModalAI FC	AI Research
Betaflight F7	FPV Racing



Flight Controller Selection Table

Application	**Recommended Flight Controller**
First Drone	KK2.1.5, CC3D
F330 Learning Drone	Radiolink Crossflight, Pixhawk 2.4.8
F450 Learning Drone	Pixhawk 2.4.8
Autonomous Drone	Pixhawk 4, Pixhawk 6C
Mapping Drone	Cube Orange, Pixhawk 6X

Survey Drone	Pixhawk 6C
Delivery Drone	Cube Orange+, CUAV X7
Agriculture Drone	Cube Orange, Pixhawk 6X
FPV Racing Drone	SpeedyBee F405, Kakute F7
FPV Freestyle	SpeedyBee F7, Kakute H7
Fixed Wing UAV	Matek F405-Wing
VTOL UAV	Pixhawk 6X
Research Project	Pixhawk 6C, Cube Orange
AI Drone	VOXL Flight Deck
Industrial UAV	Cube Orange+, CUAV X7+
Drone Swarm Research	Pixhawk 6X
Drone Startup Prototype	Pixhawk 6C
ISRO/DRDO Student Research	Cube Orange, Pixhawk 6X

How to Select a Flight Controller

Requirement	Recommended Choice
Lowest Cost	KK2.1.5
Beginner Learning	Radiolink Crossflight
Autonomous Missions	Pixhawk Series
GPS Navigation	Pixhawk, Cube
Drone Delivery	Cube Orange
Agriculture Spraying	Cube Orange+
FPV Racing	SpeedyBee F405
Fixed Wing	Matek F405-Wing
AI Integration	VOXL Flight Deck
ROS Integration	Pixhawk 6X
Companion Computer Support	Cube Orange
Research Publications	Pixhawk 6C
Startup Development	Cube Orange+
Future Scalability	Pixhawk 6X

Flight Controller Selection Based on Budget

Budget	Recommended Controller
Below ₹2,000	KK2.1.5, CC3D
₹2,000–₹5,000	Radiolink Crossflight
₹5,000–₹10,000	Pixhawk 2.4.8
₹10,000–₹20,000	Pixhawk 4
₹20,000–₹40,000	Pixhawk 6C
₹40,000–₹80,000	Cube Orange
Above ₹80,000	Cube Orange+, CUAV X7+

Beginner Recommendation

Level	Best Choice
Hobbyist	Radiolink Crossflight
Student	Pixhawk 2.4.8
Research Student	Pixhawk 6C
Startup Founder	Cube Orange
Industrial UAV Developer	Cube Orange+

For most engineering students building autonomous drones, **Pixhawk 2.4.8** is the best low-cost starting point, while **Pixhawk 6C** or **Cube Orange** are ideal for advanced research, mapping, delivery, agriculture, and startup-grade UAV development.

Sensors Inside a Flight Controller :

A flight controller contains several sensors that help the drone understand its position, orientation, movement, and environment. These sensors act as the **eyes and ears** of the drone.

Sensor	**Full Name**	**Purpose**	**What Happens if Absent?**
Accelerometer	Acceleration Sensor	Measures tilt and acceleration	Drone cannot determine level position accurately
Gyroscope	Angular Velocity Sensor	Measures rotation around Roll, Pitch, and Yaw axes	Drone becomes unstable and difficult to control
Magnetometer	Digital Compass	Determines heading and direction	GPS navigation becomes inaccurate
Barometer	Pressure Sensor	Measures altitude using air pressure	Poor altitude hold performance
GPS Module*	Global Positioning System	Provides location, speed, and navigation	No autonomous navigation or position hold
Airspeed Sensor*	Measures Airspeed	Used mainly in fixed-wing UAVs	Less accurate speed estimation
Rangefinder / LiDAR*	Distance Sensor	Measures distance from ground or obstacles	Poor low-altitude precision
Optical Flow Sensor*	Motion Tracking Sensor	Detects movement relative to the ground	Poor indoor positioning

Current Sensor	Electrical Current Sensor	Measures battery current consumption	No accurate battery monitoring
Voltage Sensor	Voltage Sensor	Monitors battery voltage	Risk of over-discharging battery
Temperature Sensor	Temperature Monitoring	Monitors controller temperature	Possible overheating issues

*Usually connected externally, not always built into the flight controller.

Most Important Sensors for a Beginner Drone

Sensor	**Importance**
Gyroscope	Essential
Accelerometer	Essential
Magnetometer	Very Important
Barometer	Important
GPS	Optional for manual flight, essential for autonomous flight

Accelerometer:

Purpose

Measures linear acceleration and tilt.

Uses

- Self-leveling
- Angle mode flying
- Detecting drone orientation

Example

If the drone tilts forward, the accelerometer detects the change and helps the flight controller stabilize the drone.

Gyroscope:

Purpose

Measures rotational speed.

Uses

- Stabilization
- Roll, Pitch, and Yaw control
- Fast attitude correction

Example

When wind tilts the drone, the gyroscope detects the rotation and the flight controller adjusts motor speeds to restore balance.

Magnetometer (Compass):

Purpose

Determines the drone's heading relative to Earth's magnetic field.

Uses

- Navigation
- Return-to-Home (RTH)
- Waypoint missions

Example : GPS tells the drone where it is, while the compass tells it which direction it is facing.

Barometer:

Purpose

Measures atmospheric pressure.

Uses

- Altitude hold
- Automatic takeoff and landing
- Height estimation

Example

If the drone rises unexpectedly, the barometer detects the altitude change and helps maintain the desired height.

GPS:

Purpose

Provides position coordinates.

Uses

- Position Hold
- Return-to-Home
- Autonomous missions
- Mapping

Example : If the pilot loses signal, GPS allows the drone to return automatically to the takeoff location.

Optical Flow Sensor:

Purpose : Tracks movement by observing the ground.

Uses

- Indoor hovering
- GPS-denied environments

Example

A warehouse drone can maintain position indoors without GPS.

Rangefinder / LiDAR:

Purpose : Measures distance to objects or ground.

Uses

- Terrain following
- Precision landing
- Obstacle avoidance

Example

Agriculture drones use LiDAR to maintain a constant height above crops.

Current Sensor:

Purpose: Measures battery current draw.

Uses

- Power monitoring
- Flight time estimation

Example

The flight controller can warn the pilot when excessive current is being drawn.

Voltage Sensor:

Purpose : Measures battery voltage.

Uses

- Low battery warning
- Battery health monitoring

Example

The drone can trigger Return-to-Home when the battery voltage becomes too low.

Sensor Fusion

A flight controller does not rely on a single sensor. Instead, it combines data from multiple sensors to make accurate decisions.

Example

Sensor	**Information Provided**
Gyroscope	Rotation
Accelerometer	Tilt
Magnetometer	Direction
Barometer	Altitude
GPS	Position

The process of combining data from multiple sensors is called **Sensor Fusion**.

Sensor Importance in Different Applications

Application	**Required Sensors**
Basic Manual Drone	Gyroscope, Accelerometer
Beginner GPS Drone	Gyroscope, Accelerometer, Compass, GPS
Mapping Drone	Gyroscope, Accelerometer, Compass, GPS, Barometer
Delivery Drone	GPS, Compass, Barometer, Current Sensor
Agriculture Drone	GPS, Compass, Barometer, LiDAR
FPV Racing Drone	Gyroscope, Accelerometer

Indoor Drone	Gyroscope, Accelerometer, Optical Flow
Autonomous Research Drone	All Available Sensors

Beginner Tip

The **Gyroscope** and **Accelerometer** are the most critical sensors. Together they form the **IMU (Inertial Measurement Unit)**, which is the foundation of drone stability. Without a properly functioning IMU, a drone cannot fly safely.

GPS (Global Positioning System)

GPS is a satellite-based navigation system that helps a drone determine its location, altitude, speed, and direction anywhere on Earth.

Why is GPS Important?

GPS allows a drone to know **where it is** and helps it fly autonomously without constant pilot **control.**

Uses of GPS in Drones

Use	**Description**
Position Hold	Keeps the drone fixed at one location
Return-to-Home (RTH)	Automatically returns the drone to the takeoff point
Waypoint Navigation	Flies through pre-planned locations
Autonomous Missions	Performs tasks without pilot intervention
Mapping & Surveying	Records accurate geographical locations
Speed Measurement	Calculates ground speed
Tracking	Monitors drone position in real time
Geofencing	Prevents drone from entering restricted areas

How GPS Works

1. GPS satellites continuously transmit signals.
2. The GPS module on the drone receives signals from multiple satellites.
3. The module calculates its position using these signals.
4. The flight controller uses this information for navigation and autonomous flight.

Component	Function
GPS Receiver	Receives satellite signals
Antenna	Captures GPS signals
Compass (Magnetometer)	Determines drone heading
Flight Controller	Processes GPS data

Popular GPS Modules



GPS Module	**Suitable For**
BN-180	Beginners
BN-220	Small Drones
BN-280	FPV Drones
M8N GPS	Most Hobby and Research Drones
M9N GPS	Advanced Autonomous Drones
Here 3 GPS	Professional UAVs
Here 4 GPS	Industrial Applications
CUAV NEO 3 Pro	Mapping & Survey Drones
Holybro M8N	Pixhawk Projects
Holybro M9N	High-Accuracy Navigation

GPS Selection Guide

Application	Recommended GPS
Beginner Drone	BN-220
F450 Drone	M8N GPS
Autonomous Drone	M8N / M9N
Mapping Drone	Here 3
Agriculture Drone	Here 3 / Here 4
Delivery Drone	Here 4
Research Drone	CUAV NEO 3 Pro
Industrial UAV	Here 4

GPS Accuracy

GPS Type	Typical Accuracy
Standard GPS	2–5 m
GPS + GLONASS	1–3 m
GPS + Galileo	1–2 m
RTK GPS	1–5 cm

Common GPS Problems

Problem	**Cause**	**Solution**
No GPS Lock	Poor satellite visibility	Move to open area
Slow GPS Lock	Weak signal	Wait longer before takeoff
Position Drift	Low satellite count	Ensure 10+ satellites
Compass Error	Magnetic interference	Calibrate compass
Fly Away Risk	Incorrect GPS/Compass setup	Perform calibration before flight

Satellite Requirements

Satellite Count	**Flight Quality**
Below 6	Not Recommended
6–10	Basic GPS Lock
10–15	Good Navigation
15–25+	Excellent Accuracy

GPS Constellations

Modern GPS modules can use multiple satellite systems.

System	Country/Region
GPS	United States
GLONASS	Russia
Galileo	European Union
BeiDou	China
NavIC	India

Using multiple satellite systems improves accuracy and reliability.

GPS vs Compass

GPS	Compass
Tells where the drone is	Tells which direction the drone is facing
Uses satellites	Uses Earth's magnetic field
Used for navigation	Used for heading information

Example

- GPS says: "You are at this location."
- Compass says: "You are facing north."

Both are required for accurate autonomous flight.

Beginner Recommendation

Budget Level	Recommended GPS
Low Budget	BN-220
Student Projects	M8N GPS
Research Projects	M9N GPS
Professional UAVs	Here 3
Industrial UAVs	Here 4

Beginner Tip

For most **F450, S500, Pixhawk 2.4.8, and student autonomous drone projects**, the **M8N GPS** provides the best balance of cost, reliability, satellite reception, and ease of use. It is one of the most widely used GPS modules in hobby, academic, and research drone applications.

Telemetry

Telemetry is a wireless communication system that allows a drone to send flight data to a Ground Control Station (GCS), laptop, tablet, or mobile device in real time.

Why is Telemetry Important?

Telemetry helps the pilot monitor the drone's status without physically connecting to it.

Uses of Telemetry

Use	Description
Real-Time Monitoring	View live flight data
Mission Planning	Upload waypoint missions
Parameter Tuning	Change flight controller settings
Flight Logging	Record flight data

Battery Monitoring	Monitor voltage and current
GPS Monitoring	Check location and satellite count
Autonomous Missions	Start and monitor automated flights
Troubleshooting	Diagnose drone problems

Information Sent Through Telemetry

Data Type	**Example**
Battery Voltage	15.2 V
Current Consumption	12 A
GPS Coordinates	Latitude & Longitude
Altitude	50 m
Speed	10 m/s
Flight Mode	Loiter, Auto, RTL
Satellite Count	15 Satellites
Compass Status	Healthy
Distance from Home	200 m

How Telemetry Works

Drone

↓

Flight Controller

↓

Telemetry Module

↓ Wireless Link

Ground Station

(QGroundControl / Mission Planner)

The telemetry module sends and receives data between the drone and the ground station.

Popular Telemetry Modules



Telemetry Module	Frequency	Range
SiK Telemetry V3	433 MHz	1–3 km
SiK Telemetry V4	433 MHz	2–5 km
Holybro Telemetry	433/915 MHz	2–10 km
RFD900x	900 MHz	20–40+ km
RFD868x	868 MHz	20–40+ km
Herelink	2.4 GHz	10–20 km
Wi-Fi Telemetry	2.4 GHz	50–200 m
ESP32 Telemetry	Wi-Fi	Short Range
LTE/4G Telemetry	Cellular Network	Virtually Unlimited

Telemetry Selection Guide

Application	Recommended Telemetry
Learning Drone	433 MHz SiK
F450 Autonomous Drone	Holybro Telemetry
Mapping Drone	Holybro Telemetry
Agriculture Drone	Herelink

Delivery Drone	RFD900x
Research UAV	RFD900x
Industrial UAV	LTE/4G Telemetry
Long-Range UAV	RFD900x

Common Telemetry Frequencies

Frequency	**Characteristics**
433 MHz	Long range, widely used
868 MHz	Long range, Europe
915 MHz	Long range, USA and many UAV applications
2.4 GHz	High data rate, shorter range
LTE/4G	Uses mobile network coverage

Telemetry vs Radio Controller

Telemetry	**Radio Controller**
Sends flight data	Sends pilot commands
Used for monitoring	Used for flying
Connects to laptop/mobile	Connects to transmitter

Optional for manual flight	Essential for manual flight

Example

- Radio Controller → "Fly forward"
- Telemetry → "Battery = 14.8 V, Altitude = 50 m"

Common Telemetry Problems

Problem	**Cause**	**Solution**
No Connection	Wrong baud rate or wiring	Verify settings
Short Range	Poor antenna placement	Reposition antenna
Data Loss	Signal interference	Change location/frequency
Frequent Disconnects	Weak power supply	Check wiring and power
Slow Data Updates	Low telemetry speed	Increase data rate

Beginner Recommendation

User Type	**Recommended Telemetry**
Hobbyist	433 MHz SiK Telemetry
Student Projects	Holybro Telemetry
Pixhawk 2.4.8 Users	433 MHz SiK Telemetry
Research Projects	RFD900x
Industrial UAVs	Herelink or LTE Telemetry

Beginner Tip

For most student projects using **Pixhawk 2.4.8**, **Mission Planner**, and **F450/S500 drones**, a **433 MHz SiK Telemetry module** is the most affordable and practical option. It allows real-time monitoring, mission upload, parameter tuning, and autonomous flight testing directly from a laptop.

Radio Transmitter (Remote Controller)

A Radio Transmitter (Tx) is a handheld device used by the pilot to control the drone. It sends commands wirelessly to the receiver on the drone.

Why is a Radio Transmitter Important?

The transmitter allows the pilot to control:

- Throttle (Up/Down)
- Roll (Left/Right Tilt)
- Pitch (Forward/Backward Movement)
- Yaw (Rotation)

Without a transmitter, manual control of the drone is not possible.

Main Components of a Radio Transmitter

Component	Function
Joysticks (Gimbals)	Control drone movement
Switches	Change flight modes
Antenna	Transmits radio signals
Display Screen	Shows settings and status
Battery	Powers the transmitter
RF Module	Generates radio signals

Channels in a Transmitter

A channel is a separate control signal sent to the drone.

Channel	Function
CH1	Roll
CH2	Pitch
CH3	Throttle
CH4	Yaw
CH5	Flight Mode

CH6	Return-to-Home
CH7+	Camera, Payload, Special Functions

Rule

More channels = More features and accessories can be controlled.

Popular Radio Transmitters

Radio Transmitter	**Channels**	**Best For**
FlySky FS-i6	6–10	Beginners
FlySky FS-i6X	10	Beginners
FlySky FS-i10	10	Hobby Projects
Radiolink AT9S Pro	12	Autonomous Drones
Radiolink AT10II	12	Advanced Hobbyists
Radiomaster Pocket	16+	Students & FPV
Radiomaster Boxer	16+	FPV & Research
Radiomaster TX12	16+	Portable Use
Radiomaster Zorro	16+	FPV Pilots
Radiomaster TX16S	16+	Professional Use

FrSky Taranis X9D Plus	16+	FPV & Research
FrSky X-Lite	16+	FPV Racing
Jumper T-Pro	16+	Portable FPV
Futaba 14SG	14	Professional UAVs
Futaba 16IZ	16	Industrial UAVs
Futaba 18SZ	18	Enterprise UAVs

Receiver Compatibility



A transmitter requires a compatible receiver.

Transmitter Brand	Compatible Receiver
FlySky	FS-iA6B, X6B
Radiolink	R6FG, R8EF
FrSky	X8R, RXSR
Radiomaster ELRS	ELRS Receivers
Futaba	Futaba Receivers

Radio Protocols

Protocol	Features
AFHDS 2A	FlySky System
ELRS (ExpressLRS)	Long Range, Low Latency
FrSky ACCST	Popular FPV Protocol
FrSky ACCESS	Improved FrSky Protocol
CRSF	Long Range and Fast Response
SBUS	Digital Communication
PPM	Older Analog Method

Transmitter Selection Guide

Application	Recommended Transmitter
Beginner Drone	FlySky FS-i6X
F330 Drone	FlySky FS-i6X
F450 Drone	Radiolink AT9S Pro
S500 Drone	Radiolink AT9S Pro
Autonomous Drone	Radiolink AT9S Pro
FPV Racing	Radiomaster Pocket
FPV Freestyle	Radiomaster Boxer
Mapping Drone	Radiomaster TX16S
Research Drone	TX16S / Boxer
Agriculture Drone	TX16S
Delivery Drone	TX16S
Industrial UAV	Futaba 16IZ

Range Comparison

System	Typical Range
FlySky	500 m – 2 km
Radiolink	2–4 km
FrSky	2–10 km
ELRS	5–50+ km
Futaba	2–10 km

Common Problems

Problem	Cause	Solution
No Connection	Receiver not bound	Re-bind receiver
Short Range	Poor antenna placement	Reposition antennas
Signal Loss	Interference	Fly in open areas
Control Delay	Weak signal	Improve link quality
Unexpected Failsafe	Receiver power issue	Check power supply

Beginner Recommendation

Budget	Recommended Radio
₹3,000–₹6,000	FlySky FS-i6X
₹6,000–₹10,000	Radiomaster Pocket ELRS
₹10,000–₹18,000	Radiomaster Boxer ELRS
₹18,000+	Radiomaster TX16S

Beginner Tip

For new drone builders and engineering students, **Radiomaster Pocket ELRS** offers one of the best combinations of price, range, reliability, future compatibility, and upgrade potential. For larger autonomous drones using Pixhawk, the **Radiomaster Boxer** or **TX16S** are excellent long-term choices.

Receiver (Rx)

A receiver is an electronic device mounted on the drone that receives commands from the radio transmitter and passes them to the flight controller.

Simple Working Principle

Pilot Moves Stick

↓

Radio Transmitter (Tx)

↓

Wireless Signal

↓

Receiver (Rx)

↓

Flight Controller

↓

ESC

↓

Motors

The receiver acts as a **bridge between the transmitter and flight controller**.

How a Receiver Works

Step	Process
1	Pilot moves transmitter sticks
2	Transmitter converts commands into radio signals
3	Receiver receives signals through antenna
4	Receiver decodes the signals
5	Commands are sent to the flight controller
6	Flight controller adjusts motor speeds
7	Drone moves accordingly

Types of Receivers

Receiver Type	Description	Application
PWM Receiver	Individual wire for each channel	Older drones
PPM Receiver	Single signal wire	Basic hobby drones
SBUS Receiver	Digital communication	Modern drones
IBUS Receiver	FlySky digital protocol	Beginner drones
CRSF Receiver	Long-range protocol	FPV & autonomous drones

ELRS Receiver	ExpressLRS protocol	Long-range, modern systems
DSMX Receiver	Spektrum systems	RC aircraft
FPort Receiver	Combined control and telemetry	Advanced drones

How to Match a Receiver with a Transmitter

Rule 1: Same Protocol

The transmitter and receiver must support the same communication protocol.

Rule 2: Same Brand (Usually)

Most receivers work only with compatible transmitter systems.

Rule 3: Supported by Flight Controller

The flight controller must support the receiver output protocol.

Compatibility Table

Transmitter	**Compatible Receiver**	**Protocol**
FlySky FS-i6	FS-iA6B	AFHDS 2A
FlySky FS-i6X	FS-iA10B	AFHDS 2A
Radiolink AT9S Pro	R6FG	Radiolink Protocol
Radiolink AT9S Pro	R8EF	Radiolink Protocol
FrSky X9D	X8R	ACCST
FrSky X9D	RXSR	ACCST
Radiomaster Pocket ELRS	RP1	ELRS

Radiomaster Pocket ELRS	RP3	ELRS
Radiomaster Boxer ELRS	RP1	ELRS
Radiomaster TX16S ELRS	RP4TD	ELRS
TBS Tango 2	Nano RX	CRSF
Futaba 14SG	R7008SB	Futaba SBUS
Futaba 16IZ	R7108SB	Futaba SBUS

Problems Caused by Receiver Mismatch

Problem	**Cause**
Receiver Does Not Bind	Different protocols
No Control Response	Unsupported receiver
Random Signal Loss	Incompatible firmware
Limited Channels	Wrong receiver type
Telemetry Not Working	Protocol mismatch
Flight Controller Not Detecting Receiver	Wrong output protocol
Failsafe Issues	Incorrect configuration
Reduced Range	Wrong receiver-transmitter combination

Common Receiver Outputs

Output Type	**Modern Use**
PWM	Rarely used
PPM	Older drones
SBUS	Most common
IBUS	FlySky systems
CRSF	Long-range systems
ELRS	New-generation systems

Receiver Selection Based on Application

Application	**Receiver Type**	**Example Receiver**
Beginner Drone	IBUS	FS-iA6B
F330 Drone	IBUS	FS-iA6B
F450 Drone	IBUS / SBUS	FS-iA10B
S500 Drone	SBUS	R8EF
Autonomous Drone	SBUS / ELRS	RP1
Mapping Drone	ELRS	RP3

Survey Drone	ELRS	RP4TD
Agriculture Drone	ELRS	RP4TD
Delivery Drone	ELRS / CRSF	RP4TD
FPV Racing	ELRS	RP1
FPV Freestyle	ELRS	RP1
Long-Range UAV	ELRS / CRSF	RP4TD
Research UAV	ELRS	RP4TD
Industrial UAV	ELRS / CRSF	RP4TD

Receiver Range Comparison

Receiver System	**Typical Range**
PWM Receiver	500 m
FlySky IBUS	1–2 km
Radiolink Receiver	2–4 km
FrSky Receiver	2–10 km
ELRS Receiver	5–50+ km
CRSF Receiver	10–100+ km

Quick Selection Table

If You Have This Transmitter	Buy This Receiver
FlySky FS-i6	FS-iA6B
FlySky FS-i6X	FS-iA10B
Radiolink AT9S Pro	R8EF
Radiomaster Pocket ELRS	RP1
Radiomaster Boxer ELRS	RP3
Radiomaster TX16S ELRS	RP4TD
TBS Tango 2	Nano RX
Futaba 16IZ	R7108SB

Beginner Recommendation

User Level	Best Receiver
Beginner	FS-iA6B
Student Projects	R8EF
Pixhawk Projects	RP1 ELRS
Research Drones	RP3 ELRS

Long-Range UAVs	RP4TD ELRS
Industrial UAVs	CRSF or ELRS Diversity Receiver

Important Rule

Transmitter and Receiver must speak the same language (protocol).

For example:

- FlySky ↔ FlySky Receiver ✓
- ELRS Transmitter ↔ ELRS Receiver ✓
- FrSky ↔ FrSky Receiver ✓
- FlySky ↔ ELRS Receiver ✗
- Radiolink ↔ FrSky Receiver ✗

If the protocols do not match, the drone cannot receive control commands, even if all hardware is connected correctly. This is one of the most common mistakes made by beginners.

Examples of Built Drones Components matching

Selecting Components: The most important rule in drone building is that all components must work together as a system. A powerful motor with the wrong propeller or battery can reduce performance, overheat components, or even cause a crash.

Motor + Propeller + ESC + Battery Matching

Component	**Must Match With**
Motor	Propeller, ESC, Battery
Propeller	Motor KV, Frame Size
ESC	Motor Current, Battery Voltage
Battery	Motor KV, ESC Voltage Rating
Frame	Propeller Size, Payload

Matching Rule

Motor

↓

Propeller

↓

ESC

↓

Battery

↓

Flight Time & Performance

Example 1: Beginner Quadcopter

Purpose

Learning drone building and basic flying.

Component	**Selection**
Frame	F450
Flight Controller	Pixhawk 2.4.8 / Radiolink Crossflight
Motors	2212 920KV × 4
Propellers	1045 (10×4.5)
ESC	30A × 4
Battery	3S 5200mAh LiPo
Receiver	FS-iA6B / R8EF
Transmitter	FlySky FS-i6X

GPS	Optional
Telemetry	Optional

Expected Performance

Parameter	**Value**
Flight Time	12–18 min
Payload	Small Camera
Difficulty	Beginner
Cost	Low

Example 2: Autonomous Drone Setup

Purpose

Waypoint missions, mapping, research, and autonomous flight.

Component	**Selection**
Frame	F450 / S500
Flight Controller	Pixhawk 2.4.8
Motors	2212 920KV × 4
Propellers	1045
ESC	30A × 4

Battery	4S 5200mAh LiPo
GPS	M8N GPS
Telemetry	433 MHz SiK
Receiver	R8EF / ELRS
Transmitter	Radiomaster Pocket
Ground Station	Mission Planner

Additional Features

✓ GPS Position Hold
✓ Return-To-Home (RTH)
✓ Waypoint Navigation
✓ Telemetry Monitoring
✓ Mission Planning

Ready-Made Component Selection Table

Application	**Frame**	**Motor**	**Propeller**	**ESC**	**Battery**
Indoor Drone	65–100 mm	0802	31–40 mm	5A	1S 450mAh
Tiny FPV	75 mm	1102	2 inch	12A	2S 650mAh
Racing Drone	220 mm	2207 2400KV	5 inch	45A	6S 1300mAh
Freestyle Drone	250 mm	2306 1800KV	5 inch	45A	6S 1500mAh
Beginner	F330	2212	9 inch	30A	3S 2200–4500mAh

F330		1000KV			
Beginner F450	F450	2212 920KV	1045	30A	3S 5200mAh
S500 Drone	S500	2216 880KV	1045–1147	30A–40A	4S 5200mAh
Photography Drone	550 mm	2814 700KV	12 inch	40A	4S 10000mAh
Mapping Drone	650 mm	3508 580KV	13 inch	50A	6S 12000mAh
Inspection Drone	650 mm	4006 380KV	15 inch	60A	6S 16000mAh
Research Drone	650 mm	4008 380KV	15 inch	60A	6S 22000mAh
Delivery Drone	900 mm	6215 170KV	22 inch	80A	8S 22000mAh
Agriculture 5L	1100 mm	6215 170KV	24 inch	80A	12S 16000mAh
Agriculture 10L	1200 mm	7215 150KV	28 inch	100A	12S 22000mAh
Agriculture 20L	1400 mm	8120 120KV	32 inch	120A	12S 30000mAh
Heavy Lift Drone	1500 mm	10020 100KV	34 inch	150A	14S 32000mAh

Quick Beginner Formula

Requirement	Recommended Setup
Learn Drone Building	F450 + 2212 + 1045 + 30A + 3S
Learn Pixhawk	F450 + Pixhawk + GPS
Learn Autonomous Flight	Pixhawk + M8N + Telemetry
Learn Mapping	S500 + Pixhawk + GPS
Learn Long Flight Time	Low KV Motor + Large Prop + High Capacity Battery
Learn Heavy Lift	Large Frame + Low KV Motor + Large Propeller

Golden Rule

Always select components in this order:

Mission → Payload → Frame → Motor → Propeller → ESC → Battery → Flight Controller → GPS → Telemetry

This ensures that every component is compatible and optimized for the intended application.

Your First Quadcopter

Building your first quadcopter is one of the best ways to learn drone technology. Follow the steps carefully and test each component before flying.

Step 1: Assemble the Frame

- Unpack all frame parts.
- Attach the arms to the center plates.
- Tighten all screws securely.
- Ensure the frame is straight and rigid.

Check

✓ No loose parts
✓ Arms properly aligned
✓ Sufficient space for electronics

Step 2: Install the Motors

- Mount one motor on each arm.
- Use the correct screws provided with the motor.
- Do not use screws that are too long, as they may damage the motor windings.

Check

✓ Motors firmly mounted
✓ No motor movement or wobbling

Step 3: Install the ESCs

- Connect one ESC to each motor.
- Secure ESCs to the arms using zip ties or tape.
- Keep wires neat and organized.

Check

✓ ESCs securely mounted
✓ Motor wires connected properly

Step 4: Install Power Distribution

- Connect all ESC power wires to the Power Distribution Board (PDB) or Power Module.
- Ensure correct polarity.

Red Wire → Positive (+)

Black Wire → Negative (-)

Warning

Reversing polarity can permanently damage electronics.

Step 5: Install the Flight Controller

- Mount the Pixhawk at the center of the frame.
- Ensure the arrow on the flight controller points toward the front of the drone.
- Use vibration-damping foam or mounts.

Check

✓ Arrow facing forward
✓ Mounted firmly

Step 6: Install the GPS Module

- Mount the GPS above the frame whenever possible.
- Keep it away from power wires and motors.
- Ensure clear visibility to the sky.

Check

✓ Compass cable connected
✓ GPS securely mounted

Step 7: Install the Receiver

- Connect the receiver to the flight controller.
- Bind the receiver with the transmitter.
- Secure antennas properly.

Check

✓ Receiver bound successfully
✓ Stick movements detected in Mission Planner

Step 8: Connect Telemetry (Optional)

- Connect telemetry module to the telemetry port.
- Pair with Mission Planner or QGroundControl.

Benefits

✓ Real-time monitoring
✓ Parameter tuning
✓ Mission upload

Step 9: Mount the Battery

- Place the battery near the center of gravity.
- Secure it using battery straps.
- Ensure it cannot move during flight.

Check

✓ Battery firmly secured
✓ Balanced drone

Step 10: Software Setup

- Install Mission Planner.
- Update firmware.
- Calibrate:
  - Accelerometer
  - Compass
  - Radio
  - ESCs

Check

✓ All sensors healthy
✓ GPS detected
✓ Receiver working

Step 11: Motor Direction Test

Remove all propellers before testing.

For a typical quadcopter:

Motor	**Direction**
Front Left	Clockwise (CW)
Front Right	Counter-Clockwise (CCW)

Rear Left	Counter-Clockwise (CCW)
Rear Right	Clockwise (CW)

If a motor rotates incorrectly, swap any two motor wires between the ESC and motor.

Step 12: Install Propellers

Install propellers according to motor direction.

Motor Direction	**Propeller Type**
CW Motor	CW Propeller
CCW Motor	CCW Propeller

Check

✓ Propellers tightened properly
✓ Correct propeller on each motor

Pre-Flight Checklist

Item	**Status**
Frame Tightened	✓
Motors Secure	✓
ESC Connected	✓
Battery Charged	✓
GPS Lock Acquired	✓

Receiver Connected	✓
Flight Controller Calibrated	✓
Propellers Installed Correctly	✓

Common Mistakes

Mistake	**Result**
Wrong Motor Direction	Drone flips immediately after takeoff
Wrong Propeller Placement	No lift or instant crash
Loose Screws	Vibrations and instability
Reverse Battery Polarity	Electronic damage
Flight Controller Mounted Backward	Incorrect control response
Skipping Compass Calibration	Navigation errors
Flying Without GPS Lock	Poor autonomous performance
Unsecured Battery	Shifted center of gravity
Unbalanced Propellers	Vibrations and sensor errors
Forgetting to Tighten Propellers	Propeller may detach in flight

First Flight Procedure

1. Choose an open field.
2. Verify GPS lock (if using GPS).
3. Arm the drone.
4. Slowly increase throttle.
5. Hover at 1–2 meters.
6. Check stability.
7. Land and inspect all components.

Beginner Tip

Always perform the first motor test and calibration without propellers installed. This simple habit prevents most beginner accidents and protects both the drone and the pilot.

Beginner Drone Wiring Diagram

Example Setup

- F450 Frame
- Pixhawk 2.4.8
- 2212 920KV Motors
- 30A ESCs
- M8N GPS
- FlySky Receiver
- 3S 5200mAh LiPo Battery

Detailed Connection Table

Component	Connected To	Purpose
Battery	Power Module	Main power source
Power Module	Pixhawk Power Port	Powers flight controller
Power Module	ESCs/PDB	Distributes battery power
ESC	Motor	Controls motor speed
ESC Signal Wire	Pixhawk MAIN OUT	Receives motor commands
GPS	GPS Port	Navigation

Compass	I2C Port	Direction sensing
Receiver	RC IN Port	Pilot commands
Telemetry	TELEM Port	Ground station communication
Buzzer	BUZZER Port	Audio alerts

ESC Wiring

Each ESC has two sides.

Power Side

ESC

├── Red Wire (+)

└── Black Wire (-)

Connected to:

Battery / Power Distribution Board

Motor Side

ESC

├── Motor Wire A

├── Motor Wire B

└── Motor Wire C

Connected to:

Brushless Motor

Signal Side

ESC

├── Signal Wire

├── Ground

└── +5V (if available)

Connected to:

Pixhawk MAIN OUT

Pixhawk Motor Outputs

Pixhawk Output	**Motor**
MAIN OUT 1	Motor 1
MAIN OUT 2	Motor 2
MAIN OUT 3	Motor 3
MAIN OUT 4	Motor 4

GPS Wiring

GPS Wire	**Pixhawk Port**
GPS Connector	GPS Port
Compass Connector	I2C Port

GPS Placement Rule

GPS

↑

10–15 cm Above Frame

↑

Away from ESCs

↑

Away from Power Wires

This reduces magnetic interference.

Receiver Wiring

FlySky Example

Receiver	**Pixhawk**
IBUS Output	RC IN
Power	5V
Ground	GND

ELRS Example

Receiver	**Pixhawk**
TX	RX Port
RX	TX Port
5V	5V
GND	GND

Battery Wiring, Example Battery:3S 5200mAh LiPo

Battery

|

XT60 Connector

|

Power Module

|

Power Distribution

|

ESCs

Voltage Check

Before powering ON:

Battery Type	Full Charge Voltage
3S LiPo	12.6 V
4S LiPo	16.8 V
6S LiPo	25.2 V

Formula

$$V_{full} = 4.2 \times Cells$$

Example:

3S Battery

4.2 × 3

= 12.6 V

Polarity Check

Correct

Red Wire → Positive (+)

Black Wire → Negative (-)

Wrong

Red → Negative

Black → Positive

Results:

✗ Burned ESC
✗ Burned Pixhawk
✗ Damaged GPS
✗ Smoke

Current Check

Current drawn by motors determines ESC selection.

Formula

$$ESC\ Rating \geq 1.3 \times Motor\ Current$$

Example:

Motor Current = 20A

Required ESC

= 20 × 1.3

= 26A

Use 30A ESC

Pre-Power Safety Checklist

Check Item	**Verify**
Battery Voltage Correct	✓
Positive and Negative Correct	✓
No Exposed Wires	✓
GPS Connected	✓
Receiver Connected	✓
Pixhawk Orientation Correct	✓
ESC Signal Wires Correct	✓
XT60 Connector Secure	✓
No Short Circuit	✓

Most Common Beginner Wiring Mistakes

Mistake	Result
Reverse Battery Polarity	Instant component damage
GPS Connected to Wrong Port	GPS not detected
Receiver Connected Incorrectly	No radio control
Wrong ESC Output Number	Drone flips on takeoff
Loose XT60 Connector	Sudden power loss
Exposed Solder Joints	Short circuit
GPS Near Power Wires	Compass errors
Incorrect Ground Connections	Random system failures
Wrong Motor Numbering	Unstable flight
Powering Pixhawk Directly from Battery	Permanent damage



Before installing propellers, test every connection, verify motor directions, check GPS detection, and confirm receiver operation. Most beginner crashes occur because propellers are installed before electrical testing is completed.

Mission Planner Setup Guide for Beginners

Mission Planner is a free Ground Control Station (GCS) software used to configure, calibrate, monitor, and control drones running ArduPilot firmware.

Q.What is Mission Planner?

Mission Planner allows you to:

- Upload firmware
- Configure Pixhawk
- Calibrate sensors
- Set flight modes
- Plan autonomous missions
- Monitor telemetry
- Analyze flight logs

Think of it as: **Mission Planner = Control Center for Your Drone**

Before You Start

Item	**Purpose**
Pixhawk Flight Controller	Drone Brain
USB Cable	Connection to Computer
Mission Planner Software	Configuration Software
GPS Module	Navigation
Receiver & Transmitter	Manual Control
Fully Charged Battery	Testing

Requirements

Step 1: Install Mission Planner

Procedure

1. Download Mission Planner.
2. Install on Windows PC.
3. Connect Pixhawk using USB.
4. Install required drivers automatically.
5. Open Mission Planner.

Successful Connection

You should see:

- COM Port detected
- Green connection indicator
- Pixhawk information displayed

Common Installation Problems

Problem	Cause	Solution
COM Port Not Visible	Driver issue	Reinstall drivers
Connection Failed	Wrong COM Port	Select correct port
Pixhawk Not Detected	Faulty USB Cable	Replace cable
Software Crash	Old version	Update Mission Planner

Step 2: Upload Firmware

Firmware is the operating system of the flight controller.

Popular Firmware Types

Firmware	Application
ArduCopter	Multirotors
ArduPlane	Fixed-Wing
ArduRover	Ground Vehicles
ArduSub	Underwater Vehicles

Upload Procedure

1. Initial Setup
2. Install Firmware
3. Select ArduCopter
4. Wait for upload

Example 1

Quadcopter

→ Select ArduCopter

Example 2

Fixed-Wing UAV

→ Select ArduPlane

Common Mistakes

Mistake	**Result**
Wrong Firmware	Drone won't operate correctly
Disconnect During Upload	Corrupted firmware
Low Battery During Update	Upload failure

Step 3: Accelerometer Calibration

What is an Accelerometer?

The accelerometer measures:

- Tilt
- Orientation
- Linear acceleration

It helps the drone know:

- Up
- Down
- Left
- Right

Why Calibration is Necessary?

Without calibration:

- Drone drifts
- Drone tilts
- Poor hovering

Calibration Procedure

Mission Planner asks you to place the drone in six positions:

1. Level
2. Left Side
3. Right Side
4. Nose Down
5. Nose Up
6. Upside Down

Example 1

Correct Calibration

Result:

✓ Stable hover

Example 2

Calibration on Uneven Table

Result:

✗ Drone drifts constantly

Common Mistakes

Mistake	**Result**
Uneven Surface	Incorrect calibration
Moving Drone	Sensor errors
Skipping Steps	Poor stability

Step 4: Compass Calibration

What is a Compass?

The compass determines:

- Heading
- Direction

GPS tells location.

Compass tells facing direction.

Why Calibration is Important

Required for:

- Loiter
- Return To Launch
- Auto Missions

Procedure

1. Start Compass Calibration.
2. Rotate drone slowly in all directions.
3. Complete all rotations.

Example 1

Proper Calibration

Result:

✓ Accurate navigation

Example 2

Calibrating Near Metal Objects

Result:

✗ Compass errors

✗ Fly-away risk

Common Mistakes

Mistake	**Result**
Near Car	Magnetic interference
Near Power Lines	Compass disturbance
GPS Too Close to ESC	Compass errors

Step 5: Radio Calibration

Purpose

Ensures transmitter stick movements are correctly recognized.

Procedure

1. Turn ON transmitter.
2. Open Radio Calibration.
3. Move all sticks fully.
4. Move switches.
5. Save calibration.

Example 1

Correct Calibration

Throttle Up

→ Drone climbs

Example 2

Incorrect Calibration

Throttle Up

→ Unexpected response

Common Mistakes

Mistake	**Result**
Not Moving Full Stick Range	Reduced control
Incorrect Channel Mapping	Wrong controls
Low Transmitter Battery	Signal issues

Flight Modes

Flight modes determine how the drone behaves.

1. Stabilize Mode

What It Does

- Self-leveling
- Pilot controls everything

Uses

- Learning
- Manual Flying

Example

Wind tilts drone.

Pilot must correct manually.

Advantages

✓ Simple

✓ Beginner Friendly

Disadvantages

✗ No altitude hold

✗ No GPS assistance

2. Alt Hold Mode

What It Does

Maintains altitude automatically.

Pilot controls:

- Roll
- Pitch
- Yaw

Altitude remains constant.

Example

Drone at 10 m.

Release throttle.

Drone remains near 10 m.

Advantages

✓ Easier flying

✓ Better hovering

Common Mistakes

Problem	**Cause**
Altitude drift	Poor barometer calibration
Unstable hover	Excessive vibration

3. Loiter Mode

What It Does

Uses:

- GPS
- Compass

Maintains:

- Position
- Altitude

Example

Release all sticks.

Drone stays at same location.

Advantages

✓ Excellent hovering

✓ Aerial photography

✓ Mapping

Requirements

✓ GPS Lock

✓ Compass Calibration

Common Mistakes

Mistake	**Result**
Flying without GPS lock	Position drift
Poor compass calibration	Fly-away risk

4. RTL (Return-To-Launch)

What It Does

Drone automatically:

1. Climbs to safe altitude
2. Returns home
3. Lands

Example 1

Pilot loses orientation.

Activate RTL.

Drone returns automatically.

Example 2

Low battery failsafe triggers RTL.

Drone returns safely.

Requirements

✓ GPS

✓ Home Position Recorded

Common Mistakes

Mistake	**Result**
No GPS lock before takeoff	Wrong return location
Wrong compass calibration	Wrong direction

5. Auto Mode

What It Does?

Drone follows pre-planned waypoints automatically.

Example 1

Mapping Mission

Takeoff

→ Waypoint 1

→ Waypoint 2

→ Waypoint 3

→ Land

Example 2

Agriculture Mission

Fly spray route automatically.

Requirements

✓ GPS

✓ Compass

✓ Mission Uploaded

Common Mistakes

Mistake	**Result**
Incorrect waypoints	Wrong route
Low battery	Mission failure
No GPS lock	Navigation issues

Pre-Flight Checklist

Item	**Status**
Firmware Installed	✓
Accelerometer Calibrated	✓
Compass Calibrated	✓
Radio Calibrated	✓
GPS Lock Acquired	✓
Battery Fully Charged	✓
Propellers Tightened	✓
Flight Mode Switch Working	✓
RTL Tested	✓

Failsafe Configured	✓

Recommended Learning Sequence

Stage	**Flight Mode**
First Flight	Stabilize
Hover Practice	Alt Hold
GPS Practice	Loiter
Safety Training	RTL
Autonomous Missions	Auto

Golden Rule for Beginners

Never perform your first flight in Auto Mode.

Start with **Stabilize**, then **Alt Hold**, then **Loiter**, and only after gaining confidence should you use **RTL** and **Auto** missions. This progression helps you understand both manual and autonomous flight while reducing the risk of crashes.

What is Firmware? (Simple Explanation)-

Firmware is the software that runs inside a hardware device and tells it how to work.

Think of firmware as the **brain's operating system** of a device.

Simple Example

Device	**Firmware Does**
Drone Flight Controller	Controls sensors, motors, GPS, and flight modes
Smartphone	Controls hardware functions

Wi-Fi Router	Manages internet connections
Camera	Controls image capture and settings

Drone Example



The firmware tells the flight controller:

- How to read sensor data
- How to stabilize the drone
- How to control motors
- How to use GPS
- How to perform Return-to-Home
- How to execute autonomous missions



A brain without knowledge cannot perform tasks. Similarly, a flight controller without firmware cannot fly a drone.

Common Drone Firmware

Firmware	Used For
ArduCopter	Quadcopters, Hexacopters, Octocopters
ArduPlane	Fixed-Wing UAVs
ArduRover	Ground Robots
PX4	Research and Autonomous Drones
Betaflight	FPV Racing Drones
INAV	GPS FPV Drones

Example 1: Quadcopter

Hardware:

- Pixhawk 2.4.8
- Motors
- ESCs
- GPS

Firmware:

- ArduCopter

Result:

- Stable flight
- GPS navigation
- RTL
- Auto missions

Example 2: FPV Racing Drone

Hardware:

- F7 Flight Controller
- FPV Motors
- ESCs

Firmware:

- Betaflight

Result:

- Fast response
- Racing performance
- Acrobatic flying

What Happens If Wrong Firmware Is Installed?

Wrong Firmware	**Problem**
ArduPlane on Quadcopter	Motors won't work correctly
ArduCopter on Fixed Wing	Control system mismatch
Corrupted Firmware	Flight controller won't boot

Firmware is a special software installed inside the flight controller that tells the drone how to fly, control motors, read sensors, and perform different flight functions. Without firmware, the flight controller cannot operate the drone.

What is Autonomous Flight?

Autonomous flight is a mode in which a drone can fly and perform tasks automatically without continuous control from the pilot.

The drone uses a flight controller, GPS, sensors, and pre-programmed instructions to make decisions and navigate on its own.

Simple Definition

In manual flight, the pilot controls the drone.

In autonomous flight, the drone controls itself based on programmed commands and sensor data.

Example 1: Mapping Mission

A pilot creates a survey mission in Mission Planner.

The drone:

1. Takes off automatically
2. Flies through all waypoints
3. Captures images
4. Returns to the starting point
5. Lands automatically

No manual control is needed during the mission.

Example 2: Agriculture Drone

The pilot enters the field boundaries.

The drone:

1. Takes off
2. Follows the planned route
3. Sprays crops automatically
4. Returns after completing the mission

Components Required for Autonomous Flight

Component	**Purpose**
Flight Controller	Controls the drone
GPS	Provides location
Compass	Determines direction

Barometer	Measures altitude
Telemetry	Communicates with ground station
Mission Planner	Creates missions
Battery	Powers the system

Autonomous Flight Features

Feature	**Description**
Auto Takeoff	Drone takes off automatically
Waypoint Navigation	Flies through predefined points
Position Hold	Maintains location automatically
Return-to-Launch (RTL)	Returns home automatically
Auto Landing	Lands without pilot input
Mission Execution	Performs planned tasks

Manual Flight vs Autonomous Flight

Manual Flight	**Autonomous Flight**
Pilot controls continuously	Drone follows programmed instructions
Requires constant attention	Minimal pilot intervention

Suitable for beginners	Suitable for advanced applications
Limited coverage area	Efficient for large-area operations

Common Applications

Application	**Use of Autonomous Flight**
Mapping	Automatic survey missions
Agriculture	Crop spraying
Delivery	Package transport
Inspection	Power line and pipeline inspection
Research	Data collection
Defense	Surveillance and reconnaissance
Search and Rescue	Area scanning

Common Problems

Problem	**Cause**
Drone flies off course	Poor GPS signal
Incorrect waypoint path	Mission planning error
RTL failure	Compass calibration issue

Position drift	Insufficient satellites
Mission interruption	Low battery

Pre-Flight Checks for Autonomous Missions

Check	**Status**
GPS Lock (10+ Satellites)	✓
Compass Calibrated	✓
Battery Fully Charged	✓
Waypoints Verified	✓
RTL Tested	✓
Telemetry Connected	✓
Home Position Recorded	✓

Beginner Tip

Before attempting a fully autonomous mission:

1. Learn **Stabilize Mode**
2. Practice **Alt Hold**
3. Master **Loiter Mode**
4. Test **RTL**
5. Then try **Auto Mode**

This step-by-step approach helps ensure safe and successful autonomous flights.

GPS Navigation

What is GPS Navigation?

GPS Navigation is the process by which a drone uses GPS data to determine its location and travel from one point to another automatically.
In simple words, GPS navigation helps the drone know where it is and where it needs to go.



GPS (Global Positioning System) in Drones

GPS is a navigation system that helps a drone determine its exact position, altitude, speed, and direction by receiving signals from satellites orbiting the Earth. It enables autonomous flight features such as waypoint navigation, position hold, return-to-home (RTH), and automatic landing. The GPS module continuously sends location data to the flight controller, allowing the drone to maintain stable and accurate flight. Modern drones often use GPS along with other satellite systems such as GLONASS, Galileo, and BeiDou for improved accuracy and reliability. GPS is essential for autonomous and long-range drone operations.

How GPS Navigation Works



The GPS module receives signals from satellites, calculates the drone's position, and sends the information to the flight controller. The flight controller then guides the drone along the desired route.

Components Required for GPS Navigation

Component	**Purpose**
GPS Module	Provides location coordinates
Flight Controller	Processes GPS data
Compass (Magnetometer)	Determines direction

Telemetry	Monitors mission progress
Mission Planner	Creates navigation routes
Battery	Powers the system

Information Provided by GPS

Information	**Description**
Latitude	North-South position
Longitude	East-West position
Altitude	Height above sea level
Ground Speed	Speed over the ground
Distance	Distance from home point
Position	Exact location of the drone

GPS Navigation Features

Feature	**Description**
Position Hold	Keeps drone at one location
Waypoint Navigation	Flies through predefined points
Return-To-Launch (RTL)	Returns to takeoff location

Auto Mission	Completes missions automatically
Follow Me	Follows a moving target
Geofencing	Restricts flight area

Example 1: Mapping Mission

A survey area is defined in Mission Planner.

The drone:

1. Takes off
2. Flies to Waypoint 1
3. Captures images
4. Continues to Waypoint 2, 3, and 4
5. Returns home automatically

Result: Accurate aerial map generation.

Example 2: Agriculture Survey

A farmer selects the field boundary.

The drone:

1. Flies over the field
2. Follows a GPS-guided path
3. Collects crop data
4. Returns automatically

Result: Efficient crop monitoring.

GPS Navigation Flight Modes

Flight Mode	**GPS Usage**
Stabilize	No GPS assistance
Alt Hold	Altitude only
Loiter	GPS Position Hold

RTL	GPS Navigation to Home
Auto	Full GPS Navigation
Guided	GPS-Controlled Commands

GPS Navigation Accuracy

GPS Type	**Accuracy**
Standard GPS	2–5 m
GPS + GLONASS	1–3 m
GPS + Galileo	1–2 m
RTK GPS	1–5 cm

GPS Satellite Requirements

Satellites Visible	**Navigation Quality**
Less than 6	Poor
6–10	Basic
10–15	Good
More than 15	Excellent

Common GPS Navigation Problems

Problem	Cause	Solution
Position Drift	Weak GPS signal	Wait for more satellites
Wrong Direction	Compass error	Recalibrate compass
RTL Failure	Home point not recorded	Wait for GPS lock
Fly-Away	Compass interference	Move GPS away from power wires
Slow Navigation	Poor satellite visibility	Fly in open areas

Pre-Flight GPS Navigation Checklist

Check	Status
GPS Detected	✓
Compass Calibrated	✓
10+ Satellites Acquired	✓
Home Position Recorded	✓
RTL Tested	✓
Mission Uploaded Correctly	✓

Telemetry Connected	✓

GPS Navigation vs Manual Navigation

Manual Navigation	**GPS Navigation**
Pilot controls route	Drone follows GPS route
Requires constant input	Automated navigation
Suitable for short flights	Suitable for large-area missions
Human decision-making	Computer-guided decisions

Common Beginner Mistakes

Mistake	**Result**
Taking off before GPS lock	Poor navigation
Ignoring compass calibration	Incorrect heading
Flying near buildings	Weak GPS signal
Not checking home location	RTL problems
Relying only on GPS	Reduced safety

Waypoint Mission

What is a Waypoint Mission?

A Waypoint Mission is an autonomous flight where the drone flies through a series of predefined GPS locations called waypoints.

The pilot creates the route in Mission Planner, uploads it to the drone, and the drone follows the path automatically.

Example

DRONE MISSION SEQUENCE

Automated Waypoint Mission Flow



This mission sequence can be executed in Auto mode using a Flight Controller with GPS.
Ensure GPS lock, safe altitude, and failsafe settings before mission start.

Applications

Application	Use
Mapping	Survey large areas
Agriculture	Field monitoring
Inspection	Power line inspection
Research	Data collection
Delivery	Package transport

Common Mistakes

Mistake	Result
Wrong waypoint location	Drone flies to wrong area
Low battery	Mission incomplete
No GPS lock	Navigation errors
Incorrect altitude	Collision risk

Return To Launch (RTL)

What is RTL?

Return To Launch (RTL) is a safety feature that automatically returns the drone to its takeoff location.

How RTL Works

1. Drone records Home Position.
2. RTL is activated manually or automatically.

3. Drone climbs to a safe altitude.
4. Returns to Home Position.
5. Lands automatically.

Example 1

Pilot loses orientation.

→ Activate RTL

→ Drone returns safely.

Example 2

Low battery detected.

→ Automatic RTL triggered.

→ Drone returns before battery becomes critical.

Common Mistakes

Mistake	**Result**
Taking off before GPS lock	Wrong home position
Compass not calibrated	Wrong return direction
RTL altitude too low	Obstacle collision risk

Geo-Fencing

What is Geo-Fencing?

Geo-Fencing creates a virtual boundary around the drone's operating area.

The drone cannot fly beyond the defined limits.

Example

Allowed Area



Outside Boundary = Not Allowed

Benefits

Benefit	Description
Safety	Prevents fly-aways
Regulations	Keeps drone in legal area
Training	Limits beginner mistakes
Security	Restricts sensitive zones

Common Actions

Fence Violation	Drone Response
Exceed Distance	RTL
Exceed Altitude	RTL or Land
Enter Restricted Zone	Warning

Mission Planning

What is Mission Planning?

Mission Planning is the process of creating an autonomous flight route before takeoff.

The route is created using Mission Planner and uploaded to the flight controller.

Mission Planning Steps

1. Connect Pixhawk.
2. Open Mission Planner.
3. Select mission area.
4. Add waypoints.
5. Set altitude.
6. Upload mission.
7. Verify GPS lock.
8. Start Auto Mode.

Example 1: Mapping Mission

Waypoint	**Altitude**
Takeoff	20 m
WP1	50 m
WP2	50 m
WP3	50 m
RTL	Automatic

Result:

✓ Complete area coverage
✓ Image collection

Example 2: Agriculture Survey

Waypoint	**Task**
WP1	Start Survey
WP2	Scan Crop Area
WP3	Scan Crop Area
WP4	Complete Survey
RTL	Return Home

Result:

✓ Automatic field inspection

Common Mission Planning Mistakes

Mistake	**Result**
Wrong waypoint altitude	Obstacle collision
Mission not uploaded	Drone does nothing
No GPS lock	Navigation failure
Insufficient battery	Mission interruption
Incorrect home position	RTL problems

Pre-Mission Checklist

Check Item	**Status**
Firmware Installed	✓
Accelerometer Calibrated	✓
Compass Calibrated	✓
Radio Calibrated	✓
GPS Lock (10+ Satellites)	✓
Home Position Recorded	✓

Battery Fully Charged	✓
Telemetry Connected	✓
Waypoints Verified	✓
RTL Tested	✓

Learn your own Mission Planner installation:

1. **Mission Planner Home Screen**
2. **Firmware Installation Page**



Mission Planner: Install FirmwareScreen

3. **Accelerometer Calibration Window**
4. **Compass Calibration Window**
5. **Radio Calibration Window**

6. **Flight Modes Setup Page**
7. **Mission Planning Map Screen**
8. **Waypoint Creation Screen**
9. **Geo-Fence Configuration Screen**
10. **Flight Data Dashboard**
11. **Telemetry Status Screen**
12. **GPS Status Window**

Note: Mission Planner's interface changes between versions,

Testing & Troubleshooting Guide for Beginners

1. Drone Not Arming

What Does "Arming" Mean?

Arming is the process of activating the motors so the drone is ready to fly.

If the drone is not arming, the motors will not start.

Example 1

You connect the battery.

Move throttle stick down-right.

Nothing happens.

Motors do not spin.

Example 2

Pixhawk LEDs are ON.

Receiver is connected.

But Mission Planner shows:

"PreArm Check Failed"

Drone will not arm.

Common Causes

Cause	**Description**
No GPS Lock	Required flight mode not ready
Compass Error	Compass not calibrated
Radio Not Calibrated	Flight controller not detecting sticks

Safety Switch Not Pressed	Pixhawk safety still enabled
Low Battery	Voltage below limit
Accelerometer Error	Sensor calibration issue

3 Ways to Fix It

Fix 1

Check Mission Planner Messages.

Read the exact Pre-Arm error.

Fix 2

Calibrate:

- Accelerometer
- Compass
- Radio

Fix 3

Ensure GPS has at least 10 satellites.

Pre-Checks

✓ Battery charged

✓ Receiver connected

✓ GPS working

✓ Safety switch pressed

✓ Flight controller calibrated

2. Drone Flips During Takeoff

What Happens?

Drone immediately flips over instead of lifting off.

This is one of the most common beginner mistakes.

Example 1

Throttle increased.

Drone flips to the left.

Example 2

Drone lifts a few centimeters.

Suddenly rolls and crashes.

Common Causes

Cause	Description
Wrong Propeller Position	CW and CCW props mixed
Wrong Motor Direction	Motor spinning opposite direction
Wrong Motor Numbering	ESC connected to wrong output
Flight Controller Orientation Wrong	Pixhawk facing wrong direction

3 Ways to Fix It

Fix 1

Check motor numbering.

Motor 1 → Output 1

Motor 2 → Output 2

Motor 3 → Output 3

Motor 4 → Output 4

Fix 2

Check motor directions.

Remove propellers first.

Verify each motor rotation.

Fix 3

Verify propeller installation.

CW Prop → CW Motor

CCW Prop → CCW Motor

Pre-Checks

✓ Propellers correct

✓ Motors correct

✓ Pixhawk arrow forward

✓ Motor test completed

3. GPS Not Locking

What Does It Mean?

GPS cannot detect enough satellites.

Without GPS lock:

- RTL won't work
- Loiter won't work
- Auto mode won't work

Example 1

GPS shows:

Satellites = 3

No lock after 5 minutes.

Example 2

Drone works indoors.

GPS never gets a fix.

Common Causes

Cause	Description
Indoor Testing	Satellite signals blocked
Poor GPS Placement	Antenna blocked
Damaged GPS Module	Hardware issue
Bad Weather	Weak signals

3 Ways to Fix It

Fix 1

Move to open outdoor area.

Fix 2

Raise GPS above frame.

Fix 3

Wait 3–10 minutes for first lock.

Pre-Checks

✓ Open sky

✓ GPS connected

✓ Compass connected

✓ Antenna facing upward

4. Compass Errors

What Is a Compass Error?

The compass cannot determine direction correctly.

This can cause:

- Wrong heading
- RTL failure
- Fly-away incidents

Example 1

Drone points north.

Mission Planner shows south.

Example 2

RTL activated.

Drone flies in wrong direction.

Common Causes

Cause	**Description**
Poor Calibration	Compass not calibrated
GPS Near Power Wires	Magnetic interference
Metal Nearby	Disturbs magnetic field
Loose Compass Module	Incorrect readings

3 Ways to Fix It

Fix 1

Perform compass calibration.

Fix 2

Mount GPS/Compass away from ESCs.

Fix 3

Avoid calibrating near:

- Cars
- Metal tables
- Power lines

Pre-Checks

✓ Compass calibrated

✓ GPS mounted properly

✓ No nearby magnetic sources

5. Vibration Issues

What Are Vibrations?

Vibrations occur when motors and propellers do not rotate smoothly.

Too much vibration can confuse sensors.

Example 1

Drone shakes while hovering.

Camera footage becomes blurry.

Example 2

Drone drifts despite calibration.

Mission Planner shows high vibration values.

Common Causes

Cause	**Description**
Bent Propeller	Uneven airflow
Unbalanced Propeller	Excess vibration
Loose Screws	Frame movement
Bent Motor Shaft	Motor wobble

Poor Pixhawk Mounting	Sensors affected

3 Ways to Fix It

Fix 1

Replace damaged propellers.

Fix 2

Tighten all screws.

Fix 3

Use vibration damping foam under Pixhawk.

Pre-Checks

✓ Props balanced

✓ Motors secure

✓ Frame tight

✓ Flight controller damped

6. ESC Calibration Problems

What Is ESC Calibration?

ESC calibration teaches all ESCs the same throttle range.

Without calibration:

- Motors start at different times
- Uneven thrust occurs

Example 1

Motor 1 starts first.

Motor 4 starts much later.

Example 2

Drone drifts during takeoff despite correct setup.

Common Causes

Cause	**Description**
ESC Not Calibrated	Different throttle ranges

Faulty ESC	Hardware issue
Wrong PWM Signal	Configuration problem
Different ESC Models	Inconsistent response

3 Ways to Fix It

Fix 1

Perform ESC calibration again.

Fix 2

Check ESC firmware and settings.

Fix 3

Use identical ESC models on all motors.

Pre-Checks

✓ Same ESC model

✓ Correct wiring

✓ Throttle calibration complete

✓ Battery fully charged

Emergency Troubleshooting Table

Problem	**Most Likely Cause**	**First Thing to Check**
Drone Not Arming	Calibration Issue	Mission Planner Messages
Drone Flips	Wrong Propellers	Motor Direction
GPS Not Locking	Indoor Testing	Satellite Count
Compass Error	Bad Calibration	Compass Status
Heavy Vibrations	Damaged Propeller	Propeller Condition

ESC Problem	No Calibration	ESC Calibration
RTL Not Working	No GPS Lock	Home Position
Drone Drifting	Accelerometer Error	Recalibration
One Motor Not Spinning	ESC/Motor Wiring	Connections
Short Flight Time	Weak Battery	Battery Health

Golden Rule for Beginners

Never install propellers while troubleshooting motors, ESCs, receiver, GPS, or flight controller settings.

Always:

1. Remove propellers
2. Test motors
3. Verify directions
4. Check sensors
5. Confirm calibrations

Only then install propellers and perform a hover test. This single habit prevents most beginner injuries and drone crashes.

FPV Drones (First Person View Drones)

FPV means **First Person View**. The pilot sees live video from the drone's camera through FPV goggles, a monitor, or a screen, creating the feeling of sitting inside the drone. FPV systems typically include a camera, video transmitter (VTX), antenna, and goggles/receiver. (getfpv.com)

Main FPV Components

Component	**Purpose**
Frame	Holds all components
Flight Controller	Controls the drone
ESC	Controls motor speed

Motors	Generate thrust
Propellers	Produce lift
FPV Camera	Live video feed
VTX	Sends video signal
Antenna	Improves video range
Receiver	Receives control commands
Radio Transmitter	Pilot control
Battery	Power source
FPV Goggles	View live video

Example FPV Components

- RadioMaster Boxer Radio Controller
- DakeFPV F405 BLS 55A Flight Controller & ESC Stack
- TBS Crossfire Nano Rx Pro
- Long Range 5.8G FPV Video Transmitter

How to Build an FPV Drone

Step 1

Choose the mission:

- Racing
- Freestyle
- Cinematic
- Long Range
- Indoor

Step 2

Select frame size.

Step 3

Select motor and propeller combination.

Step 4

Select ESC and Flight Controller.

Step 5

Install FPV Camera and VTX.

Step 6

Install Receiver.

Step 7

Install Battery.

Step 8

Flash Betaflight or INAV firmware.

Step 9

Configure radio and flight modes.

Step 10

Perform test flight.

FPV Drone Build Reference Table (35+ Types)

FPV Type	Frame	Motor	KV	Prop	ESC	Battery
Tiny Whoop 65	65 mm	0802	19000KV	31 mm	5A	1S 300mAh
Tiny Whoop 75	75 mm	0802	19000KV	40 mm	5A	1S 450mAh
Tiny Whoop 85	85 mm	1102	10000KV	2 inch	12A	2S 450mAh
Toothpick 2"	95 mm	1103	8000KV	2 inch	12A	2S 650mAh
Toothpick 2.5"	105 mm	1204	5000KV	2.5 inch	15A	3S 650mAh
Cinewhoop 3"	95 mm	1404	4500KV	3 inch	20A	4S 850mAh

Cinewhoop 3.5"	120 mm	1505	3600KV	3.5 inch	30A	4S 850mAh
Micro Freestyle	130 mm	1407	3800KV	4 inch	35A	4S 850mAh
Racing 5"	210 mm	2207	2500KV	5 inch	45A	6S 1300mAh
Racing Pro	220 mm	2207	2700KV	5 inch	55A	6S 1300mAh
Freestyle 5"	225 mm	2306	1900KV	5 inch	45A	6S 1500mAh
Freestyle HD	225 mm	2306	1750KV	5 inch	55A	6S 1500mAh
Freestyle GoPro	230 mm	2306	1700KV	5 inch	55A	6S 1800mAh
Long Range 4"	180 mm	2004	3000KV	4 inch	35A	4S Li-Ion
Long Range 5"	230 mm	2207	1700KV	5 inch	45A	6S Li-Ion
Long Range 7"	295 mm	2807	1300KV	7 inch	55A	6S 4000mAh
Long Range 8"	330 mm	3110	900KV	8 inch	60A	6S Li-Ion
Mountain Explorer	330 mm	2807	1300KV	7 inch	55A	6S 5000mAh
Cinematic 5"	225 mm	2306	1750KV	5 inch	55A	6S 1500mAh
Cinematic 7"	295 mm	2807	1300KV	7 inch	55A	6S 4000mAh
GoPro Carrier	250 mm	2407	1700KV	5 inch	55A	6S 1800mAh
Action Camera	250 mm	2408	1600KV	5 inch	55A	6S 1800mAh

FPV						
Night FPV	225 mm	2306	1750KV	5 inch	45A	6S 1500mAh
Search & Rescue FPV	330 mm	2807	1300KV	7 inch	60A	6S 4000mAh
Mapping FPV	330 mm	2807	1300KV	7 inch	60A	6S Li-Ion
Inspection FPV	295 mm	2807	1300KV	7 inch	55A	6S 4000mAh
FPV Delivery Prototype	450 mm	3508	700KV	12 inch	60A	6S 10000mAh
Agricultural FPV	1200 mm	6215	170KV	24 inch	80A	12S 16000mAh
Hexa FPV	550 mm	2814	700KV	12 inch	40A	6S 10000mAh
Octo FPV	650 mm	3508	580KV	15 inch	60A	6S 16000mAh
AI FPV Drone	330 mm	2807	1300KV	7 inch	55A	6S 4000mAh
Autonomous FPV	330 mm	2807	1300KV	7 inch	55A	6S 4000mAh
FPV Fixed Wing	1000 mm Wingspan	2216	1200KV	9x6	40A	4S 5000mAh
FPV VTOL	1800 mm Wingspan	3508	700KV	13 inch	60A	6S 10000mAh
Micro Long Range	160 mm	1404	3800KV	4 inch	20A	4S Li-Ion

Indoor Training FPV	75 mm	0802	19000KV	40 mm	5A	1S 450mAh

Best FPV Builds for Students

Goal	**Recommended Build**
First FPV Drone	Tiny Whoop 75
Budget FPV	Toothpick 2.5"
Learning Betaflight	5" Freestyle
Long Range FPV	7" Long Range
FPV + Autonomous Flight	7" Long Range + GPS
Research Project	7" Autonomous FPV
Aerial Cinematography	Cinewhoop 3.5"
Future Startup Prototype	7" Long Range Platform

For an Aeronautical Engineering student, a **5-inch Freestyle FPV** is usually the best first serious build because it teaches assembly, tuning, soldering, radio systems, FPV video systems, and flight dynamics while remaining affordable and easy to repair. FPV drones commonly use components such as a frame, motors, ESCs, flight controller, radio receiver, battery, FPV camera, VTX, and goggles integrated into one system. (Mepsking)

Mark4 5 Inch Carbon Fiber Analog FPV Drone Kit

₹29,649

HGLRC Wind5 Lite V2 5 Inch Frame Kit

₹5,066

Master 5 V2 Freestyle Analog FPV Drone Kit

₹30,099

RadioMaster Boxer Radio Controller

₹16,499

Obstacle Avoidance in Drones

What is Obstacle Avoidance?

Obstacle Avoidance is the ability of a drone to detect and avoid objects such as trees, buildings, poles, walls, wires, and people automatically during flight.

Instead of crashing into an object, the drone:

1. Detects the obstacle
2. Calculates a safe path
3. Slows down, stops, or changes direction

HOW OBSTACLE AVOIDANCE WORKS

Obstacle avoidance helps the drone detect objects in its path and take appropriate action to fly safely.

1 SENSOR DETECTS OBJECT

Sensors like LiDAR, Ultrasonic, Infrared, or Camera scan the surroundings and detect an object.



The sensor measures the distance and position of the obstacle.

2 FLIGHT CONTROLLER RECEIVES DATA

The sensor data is sent to the flight controller for processing.



Flight controller reads the data through serial communication (I2C / UART / CAN).

3 DISTANCE CALCULATED

The flight controller calculates the distance, direction, and size of the obstacle.



Using algorithms and trigonometry, it determines how close the obstacle is.

4 DECISION MADE

Based on the distance, speed, direction, and flight mode, the controller decides the best action.



If the obstacle is too close, the controller plans a safe path to avoid it.

5 STOP / MOVE LEFT / MOVE RIGHT / CLIMB

The drone executes the decision by adjusting its motors.

COMMON SENSORS USED

- LiDAR (Light Detection and Ranging)
- Ultrasonic Sensors
- Infrared (IR) Sensors
- Stereo Cameras / Depth Cameras
- ToF (Time of Flight) Sensors
- Radar Sensors

KEY BENEFITS

- ✓ Prevents collisions
- ✓ Enhances flight safety
- ✓ Enables autonomous navigation
- ✓ Works in GPS-denied environments
- ✓ Improves mission reliability

NOTE

Obstacle avoidance works best when sensors are properly calibrated and the environment is within the sensor's range and field of view.

Obstacle Avoidance = Sense → Analyze → Decide → Act → Fly Safely

Sensors Used for Obstacle Avoidance

Sensor	Range	Best Use
Ultrasonic Sensor	0.2–5 m	Indoor Drones
Infrared (IR) Sensor	0.1–2 m	Simple Robots
LiDAR	0.2–100+ m	Professional Drones
Optical Flow Camera	0.1–20 m	Indoor Navigation
Stereo Camera	0.5–30 m	AI Drones
Depth Camera	0.5–20 m	Autonomous Drones
Radar	1–500 m	Large UAVs
ToF Sensor	0.05–10 m	Small Drones

Obstacle Avoidance Levels

Level	Capability
Level 1	Warning Only
Level 2	Stop Before Collision
Level 3	Automatic Avoidance
Level 4	Full Autonomous Navigation

Level 5	AI-Based Path Planning

Beginner Obstacle Avoidance Build

Component	**Recommended Part**
Frame	F450
Flight Controller	Pixhawk 2.4.8
GPS	M8N GPS
Telemetry	433 MHz
Obstacle Sensor	Benewake TFmini LiDAR
Battery	3S 5200mAh
Companion Computer	Not Required

Capability

✓ Front obstacle detection
✓ Automatic stop
✓ Terrain following

Intermediate Obstacle Avoidance Build

Component	**Recommended Part**
Frame	S500
Flight Controller	Pixhawk 6C
GPS	Here 3 GPS

LiDAR	TFmini Plus
Telemetry	Holybro
Battery	4S 5200mAh

Capability

✓ Front avoidance
✓ Side avoidance
✓ Better accuracy

Advanced AI Obstacle Avoidance Build

Component	**Recommended Part**
Frame	650 mm
Flight Controller	Pixhawk 6X
Companion Computer	Raspberry Pi 5
Camera	Intel RealSense D435i
GPS	Here 4
Telemetry	Herelink
Battery	6S 10000mAh

Capability

✓ Object recognition
✓ Path planning
✓ Autonomous avoidance
✓ AI navigation

Obstacle Avoidance Sensor Selection Table

Application	Sensor
Beginner Project	HC-SR04 Ultrasonic
College Mini Project	TFmini LiDAR
Mapping Drone	TFmini Plus
Delivery Drone	TF03 LiDAR
Agriculture Drone	TF03 + Radar
Autonomous Drone	RealSense D435i
AI Research Drone	RealSense + LiDAR
Industrial UAV	Livox LiDAR

Direction-Based Sensor Placement

Position	Sensor Purpose
Front	Detect forward obstacles
Rear	Reverse protection
Left	Side avoidance
Right	Side avoidance

Bottom	Terrain following
Top	Ceiling detection

Practical Obstacle Avoidance Configurations

Configuration	**Sensors**
Front Only	1 Sensor
Front + Rear	2 Sensors
Front + Left + Right	3 Sensors
Front + Rear + Left + Right	4 Sensors
360° Coverage	6–8 Sensors or LiDAR

Common Problems

Problem	**Cause**
Drone Hits Obstacle	Sensor range too small
False Detection	Sunlight interference
Delayed Avoidance	Slow processor
Missed Objects	Sensor blind spots
Tree Branch Collision	Thin object detection issue

Example 1: Beginner F450 Obstacle Avoidance

Components

Component	Part
Frame	F450
FC	Pixhawk 2.4.8
GPS	M8N
Sensor	TFmini LiDAR
Battery	3S 5200mAh

Function

- Detect obstacle up to 12 m
- Stop before collision
- Return control to pilot

Example 2: Autonomous Mapping Drone

Components

Component	Part
Frame	650 mm
FC	Pixhawk 6X
Companion Computer	Raspberry Pi 5
Camera	RealSense D435i
LiDAR	TFmini Plus

GPS	Here 4

Function

- Detect trees
- Calculate alternate path
- Continue mission automatically

Recommended Sensors for Students

Budget	**Sensor**
₹100–₹300	HC-SR04
₹1,500–₹3,000	ToF Sensor
₹3,000–₹6,000	TFmini LiDAR
₹6,000–₹15,000	TFmini Plus
₹15,000–₹40,000	TF03 LiDAR
₹25,000–₹60,000	Intel RealSense D435i
₹60,000+	Livox LiDAR

Best Setup for an Aeronautical Engineering Student

Goal	**Recommended Setup**
Learn Basics	HC-SR04 + Arduino
Drone Obstacle Avoidance	Pixhawk + TFmini
Autonomous Navigation	Pixhawk + TFmini Plus

AI Drone Research	Pixhawk + Raspberry Pi + RealSense
Startup Prototype	Pixhawk 6X + RealSense + LiDAR

Obstacle Avoidance is a safety system that uses sensors such as LiDAR, cameras, ultrasonic sensors, or radar to detect obstacles and automatically prevent the drone from colliding with them during flight.

Computer Vision Drone

What is a Computer Vision Drone?

A Computer Vision Drone is a drone that can **see, understand, and make decisions using camera images and videos**, similar to how humans use their eyes and brain.

Unlike a normal drone that only relies on GPS and sensors, a computer vision drone can:

- Detect objects
- Follow people
- Avoid obstacles
- Identify vehicles
- Read QR codes
- Track targets
- Count objects
- Land on markers
- Navigate indoors without GPS



Components Required

1. Drone Platform

Component	Recommended
Frame	F450 / S500
Motor	2212 920KV
ESC	30A
Propeller	1045
Battery	3S 5200mAh

2. Flight Controller

Controller	**Level**
Pixhawk 2.4.8	Beginner
Pixhawk 4	Intermediate
Pixhawk 6C	Advanced
Cube Orange	Research

3. Companion Computer

A companion computer processes camera images

Computer	**Use**
Raspberry Pi 4	Beginner
Raspberry Pi 5	Intermediate
NVIDIA Jetson Nano	AI Projects
Jetson Xavier NX	Advanced AI
Jetson Orin Nano	Research
Jetson Orin NX	Industrial AI

4. Cameras

Camera	**Purpose**
Raspberry Pi Camera V3	Beginner Vision
USB Webcam	Testing
Arducam	General Vision
Intel RealSense D435i	Depth Vision
OAK-D Lite	AI Vision
OAK-D Pro	Advanced AI
ZED 2i	Professional Mapping

Computer Vision Applications

Application	**Function**
Object Detection	Detect cars, people, animals
Object Tracking	Follow moving targets
Face Detection	Identify faces
QR Code Detection	Read markers
Landing Pad Detection	Precision landing

Traffic Monitoring	Vehicle counting
Agriculture	Crop monitoring
Search & Rescue	Find missing persons
Security	Intruder detection
Warehouse Inspection	Inventory tracking

Beginner Computer Vision Drone

Component	**Recommended**
Frame	F450
Pixhawk	2.4.8
Camera	Raspberry Pi Camera
Computer	Raspberry Pi 4
GPS	M8N
Telemetry	433 MHz

Capabilities

✓ Color detection

✓ Shape detection

✓ QR detection

✓ Basic object tracking

Intermediate Computer Vision Drone

Component	Recommended
Frame	S500
Pixhawk	6C
Camera	OAK-D Lite
Computer	Raspberry Pi 5
GPS	Here 3
Telemetry	Holybro

Capabilities

✓ Object detection

✓ Human tracking

✓ Obstacle avoidance

✓ Autonomous following

Advanced AI Computer Vision Drone

Component	Recommended
Frame	650 mm
Pixhawk	Cube Orange
Camera	Intel RealSense D435i
Computer	Jetson Orin Nano

GPS	Here 4
Telemetry	Herelink

Capabilities

✓ AI navigation

✓ SLAM

✓ Obstacle avoidance

✓ Autonomous landing

✓ Indoor navigation

Popular Computer Vision Algorithms

Algorithm	**Purpose**
Color Detection	Identify colors
Edge Detection	Detect boundaries
Optical Flow	Motion tracking
ArUco Marker Detection	Precision landing
YOLO	Object detection
SSD	Object detection
MobileNet	Lightweight AI
DeepSORT	Object tracking
SLAM	Mapping and navigation

Recommended Software

Software	Purpose
OpenCV	Computer Vision
Python	Programming
ROS 2	Robotics
MAVSDK	Drone Control
DroneKit	Pixhawk Communication
ArduPilot	Flight Control
TensorFlow	AI Models
PyTorch	Deep Learning

Project Progression for Students

Level	Project
Level 1	Color Detection
Level 2	Line Following
Level 3	QR Detection
Level 4	Object Tracking

Level 5	Human Following Drone
Level 6	Obstacle Avoidance
Level 7	Autonomous Landing
Level 8	Indoor Navigation
Level 9	SLAM Drone
Level 10	Fully Autonomous AI Drone

Example 1: Human Following Drone

Hardware

- F450
- Pixhawk 2.4.8
- Raspberry Pi 4
- Pi Camera

Software

- Python
- OpenCV
- YOLO

Working

1. Camera detects person
2. Computer calculates position
3. Commands sent to Pixhawk
4. Drone follows person

Example 2: Precision Landing Drone

Hardware

- S500
- Pixhawk 6C
- OAK-D Lite

Software

- OpenCV
- ArUco Markers

Working

1. Drone searches landing marker
2. Marker detected
3. Position calculated
4. Drone aligns itself
5. Lands accurately

Component Selection Table

Goal	Camera	Computer	Flight Controller
Learn OpenCV	Pi Camera	Raspberry Pi 4	Pixhawk 2.4.8
Object Detection	OAK-D Lite	Raspberry Pi 5	Pixhawk 6C
Human Tracking	OAK-D Pro	Jetson Nano	Pixhawk 6C
AI Navigation	RealSense D435i	Jetson Orin Nano	Cube Orange
SLAM	ZED 2i	Jetson Orin NX	Cube Orange
Startup Prototype	RealSense + LiDAR	Jetson Orin NX	Cube Orange+

Common Problems

Problem	Cause
Slow Detection	Weak processor
Poor Tracking	Low camera quality
False Detection	Poor AI model
High Latency	Slow communication

Low Flight Time	Heavy hardware
Indoor Navigation Failure	Poor lighting

Best Beginner Setup (Budget Friendly)

Component	**Selection**
Frame	F450
FC	Pixhawk 2.4.8
Camera	Raspberry Pi Camera V3
Computer	Raspberry Pi 4 (4GB)
GPS	M8N
Telemetry	433 MHz
Battery	3S 5200mAh

This setup is ideal for learning **OpenCV, object detection, QR-code navigation, precision landing, and basic AI drone development** before moving to expensive Jetson-based systems.

A Computer Vision Drone is a drone equipped with cameras and image-processing computers that can detect, recognize, track, and interact with objects in its environment using computer vision and artificial intelligence techniques.

How to Integrate a Computer Vision System into a Drone

A computer vision drone is built by adding a **camera** and a **companion computer** to a normal drone, then connecting that computer to the **flight controller** using **MAVLink**. The flight controller still handles stabilization and motor control, while the companion computer processes images and sends higher-level commands or guidance data. ArduPilot specifically supports this kind of companion-computer setup for vision processing and other smart onboard tasks. (ArduPilot.org)

1) The Basic Idea

Do **not** connect the camera directly to the motors. The correct chain is:

Camera → Companion Computer → MAVLink → Flight Controller → ESC → Motors

The camera captures images, the companion computer analyzes them using computer vision, and the flight controller turns those results into safe flight actions. MAVLink is the standard lightweight message protocol used for this communication. (MAVLink)

2) What Each Part Does

Part	Job in the system
Camera	Captures video or images
Companion computer	Runs OpenCV / AI and understands the image
Flight controller	Stabilizes the drone and controls motors
MAVLink link	Carries commands and telemetry between computer and autopilot
GPS / compass / barometer	Help with navigation and position
Telemetry	Lets you monitor the drone from the ground

OpenCV is the standard computer-vision library used for image processing and vision algorithms, and companion computers are commonly used for CPU-intensive vision tasks on ArduPilot vehicles. (ArduPilot.org)

3) Hardware You Need

Level	Recommended hardware
Beginner	F450 / S500 frame, Pixhawk 2.4.8, Raspberry Pi 4, Pi Camera, M8N GPS
Intermediate	F450 / 650 mm frame, Pixhawk 4 or 6C, Raspberry Pi 5 or Jetson Nano, better camera
Advanced	650 mm+ frame, Pixhawk 6X or Cube Orange, Jetson Orin series, depth camera / LiDAR

ArduPilot's companion-computer documentation emphasizes that the onboard computer can receive MAVLink data such as GPS and use it for intelligent decisions and vision processing. (ArduPilot.org)

4) Physical Integration Steps

Step 1: Mount the camera

Place the camera where it has a clear forward or downward view, depending on the task. For tracking people or vehicles, mount it forward-facing. For landing-marker detection, mount it downward-facing. Vision systems commonly use markers or targets for tasks like precision landing. (MAVLink)

Step 2: Mount the companion computer

Fix the Raspberry Pi or Jetson on vibration-damping material, away from hot ESC wires and high-current power lines. The goal is to keep the camera feed stable and reduce electrical noise in the vision system. This is standard practice for onboard companion computers and sensor-heavy UAVs. (ArduPilot.org)

Step 3: Connect the companion computer to the flight controller

Use a serial telemetry port or UART connection and communicate through MAVLink. MAVLink is the standard protocol for vehicle-to-computer messaging and supports telemetry, mission control, and companion-computer communication. (MAVLink)

Step 4: Power the companion computer properly

Do not power a Raspberry Pi or Jetson from an unstable source. Use a proper 5V regulator or the vendor-recommended power method, because brownouts will crash the vision system even if the flight controller keeps flying. This is an integration requirement rather than a flight-controller feature. (ArduPilot.org)

Step 5: Keep the flight controller responsible for flight safety

The companion computer should send guidance, target location, or high-level commands. The autopilot should still handle stabilization, arming checks, and motor mixing. ArduPilot's companion-computer architecture is designed around this division of labor. (ArduPilot.org)

5) Software Integration Steps

Step 1: Install the vision software

Use **OpenCV** for image processing and, if needed, a deep-learning model for object detection. OpenCV is the standard library for real-time computer vision and image analysis. (GitHub)

Step 2: Install MAVLink communication tools

Use MAVSDK, DroneKit, or direct MAVLink libraries to send commands between the companion computer and the flight controller. MAVLink is the communication backbone, while MAVSDK provides telemetry access and control APIs. (MAVLink)

Step 3: Read the camera frame

The code gets each video frame, processes it, and extracts the important result. For example, it may detect a person, a landing marker, or an obstacle.

Step 4: Convert vision output into drone commands

The vision code should not say "spin motor 2 faster." Instead, it should calculate a safe **target position**, **velocity**, **heading**, or **landing offset** and send that to the autopilot through MAVLink. This is the normal companion-computer pattern in ArduPilot and MAVLink-based systems. (ArduPilot.org)

6) What Kind of Data the Vision System Can Send

Vision result	What the drone can do
Object center is left of image	Move left
Object center is right of image	Move right
Target is far away	Move forward
Target is close	Slow down or stop
Marker detected	Land on marker
Obstacle detected	Stop or reroute

For precision landing, MAVLink even has a dedicated landing-target protocol intended for onboard computer vision systems that detect a beacon or visual marker. (MAVLink)

7) Two Practical Integration Examples

Example 1: Human-following drone

A front camera sends video to a Raspberry Pi. OpenCV detects a person in the frame. The Raspberry Pi calculates whether the person is centered, left, or right, then sends movement commands through MAVLink to the flight controller. The flight controller keeps the drone stable while following the person. This uses the companion-computer architecture supported by ArduPilot. (ArduPilot.org)

Example 2: Precision landing drone

A downward camera looks for an ArUco or landing marker. The companion computer finds the marker position and sends landing-target information to the autopilot. The drone adjusts its position and lands accurately on the marked spot. MAVLink's landing-target protocol is designed for this kind of vision-assisted landing workflow. (MAVLink)

8) Best Order to Build It

Stage	What to test
1	Camera view only
2	Camera + image processing on laptop

3	Camera + companion computer
4	Companion computer + MAVLink connection
5	Ground test without propellers
6	Low-hover test in Stabilize mode
7	Vision-assisted test in a safe open area

This staged approach is important because companion computers are meant to add intelligence without replacing the autopilot's core stabilization role. (ArduPilot.org)

9) Common Mistakes

Mistake	**What happens**
Sending motor commands directly from vision code	Unsafe flight and loss of control
Using too weak a companion computer	Slow detection and lag
Poor camera mounting	Shaky, useless video
No vibration isolation	Blurry frames and bad detection
Wrong MAVLink settings	No communication with Pixhawk
Not testing on the ground first	Crash risk
Running vision and flight on the same weak processor	Overload and delays

MAVLink and ArduPilot both expect the companion computer to be correctly identified and configured, with unique system/component IDs and reliable communication. (MAVLink)

10) Beginner Pre-Checks

Check	Why it matters
Camera works in daylight and low light	Vision must be reliable
Companion computer boots every time	Prevents mission failure
MAVLink link is active	Needed for drone communication
GPS and compass are healthy	Needed for navigation
Battery can power all electronics	Prevents brownout
Flight controller still flies normally without vision	Safety backup
Vision latency is low	Delayed commands can cause crashes

11) Simple Formula for Integration Thinking

Vision System = Camera + Computer + Algorithm + Communication + Safety

Or in drone terms:

See → Understand → Decide → Send command → Autopilot executes

That is the clean engineering architecture for a computer vision drone. The flight controller remains the safety-critical layer, while the companion computer performs the vision intelligence on top of it. (ArduPilot.org)

A computer vision drone is a drone that uses a camera and an onboard computer to see objects, understand what the camera is showing, and send smart navigation commands to the flight controller for tasks such as tracking, obstacle avoidance, and precision landing. (ArduPilot.org)

AI Drones

What is an AI Drone?

An AI (Artificial Intelligence) Drone is a drone that can **learn, analyze, make decisions, and perform tasks intelligently** without requiring constant human control.

A normal autonomous drone follows pre-programmed instructions.

An AI drone can:

- Recognize objects
- Identify people
- Avoid obstacles intelligently
- Analyze situations
- Make decisions
- Learn patterns
- Navigate in unknown environments

Normal Drone vs Autonomous Drone vs AI Drone

Feature	Normal Drone	Autonomous Drone	AI Drone
Manual Control	✓	Optional	Optional
GPS Navigation	✗	✓	✓
Waypoint Mission	✗	✓	✓
Object Detection	✗	Limited	✓
Obstacle Avoidance	Basic	Basic	Intelligent
Decision Making	Pilot	Predefined Rules	AI Based
Learning Ability	✗	✗	✓
Indoor Navigation	Difficult	Limited	Excellent

AI DRONE ARCHITECTURE

High-level architecture showing how AI enables autonomous decision making in drones

1 CAMERA / SENSORS

Captures real-time visual data from the environment

- RGB Camera
- Depth Camera
- Thermal Camera
- LiDAR (Optional)

Purpose
Observe the environment in real-time

2 AI COMPUTER (Jetson / Raspberry Pi)

High-performance computer processes sensor data

or

Examples
- NVIDIA Jetson Nano / Orin
- Raspberry Pi 4 / 5

Runs AI algorithms and decision logic

3 AI MODELS

Deep learning models analyze input data to understand the environment

Object Detection

Object Tracking

Path Planning

Semantic Segmentation

AI Models
- YOLO / SSD (Detection)
- DeepSORT (Tracking)
- CNN / DNN Models
- Custom Models

4 DECISION MAKING

AI interprets results and decides the best action

Example Decisions
- Avoid Obstacle
- Follow Target
- Return Home
- Change Altitude / Path

Output
High-level commands (e.g., Move Forward, Turn Left, Ascend)

5 PIXHAWK FLIGHT CONTROLLER

Receives commands from AI computer and stabilizes the drone

- Stabilization
- Navigation (GPS, IMU)
- Sensor Fusion
- Failsafe Handling

Communication
MAVLink (UART / USB / Wi-Fi) between AI computer and Pixhawk

6 ESC (ELECTRONIC SPEED CONTROLLER)

Converts control signals from Pixhawk into power for safe motors

- Speed Control
- Signal Conversion
- Motor Protection

Function
Controls the speed of each motor

7 MOTORS (Brushless)

Generate thrust to move the drone

- Thrust Generation
- Stable Performance
- Efficient Operation

Result
Drone movement in 3D space (X, Y, Z, Yaw)

FEEDBACK LOOP
Sensors continuously provide new data to refine AI decisions for safe and adaptive flight

Outcome
Autonomous, intelligent and adaptive flight

Main Components Required

Flight Platform

Component	Beginner
Frame	F450
Motors	2212 920KV
ESC	30A
Battery	3S 5200mAh
Flight Controller	Pixhawk 2.4.8

AI Processing Unit

Device	AI Capability
Raspberry Pi 4	Basic AI
Raspberry Pi 5	Intermediate AI
Jetson Nano	Good AI
Jetson Xavier NX	Advanced AI
Jetson Orin Nano	Professional AI
Jetson Orin NX	Industrial AI

Cameras

Camera	Use
Pi Camera V3	Beginner
USB Camera	Learning
OAK-D Lite	AI Vision
RealSense D435i	Depth AI
ZED 2i	SLAM

Additional Sensors

Sensor	Purpose
GPS	Navigation
Compass	Direction
LiDAR	Distance Measurement
Radar	Long Range Detection
Optical Flow	Indoor Positioning
Ultrasonic	Short Range Avoidance

AI SOFTWARE STACK FOR DRONES

From Perception to Action – AI Powered Autonomous Flight

1 CAMERA

Captures real-time images or video from the environment.

- RGB Camera
- Stereo Camera
- Depth Camera
- IR Camera

2 OPENCV

OpenCV

Image Preprocessing
- Resize
- Denoise
- Color Conversion

→

Image Processing
- Filtering
- Edge Detection
- Feature Extraction

→

Feature Maps

Processes raw images to enhance quality and extract useful features.

- Noise Reduction
- Edge Detection
- Feature Extraction
- Perspective Transform

3 DEEP LEARNING MODEL

TensorFlow
PyTorch
ONNX

Input (Image)



CNN Backbone (Feature Extraction)

Fully Connected Layers

Person
Vehicle
Tree
...

Output (Detections)

AI model detects and classifies objects, predicts positions or behaviors.

- Object Detection
- Classification
- Segmentation
- Pose Estimation
- Tracking

4 DECISION LOGIC

Perception Input
- Detected Objects
- Distances
- Boundaries
- Paths

→

Reasoning Engine
- Rule Based
- Behavior Planner
- Path Planner
- Obstacle Avoidance

→

Action Output
- Waypoint Update
- Velocity Cmd
- Mode Change
- Land / RTL

Interprets AI results and decides next actions based on mission goals and safety rules.

5 MAVLINK

MAVLINK

MAVLINK MESSAGES

Sends commands, waypoints, and control messages to flight controller and receives telemetry data.

- Serial / UDP
- MAVLink Protocol
- Telemetry Streaming

6 PIXHAWK FLIGHT CONTROLLER



Receive Commands (MAVLink)

Flight Control Algorithms

Stabilization & Navigation

Motor Outputs & Actuators

Executes commands and controls the drone movement.

- Attitude Control
- Navigation
- Sensor Fusion
- Motor Control

SUMMARY FLOW

Camera → OpenCV → Deep Learning Model → Decision Logic → MAVLink → Pixhawk

KEY BENEFITS

- ✓ Real-time Perception
- ✓ Autonomous Decision Making
- ✓ Obstacle Avoidance
- ✓ Safe Navigation
- ✓ Intelligent Flight Control

ℹ This stack runs on a companion computer (e.g., Raspberry Pi, NVIDIA Jetson) integrated with a Pixhawk autopilot.

Required Software

Software	Purpose
Python	Programming
OpenCV	Computer Vision
TensorFlow	AI Models
PyTorch	Deep Learning
ROS2	Robotics
MAVSDK	Drone Communication
ArduPilot	Flight Control

Types of AI Drones

AI Drone Type	Application
Object Tracking Drone	Follow People
Surveillance Drone	Security
Search and Rescue Drone	Find Victims
Agricultural AI Drone	Crop Analysis
Delivery AI Drone	Route Optimization

Inspection AI Drone	Defect Detection
Mapping AI Drone	Smart Mapping
Swarm AI Drone	Multiple Drone Coordination
Military AI Drone	Reconnaissance
Indoor AI Drone	GPS-Free Navigation

AI Features and Required Hardware

AI Feature	**Camera**	**AI Computer**
Face Detection	Pi Camera	Raspberry Pi
Object Detection	OAK-D	Jetson Nano
Human Tracking	OAK-D Lite	Jetson Nano
Vehicle Detection	RealSense	Xavier NX
Obstacle Avoidance	LiDAR + Camera	Jetson Nano
SLAM	ZED 2i	Orin Nano
Swarm Intelligence	OAK-D	Orin NX
Autonomous Navigation	RealSense	Orin NX

Beginner AI Drone Build

Component	Selection
Frame	F450
Pixhawk	2.4.8
Camera	Pi Camera V3
AI Computer	Raspberry Pi 4
GPS	M8N
Telemetry	433 MHz
Battery	3S 5200mAh

AI Functions

✓ Color Detection

✓ Object Detection

✓ QR Detection

✓ Simple Tracking

Intermediate AI Drone

Component	Selection
Frame	S500
Pixhawk	6C
Camera	OAK-D Lite

AI Computer	Jetson Nano
GPS	Here 3
Telemetry	Holybro

AI Functions

✓ Person Tracking

✓ Vehicle Detection

✓ Obstacle Avoidance

✓ Smart Navigation

Advanced AI Drone

Component	**Selection**
Frame	650 mm
Pixhawk	Cube Orange
Camera	RealSense D435i
AI Computer	Jetson Orin Nano
GPS	Here 4
LiDAR	TF03
Telemetry	Herelink

AI Functions

✓ SLAM

✓ Indoor Navigation

✓ Autonomous Landing

✓ Multi-Object Tracking

✓ Real-Time Decision Making

AI Drone Development Roadmap

Level	Project
Level 1	Color Detection
Level 2	Shape Detection
Level 3	QR Detection
Level 4	Face Detection
Level 5	Object Detection
Level 6	Human Tracking
Level 7	Obstacle Avoidance
Level 8	Autonomous Landing
Level 9	SLAM Navigation
Level 10	Fully Autonomous AI Drone

Example 1: AI Human Following Drone

Working

1. Camera detects person
2. AI identifies person
3. AI calculates movement
4. Commands sent to Pixhawk
5. Drone follows target

Example 2: Search and Rescue Drone

Working

1. Drone scans disaster area
2. AI detects humans
3. GPS coordinates generated
4. Coordinates transmitted to rescue team
5. Drone continues searching

Common Problems

Problem	**Cause**
Slow Detection	Weak AI Processor
Wrong Detection	Poor Training Data
High Latency	Slow Communication
Poor Tracking	Weak Camera
Low Flight Time	Heavy Hardware
Indoor Failure	Poor SLAM Setup

AI Drone Technology Stack

Layer	**Technology**
Flight Control	Pixhawk + ArduPilot
Communication	MAVLink
Vision	OpenCV

AI	TensorFlow / PyTorch
Robotics	ROS2
Navigation	GPS + SLAM
Obstacle Avoidance	LiDAR + AI
Decision Making	Neural Networks

Best Student AI Drone (2026)

Component	**Recommended**
Frame	F450
Flight Controller	Pixhawk 2.4.8
Camera	OAK-D Lite
AI Computer	Jetson Nano
GPS	M8N
Telemetry	433 MHz
Battery	4S 5200mAh

An AI drone is a drone equipped with cameras, sensors, and artificial intelligence algorithms that can perceive its environment, analyze information, make decisions, and perform tasks intelligently with minimal human intervention.

Swarm Drones

What are Swarm Drones?

A **Drone Swarm** is a group of multiple drones that communicate, coordinate, and work together to complete a mission.

Instead of one drone doing all the work, many drones cooperate like a colony of ants, a flock of birds, or a school of fish.

Simple Definition

Drone Swarm = Multiple Drones + Communication + Coordination + Teamwork

Real-Life Examples

Example 1: Drone Light Show

100–5000 drones fly together and create shapes in the sky.

Examples include displays by companies such as Intel.

Example 2: Search and Rescue

10 drones search different parts of a forest simultaneously.

Each drone covers a specific area and shares information with the others.

Single Drone vs Swarm Drone

Feature	**Single Drone**	**Swarm Drones**
Number of Drones	1	Multiple
Area Coverage	Small	Large
Mission Speed	Slow	Fast
Fault Tolerance	Low	High
Cost	Lower	Higher
Complexity	Simple	Complex



Each drone knows:

- Its own position
- Position of nearby drones
- Mission objective
- Safety distance

Types of Drone Swarms

Swarm Type	**Description**
Centralized Swarm	One drone or ground station controls all drones
Decentralized Swarm	Drones make decisions together
Leader-Follower Swarm	One leader drone guides others
Fully Autonomous Swarm	No leader, collective intelligence
AI Swarm	Uses AI for decision-making

Components Required

Each Drone Needs

Component	**Purpose**
Flight Controller	Controls drone
GPS	Position information
Telemetry Radio	Communication
Receiver	Manual override
Battery	Power
Motors	Flight
Sensors	Awareness

Communication Systems-Swarm drones must communicate.

Communication Method	**Range**
Wi-Fi	Short
Telemetry Radios	Medium
Mesh Network	Long
LTE/5G	Very Long
Custom RF Links	Specialized



Leader-Follower

Leader

↓

Drone 2

Drone 3

Drone 4

Leader decides path.

Followers maintain formation.

Fully Distributed

Drone 1 ↔ Drone 2

↕ ↕

Drone 3 ↔ Drone 4

Every drone shares information.

No single point of failure.

Common Swarm Formations

Formation	Use
Line	Inspection
V Formation	Efficient travel
Circle	Surveillance
Grid	Mapping
Triangle	Military and search missions
Dynamic Formation	AI swarms

Swarm Drone Applications

Application	Benefit
Mapping	Faster coverage
Agriculture	Large-field spraying
Search & Rescue	Rapid searching
Defense	Reconnaissance
Border Surveillance	Wide coverage
Delivery	Multiple packages

Environmental Monitoring	Data collection
Disaster Response	Fast assessment

Software Used

Software	**Purpose**
ArduPilot	Flight control
PX4	Swarm research
ROS 2	Multi-robot communication
MAVLink	Communication protocol
MAVSDK	Drone programming
Gazebo	Simulation
AirSim	AI simulation

Beginner Swarm Setup (2–3 Drones)

Component	**Selection**
Frame	F450
Flight Controller	Pixhawk 2.4.8
GPS	M8N

Telemetry	433 MHz
Battery	3S 5200mAh
Communication	MAVLink

Capability

✓ Formation flying

✓ Basic coordination

✓ Mission sharing

Intermediate Swarm Setup (5–10 Drones)

Component	**Selection**
Frame	S500
Flight Controller	Pixhawk 6C
GPS	Here 3
Communication	Mesh Network
Companion Computer	Raspberry Pi 5

Capability

✓ Autonomous formations

✓ Cooperative missions

✓ Area division

Advanced AI Swarm

Component	Selection
Frame	650 mm
Flight Controller	Cube Orange
AI Computer	Jetson Orin Nano
Communication	Mesh + LTE
Sensors	LiDAR + Camera

Capability

✓ Autonomous decision making

✓ Dynamic formation changes

✓ Cooperative target tracking

✓ Swarm intelligence

How Drones Avoid Colliding in a Swarm

Each drone continuously shares:

- GPS position
- Speed
- Direction

Basic separation logic:

If Distance < Safe Distance

↓

Move Away

Example

Drone A and Drone B approach too closely.

Swarm software commands one drone to move left and the other right.

Swarm Levels

Level	Capability
Level 1	Simultaneous flight
Level 2	Shared waypoints
Level 3	Formation flying
Level 4	Cooperative missions
Level 5	AI swarm intelligence

Example 1: Mapping Swarm

10 drones.

Each drone maps a different section.

Result:

- Faster mapping
- Reduced mission time
- Larger coverage area

Example 2: Search and Rescue Swarm

20 drones.

Each drone searches a different grid.

If one drone finds a target:

1. GPS location recorded
2. Data sent to swarm
3. Nearby drones assist

Common Problems

Problem	Cause
Drone Collision	Poor separation logic
Communication Loss	Weak network
GPS Drift	Poor satellite coverage
Formation Break	Incorrect positioning
Leader Failure	Centralized system issue
Battery Differences	Uneven endurance

Roadmap for Students

Stage	Project
Stage 1	Single Pixhawk Drone
Stage 2	GPS Waypoint Mission
Stage 3	Telemetry Communication
Stage 4	Two-Drone Coordination
Stage 5	Leader-Follower Swarm
Stage 6	Formation Flying

Stage 7	Five-Drone Swarm
Stage 8	AI Swarm
Stage 9	Swarm with Computer Vision
Stage 10	Autonomous Research Swarm

Best Swarm Project for an Aeronautical Engineering Student

Phase 1: 2 × F450 drones + Pixhawk 2.4.8 + GPS + Telemetry
Phase 2: Formation flying using MAVLink and ROS 2
Phase 3: AI-based swarm coordination using Jetson and computer vision

This progression teaches flight control, networking, autonomy, AI, and multi-agent systems—the same foundations used in advanced research, defense UAV systems, and next-generation autonomous drone startups.

Drone Safety & Regulations (India)

What is DGCA?

The Directorate General of Civil Aviation (DGCA) is India's civil aviation authority and regulates drone operations in India. Drone operations are governed through the Drone Rules and the Digital Sky ecosystem. (Directorate General of Civil Aviation)

Why Drone Rules Exist

Drone rules are designed to:

- Protect people on the ground
- Prevent collisions with aircraft
- Protect sensitive locations
- Ensure responsible drone operations
- Enable safe commercial drone use

(DigitalSky)

Basic DGCA Drone Rules for Beginners

Drone Categories

Category	**Weight**
Nano	Up to 250 g
Micro	250 g – 2 kg
Small	2 kg – 25 kg
Medium	25 kg – 150 kg
Large	Above 150 kg

These categories are defined under India's Drone Rules. (Press Information Bureau)

Digital Sky Platform

The Digital Sky platform is India's online drone management system.

Functions include:

- Drone registration
- Permissions
- Airspace information
- Regulatory compliance

Official portal:

Digital Sky Platform

(DigitalSky)

What is NPNT?

NPNT = No Permission, No Takeoff

This means the drone must receive digital permission before flight where applicable.

Without permission:

❌ **Drone cannot legally operate in restricted situations.**

(Dronevex)

Airspace Zones

India divides airspace into different zones.

Zone	Meaning
Green Zone	Drone operations generally permitted subject to rules
Yellow Zone	Controlled airspace requiring additional authorization
Red Zone	Flying prohibited without special permission

(www.slideshare.net)

Safe Flying Practices

Rule 1: Always Fly in Open Areas

Good Example

✓ Large playground

✓ Open agricultural field

Bad Example

✗ Crowded market

✗ Busy road

Rule 2: Maintain Visual Line of Sight

Always keep the drone visible.

Good Example

Drone flying 100 m away and clearly visible.

Bad Example

Drone flying behind buildings.

Rule 3: Avoid Airports

Never fly near airports or aircraft operating areas unless properly authorized.

Why?

Aircraft travel much faster than drones.

A collision can be extremely dangerous.

(Directorate General of Civil Aviation)

Rule 4: Check Weather

Safe Conditions

✓ Clear sky

✓ Low wind

Unsafe Conditions

✗ Rain

✗ Thunderstorm

✗ Strong winds

Rule 5: Check Battery Before Flight

Never fly with:

- Swollen battery
- Damaged battery
- Loose connectors

Pre-Flight Safety Checklist

Check	Status
Battery Charged	✓
GPS Lock	✓
Compass Calibrated	✓
Propellers Tightened	✓
Frame Inspected	✓
Receiver Working	✓
Flight Controller Healthy	✓
Weather Suitable	✓

Battery Handling Safety

LiPo batteries store large amounts of energy and must be handled carefully.

Battery Inspection

Before every flight check:

Item	What to Look For
Battery Body	No swelling
Wires	No cuts
Connector	No damage
Cells	Balanced voltage

Example 1

Healthy Battery

✓ Flat shape

✓ Normal temperature

✓ Balanced cells

Safe to fly.

Example 2

Damaged Battery

✗ Swollen

✗ Hot

✗ Damaged wires

Do not use.

Charging Safety

Correct Method

1. Use LiPo balance charger.
2. Select correct battery type.
3. Select correct cell count.
4. Charge in safe area.

Wrong Method

✗ Using wrong charger

✗ Charging unattended

✗ Charging near flammable materials

Battery Storage Rules

Condition	Recommended Voltage
Full Charge	4.2 V per cell
Storage	~3.8 V per cell
Minimum Safe Voltage	~3.5 V per cell

Battery Fire Prevention

Safety Rule	Reason
Use LiPo Bag	Contains fire risk
Do Not Puncture Battery	Prevents short circuits
Avoid Water Exposure	Prevents damage
Keep Away from Heat	Prevents thermal runaway
Store in Cool Place	Improves battery life

Common Beginner Safety Mistakes

Mistake	Consequence
Flying Without GPS Lock	RTL may fail
Wrong Propeller Installation	Drone flips
Loose Battery	Drone instability

Flying in Strong Wind	Loss of control
Ignoring Low Battery Warning	Crash risk
Flying Near Crowds	Injury risk
Skipping Compass Calibration	Navigation errors
Charging Battery Unattended	Fire risk

Emergency Procedures

If Drone Loses Control

1. Stay calm.
2. Switch to RTL (if available).
3. Move away from people.
4. Monitor battery level.

If Battery Gets Hot

1. Disconnect immediately.
2. Move battery to a safe open area.
3. Allow it to cool naturally.
4. Do not recharge until inspected.

If Drone Crashes

1. Disconnect battery first.
2. Check frame damage.
3. Inspect propellers.
4. Inspect motor shafts.
5. Verify GPS and antenna connections.

Golden Rules for Beginners

1. **Remove propellers during testing.**
2. **Never fly over people.**
3. **Wait for GPS lock before takeoff.**
4. **Check battery health before every flight.**
5. **Perform a complete pre-flight inspection.**
6. **Practice in open areas first.**
7. **Follow DGCA and Digital Sky regulations.**

Drone safety is the process of operating, maintaining, and handling a drone responsibly to prevent accidents, injuries, equipment damage, and violations of aviation regulations. Following DGCA rules, safe flying practices, and proper battery handling ensures safe and successful drone operations.

Drone Rules, License, Flying Zones & Penalties in India (Beginner Guide)

Important: Drone regulations can change. Always verify the latest requirements on the official Digital Sky and DGCA portals before flying. (DigitalSky)

Drone Categories

Category	Weight
Nano	Up to 250 g
Micro	250 g – 2 kg
Small	2 kg – 25 kg
Medium	25 kg – 150 kg
Large	Above 150 kg

(Directorate General of Civil Aviation)

Do You Need a License?

Drone Type	Hobby Flying	Commercial Flying
Nano (<250g)	Generally no pilot license required for basic recreational use	Depends on operation
Micro (250g–2kg)	Rules may require registration/compliance	Remote Pilot Certificate generally required
Small & Above	Higher compliance requirements	Remote Pilot Certificate required

(Drone Pathshala)

Remote Pilot Certificate (RPC)

Requirement	Details
Minimum Age	18 Years
Education	Class 10 Pass
Training	DGCA-approved RPTO
Exam	Required
Validity	Typically 10 Years
Purpose	Commercial and professional drone operations

(Drone Pathshala)

Drone Registration Requirements

Drone Type	Registration Requirement
Nano Model Drone	Simplified requirements
Micro and Above	Registration/UIN requirements may apply
Commercial Drone	Registration mandatory
Government Projects	Registration mandatory

Airspace Zones

Zone	Can You Fly?
Green Zone	Generally permitted subject to applicable rules
Yellow Zone	Requires additional authorization
Red Zone	Central Government permission required

(DigitalSky)

Examples of Places You Should NOT Fly

If you are creating a **Drone Operation Risk Assessment Table** (based on Indian UAV regulations and general aviation safety practices), you can complete it as follows:

Location	Risk Level	Reason
Airports	**Very High Risk**	Possibility of collision with manned aircraft during takeoff and landing operations.
Military Areas	**Very High Risk**	National security concerns, sensitive operations, restricted airspace.
Defence Installations	**Very High Risk**	Surveillance risk, security threat, unauthorized imaging restrictions.
International Borders	**Very High Risk**	National security concerns and potential cross-border incidents.
Strategic Infrastructure	**High Risk**	Includes ports, power plants, oil refineries, communication hubs, dams, and transportation networks.
Nuclear Facilities	**Very High Risk**	Critical national infrastructure with strict security restrictions.
Crowded Events	**High Risk**	Risk of injury, panic, property damage, and loss of control over people.
Government Security Areas	**Very High Risk**	Includes Parliament, government complexes, VIP movement zones, and security-sensitive locations.
Urban Residential Areas	**Medium to High Risk**	Dense population, buildings, and limited emergency landing options.
Industrial Areas	**Medium Risk**	Presence of machinery, hazardous materials, and workers.
Highways & Railways	**High Risk**	Potential distraction to drivers and risk to public transport systems.
Forest Areas	**Medium Risk**	Signal interference, wildlife disturbance, and emergency recovery difficulties.
Agricultural Fields	**Low to Medium Risk**	Generally safer with fewer people, commonly used for agricultural drone operations.
Coastal Areas	**Medium Risk**	Strong winds, corrosion, and possible interference with maritime operations.
Open Rural Areas	**Low Risk**	Sparse population and large emergency landing zones.
Mountainous Regions	**Medium Risk**	Turbulence, GPS issues, terrain collision risks.
Water Bodies (Lakes/Rivers)	**Medium Risk**	Risk of drone loss due to water impact and difficult recovery.
Educational Campuses	**Medium Risk**	Presence of students and buildings requiring careful operation.
Construction Sites	**Medium Risk**	Cranes, workers, obstacles, and dust affecting flight safety.
Disaster Zones	**High Risk**	Emergency response operations and unpredictable conditions.

Risk Classification

Risk Level	Description
Low	Minimal threat to people, property, and airspace users.
Medium	Requires additional precautions and planning.
High	Significant operational and safety risks; permissions often required.
Very High	Restricted or prohibited operations without special government authorization.

These locations are often restricted or require special permission. (DigitalSky)

Safe Flying Limits

Rule	Recommendation
Maintain Visual Line of Sight (VLOS)	Yes
Fly in Open Areas	Yes
Fly Near Airport	No (unless authorized)
Fly Over Crowds	No
Fly During Storms	No
Fly After Alcohol/Drugs	No
Check Battery Before Flight	Always
Check GPS Lock	Always

(DigitalSky)

Digital Sky Platform

Purpose	Use
Registration	Drone registration
Airspace Map	Check fly zones
Flight Planning	Submit plans
Permissions	Obtain approvals
Compliance	Regulatory management

Official Portal:

Digital Sky Platform

NPNT (No Permission No Takeoff)

Term	Meaning
NPNT	No Permission No Takeoff
Purpose	Prevent unauthorized flights
Managed Through	Digital Sky Platform

Common Violations and Possible Penalties

Violation	Possible Consequences
Flying Unregistered Drone	Fine, confiscation, legal action
Flying in Red Zone	Fine and legal action
Commercial Flying Without Authorization	Penalties and enforcement action
Flying Above Permitted Limits	Penalties
Flying BVLOS Without Approval	Enforcement action
Ignoring DGCA Rules	Monetary penalties and possible prosecution

Recent legal summaries indicate penalties can reach up to ₹1 lakh for serious violations depending on the offense. (QuadX India Aerial Systems)

Can an FIR Be Filed?

Situation	Possible Outcome
Flying Near Sensitive Defence Areas	FIR possible
Security Threat	FIR possible
Endangering Aircraft	FIR possible
Intentional Restricted-Zone Violation	FIR possible
Smuggling or Illegal Activities	FIR possible

Weaponized Drone Use	Criminal prosecution

Serious airspace violations and operations near strategic infrastructure can trigger criminal proceedings. (Sigma Chambers)

Cases That Can Become Criminal Offences

Activity	**Risk Level**
Flying Near Airport Runway	Very High
Flying Over Military Bases	Very High
Carrying Weapons	Extremely High
Smuggling Using Drone	Extremely High
Surveillance of Restricted Facilities	Very High
Interfering With Aircraft Operations	Extremely High

(Sigma Chambers)

Insurance Requirements

Drone Category	**Insurance**
Nano	Often exempt from some requirements
Commercial Operations	Third-party insurance generally required
Professional Services	Strongly recommended/required depending on operation

(Neeti Niyaman)

Practical Guide for an Engineering Student

If You Build:

F450 + Pixhawk + GPS + Camera

Before flying:

Step	Required
Register if applicable	✓
Check Digital Sky Airspace Map	✓
Verify Green Zone	✓
Check GPS Lock	✓
Perform Compass Calibration	✓
Check Battery Health	✓
Maintain Visual Contact	✓
Avoid Crowded Areas	✓

What You Can Legally Do as a Beginner

Activity	Generally Allowed?
Learn Drone Building	✓
Fly in Open Field	✓

Test Pixhawk Missions in Allowed Airspace	✓
Learn Autonomous Flight	✓
Mapping Projects (with compliance)	✓
College Research Projects	✓
FPV Practice in Safe Areas	✓

Always verify local airspace restrictions before every flight. (DigitalSky)

Golden Rule

Before Every Flight

Check Airspace

↓

Check Registration

↓

Check Battery

↓

Check GPS

↓

Check Compass

↓

Check Weather

↓

Fly Only in Safe Area

A beginner should treat a drone like a small aircraft, not a toy. Following DGCA rules, Digital Sky airspace guidance, and proper safety procedures will prevent most legal and operational problems. (DigitalSky)

Beginner Drone Projects

These projects are arranged from **easy → advanced** and are suitable for diploma, B.Tech, mini-projects, workshops, hackathons, and research beginners.

Project 1: Simple Quadcopter

Objective

Build and fly a manually controlled quadcopter.

Parameter	Details
Project Level	Beginner
Estimated Cost	₹8,000 – ₹15,000
Duration	1–2 Weeks
Frame	F450
Flight Controller	KK2.1.5 / Pixhawk 2.4.8
Motors	2212 920KV ×4
ESC	30A ×4
Propellers	1045
Battery	3S 5200mAh
Transmitter	FlySky FS-i6X
Receiver	FS-iA6B
GPS	Not Required

Telemetry	Not Required
Payload	None
Flight Time	10–15 Minutes
Flight Modes	Stabilize
Skills Learned	Wiring, ESC setup, calibration, manual flight
Software	Mission Planner (Optional)
Main Learning Outcome	Understanding drone fundamentals
Challenges	Motor direction, propeller installation
Future Upgrade	Add GPS and telemetry

Expected Outcomes

✓ Stable Hover

✓ Manual Flight

✓ Basic Drone Assembly Experience

Project 2: GPS Autonomous Quadcopter

Objective :

Build a drone capable of waypoint navigation and Return-To-Home.

Parameter	**Details**
Project Level	Beginner to Intermediate
Estimated Cost	₹15,000 – ₹30,000
Duration	2–4 Weeks
Frame	F450 / S500
Flight Controller	Pixhawk 2.4.8
Motors	2212 920KV ×4
ESC	30A ×4
Propellers	1045
Battery	4S 5200mAh
GPS	M8N GPS
Telemetry	433 MHz
Transmitter	FlySky FS-i6X
Receiver	FS-iA10B

Mission Planner	Required
Flight Modes	Stabilize, Loiter, RTL, Auto
Waypoint Mission	Yes
Return To Launch	Yes
Geofencing	Yes
Flight Time	15–20 Minutes
Skills Learned	GPS navigation, mission planning
Applications	Survey, mapping, research
Challenges	Compass calibration, GPS lock
Future Upgrade	Computer vision

Expected Outcomes

✓ Autonomous Flight

✓ Waypoint Navigation

✓ GPS Position Hold

✓ RTL Functionality

Project 3: Agricultural Drone Prototype

Objective

Develop a small-scale crop-spraying and agricultural monitoring drone.

Parameter	**Details**
Project Level	Intermediate
Estimated Cost	₹35,000 – ₹80,000
Duration	1–2 Months
Frame	650 mm / X650
Flight Controller	Pixhawk 6C
Motors	3508 580KV ×4
ESC	50A ×4
Propellers	13–15 inch
Battery	6S 10000mAh
GPS	Here 3 GPS
Telemetry	Holybro Telemetry
Spray Tank	1–2 Liters
Pump	12V DC Pump

Nozzles	Agricultural Spray Nozzles
Payload Capacity	1–2 kg
Flight Time	12–18 Minutes
Flight Modes	Auto, Loiter, RTL
Waypoint Mission	Yes
Terrain Following	Optional
Skills Learned	Payload integration, spraying systems
Applications	Precision agriculture
Challenges	Weight distribution
Future Upgrade	AI crop analysis

Expected Outcomes

✓ Automated Spraying

✓ Precision Agriculture Concepts

✓ Payload Management Experience

Project 4: Delivery Drone Concept

Objective

Design a prototype drone capable of carrying and delivering small packages.

Parameter	**Details**
Project Level	Intermediate to Advanced
Estimated Cost	₹50,000 – ₹1.5 Lakhs
Duration	2–3 Months
Frame	800–1000 mm
Flight Controller	Cube Orange
Motors	6215 170KV ×4
ESC	80A ×4
Propellers	22–24 inch
Battery	8S 16000mAh
GPS	Here 4
Telemetry	Herelink
Payload Capacity	2–5 kg
Package Release System	Servo Mechanism
Flight Time	15–25 Minutes

Waypoint Navigation	Yes
Autonomous Delivery	Yes
RTL	Yes
Geofencing	Yes
Skills Learned	Logistics, payload systems
Applications	Medicine delivery, logistics
Challenges	Battery consumption
Future Upgrade	AI route optimization

Expected Outcomes

✓ Package Transport

✓ Autonomous Delivery Concept

✓ Logistics System Understanding

Project 5: Obstacle Avoidance Drone

Objective

Build a drone capable of detecting and avoiding obstacles automatically.

Parameter	**Details**
Project Level	Advanced
Estimated Cost	₹30,000 – ₹1 Lakh
Duration	1–3 Months

Frame	S500 / 650 mm
Flight Controller	Pixhawk 6C
Motors	2216 880KV ×4
ESC	40A ×4
Propellers	1147
Battery	4S 5200–10000mAh
GPS	Here 3
Telemetry	Holybro
Obstacle Sensor	TFmini LiDAR
Companion Computer	Raspberry Pi 5
Camera	Pi Camera V3
Flight Time	15–20 Minutes
Obstacle Detection	Yes
Obstacle Avoidance	Yes
Autonomous Flight	Yes
Skills Learned	Computer vision, sensor fusion

Applications	Inspection, surveillance
Challenges	Sensor tuning
Future Upgrade	AI navigation

Expected Outcomes

✓ Obstacle Detection

✓ Automatic Avoidance

✓ Autonomous Navigation

Quick Comparison Table

Parameter	**Simple Quadcopter**	**GPS Quadcopter**	**Agriculture Drone**	**Delivery Drone**	**Obstacle Avoidance Drone**
Difficulty	Easy	Medium	Medium	Hard	Hard
Cost	Low	Medium	High	Very High	High
GPS	No	Yes	Yes	Yes	Yes
Telemetry	No	Yes	Yes	Yes	Yes
Autonomous Flight	No	Yes	Yes	Yes	Yes
Payload	No	Low	Medium	High	Low
Sensors	Basic	GPS	GPS + Spray System	GPS + Delivery System	GPS + LiDAR

Research Value	Low	Medium	High	Very High	Very High
Startup Potential	Low	Medium	High	Very High	Very High

Recommended Sequence for my Students

Year	**Project**
1st Year	Simple Quadcopter
1st–2nd Year	GPS Autonomous Quadcopter
2nd Year	Obstacle Avoidance Drone
3rd Year	Agricultural Drone Prototype
3rd–4th Year	Delivery Drone Concept

This progression builds skills in **electronics → flight control → autonomy → sensing → payload integration → commercial drone systems**, which is an excellent foundation for aerospace R&D, drone startups, ISRO/DRDO projects, and advanced UAV research.

Motor KV Table

What is KV Rating?

KV (RPM per Volt) indicates how many revolutions per minute (RPM) a motor spins for every 1 Volt applied without load.

Formula

$$RPM = KV \times Voltage$$

Example

Motor	Battery	Approx. RPM
1000KV	11.1V (3S)	11,100 RPM
920KV	14.8V (4S)	13,616 RPM
2300KV	22.2V (6S)	51,060 RPM

KV Selection Rule

KV Range	Characteristics
High KV	High Speed, Small Propellers
Medium KV	Balanced Performance
Low KV	High Torque, Large Propellers

Detailed Motor KV Selection Table

Motor Size	KV	Battery	Propeller	Typical Frame	Application
0702	25000–30000KV	1S	31mm	Tiny Whoop	Indoor FPV
0802	19000–25000KV	1S	31–40mm	Tiny Whoop	Indoor Racing
1102	10000–19000KV	2S	2 inch	75–85mm	Micro FPV
1103	8000–10000KV	2S	2 inch	Toothpick	Micro FPV

1204	5000–8000KV	2–3S	2.5 inch	100mm	Micro Freestyle
1404	3800–4500KV	4S	3 inch	Cinewhoop	Cinematic FPV
1505	3600–4000KV	4S	3.5 inch	Cinewhoop	Video Capture
1806	2300–2700KV	3S	5 inch	Mini Quad	Beginner FPV
2204	2300KV	3–4S	5 inch	250 Frame	Racing
2205	2300–2600KV	4S	5 inch	210–250mm	Racing
2206	2300–2500KV	4–6S	5 inch	FPV Frame	Racing
2207	1700–2700KV	4–6S	5 inch	FPV Frame	Racing/Freestyle
2306	1700–1900KV	6S	5 inch	Freestyle	Cinematic
2407	1700KV	6S	5 inch	Freestyle	GoPro Carrying
2507	1500KV	6S	6 inch	Long Range	FPV LR
2806.5	1300KV	6S	7 inch	Long Range	Explorer Drone
2807	900–1300KV	6S	7 inch	Long Range	Mapping
3110	700–900KV	6S	8 inch	Long Range	Inspection
3508	580–700KV	6S	12–15 inch	650 Frame	Photography
3510	580KV	6S	15 inch	Mapping UAV	Survey

4006	380KV	6S	15–16 inch	Heavy Lift	Research
4008	380KV	6S	15–18 inch	Research UAV	Inspection
4114	320KV	6S–8S	18 inch	Delivery Drone	Heavy Payload
5010	300KV	8S	18–20 inch	Cargo UAV	Delivery
5212	280KV	8S	20 inch	Survey Drone	Mapping
6015	200KV	12S	22 inch	Heavy Lift	Delivery
6215	170KV	12S	22–24 inch	Agriculture	Spraying
6215 Pro	170KV	12S	24 inch	Agri Drone	Crop Spraying
7010	150KV	12S	26 inch	Heavy Lift	Cargo
7215	150KV	12S	28 inch	Agriculture	10L Sprayer
8017	120KV	12S	30 inch	Heavy Lift	Industrial UAV
8120	120KV	12S	32 inch	Agriculture	20L Sprayer
10020	100KV	14S	34 inch	Cargo Drone	Logistics
12028	80KV	14S	36–40 inch	Heavy Cargo	Industrial
15035	60KV	14S–18S	40+ inch	Large UAV	Research

18040	50KV	18S	42+ inch	Military Scale	Specialized UAV

KV vs Propeller Relationship

KV	**Recommended Propeller**
25000KV	31mm
19000KV	40mm
10000KV	2 inch
5000KV	2.5 inch
3800KV	3 inch
2300KV	5 inch
1700KV	5–6 inch
1300KV	7 inch
700KV	12 inch
580KV	15 inch
380KV	15–18 inch
170KV	22–24 inch
120KV	30–32 inch

80KV	36–40 inch

KV Selection by Application

Application	**Typical KV**
Indoor Tiny Whoop	19000–30000KV
Micro FPV	8000–15000KV
Racing Drone	2300–2700KV
Freestyle Drone	1700–1900KV
Cinewhoop	3600–4500KV
Long Range FPV	900–1500KV
Beginner F450	920–1000KV
S500 Drone	800–920KV
Photography Drone	580–700KV
Mapping Drone	380–580KV
Research Drone	380KV
Delivery Drone	170–320KV

Agriculture Drone	120–170KV
Heavy Lift Drone	50–120KV

Easy KV Rule for Beginners

If You Want	**Choose**
High Speed	High KV Motor
Long Flight Time	Lower KV Motor
Heavy Payload	Low KV Motor
Small Propeller	High KV Motor
Large Propeller	Low KV Motor
Beginner F450	920KV
FPV Racing	2300KV
Agriculture Drone	170KV
Delivery Drone	170–300KV

Beginner Tip

For most first-time builders using **F450 or S500 frames**, **2212 920KV motors with 1045 propellers and a 3S/4S battery** are one of the safest and most proven combinations. They provide good stability, reasonable flight time, easy tuning, and affordable replacement costs.

Propeller Selection Table

What is a Propeller?

A propeller converts the motor's rotational motion into thrust by pushing air downward, generating lift for the drone.

Propeller Naming Convention

Example: **1045 Propeller**

10 = Diameter (inches)

4.5 = Pitch (inches)

Meaning

Parameter	**Description**
Diameter	Total propeller size
Pitch	Distance moved forward in one revolution (theoretical)

Propeller Size vs Application

Propeller Size	**Typical Application**
31mm	Tiny Whoop
40mm	Indoor FPV
2 inch	Micro FPV
3 inch	Cinewhoop
5 inch	FPV Racing
6 inch	Long Range FPV

7 inch	Explorer Drone
8 inch	Inspection Drone
10 inch	Beginner Quadcopter
12 inch	Photography Drone
15 inch	Mapping Drone
18 inch	Heavy Lift Drone
22 inch	Delivery Drone
24 inch	Agriculture Drone
30 inch	Industrial UAV
40 inch	Heavy Cargo UAV

Detailed Propeller Selection Table

Propeller	**Diameter**	**Pitch**	**Motor KV**	**Battery**	**Application**
31mm	1.2"	Low	25000KV	1S	Tiny Whoop
40mm	1.6"	Low	19000KV	1S	Indoor FPV
2x2	2"	2"	1102	2S	Micro FPV
2.5x2.5	2.5"	2.5"	1204	3S	Toothpick

3x3	3"	3"	1404	4S	Cinewhoop
3.5x3.5	3.5"	3.5"	1505	4S	Cinematic
4x4	4"	4"	1806	4S	Micro Freestyle
5x4.3	5"	4.3"	2207	6S	Racing
5x4.5	5"	4.5"	2306	6S	Freestyle
5x5	5"	5"	2207	6S	High Speed Racing
6x4	6"	4"	2507	6S	Long Range
7x4	7"	4"	2807	6S	Explorer Drone
8x4.5	8"	4.5"	3110	6S	Inspection
9047	9"	4.7"	1000KV	3S	F330
9443	9.4"	4.3"	920KV	3S	F330/F450
1045	10"	4.5"	920KV	3S/4S	F450
1047	10"	4.7"	920KV	4S	F450
1145	11"	4.5"	800KV	4S	S500
1147	11"	4.7"	800KV	4S	S500
1245	12"	4.5"	700KV	6S	Photography

1260	12"	6"	700KV	6S	Fast Photography
1345	13"	4.5"	580KV	6S	Mapping
1365	13"	6.5"	580KV	6S	Survey
1447	14"	4.7"	580KV	6S	Inspection
1555	15"	5.5"	380KV	6S	Research UAV
1655	16"	5.5"	380KV	6S	Heavy Lift
1755	17"	5.5"	350KV	6S	Heavy Lift
1855	18"	5.5"	320KV	8S	Delivery
2055	20"	5.5"	280KV	8S	Cargo UAV
2266	22"	6.6"	170KV	12S	Delivery Drone
2470	24"	7"	170KV	12S	Agriculture
2875	28"	7.5"	150KV	12S	10L Sprayer
3090	30"	9"	120KV	12S	Heavy Lift
3285	32"	8.5"	120KV	12S	20L Agri Drone
3610	36"	10"	80KV	14S	Industrial UAV
4012	40"	12"	60KV	14S	Cargo UAV

Propeller Selection by Frame

Frame	Recommended Propeller
65mm Tiny Whoop	31mm
75mm Tiny Whoop	40mm
95mm Toothpick	2–2.5 inch
220mm Racing	5 inch
F330	8–9 inch
F450	10 inch
S500	10–12 inch
650mm Frame	13–15 inch
800mm Frame	18–20 inch
1200mm Agri Frame	24–32 inch

Propeller Selection by Mission

Mission	Propeller
Indoor FPV	31–40mm
Racing	5 inch
Freestyle	5 inch
Cinematic	3–5 inch
Long Range	6–7 inch
Beginner Drone	10 inch
Photography	12 inch
Mapping	13–15 inch
Research	15–18 inch
Delivery	18–24 inch
Agriculture	24–32 inch
Cargo Transport	30–40 inch

Diameter vs Performance

Diameter Increase	**Effect**
Diameter ↑	Thrust ↑
Diameter ↑	Payload Capacity ↑
Diameter ↑	Efficiency ↑
Diameter ↑	Current Draw ↑
Diameter ↑	Speed ↓

Pitch vs Performance

Pitch Increase	**Effect**
Pitch ↑	Speed ↑
Pitch ↑	Current Draw ↑
Pitch ↑	Efficiency ↓ (Hover)
Pitch ↑	Motor Load ↑

Example

Propeller	Result
1045	Better hover and endurance
1060	Faster forward flight
1260	Higher speed mapping
2470	High-thrust agriculture

Material Comparison

Material	Advantages	Disadvantages
Plastic	Cheap, flexible	Less efficient
ABS Plastic	Durable	Moderate performance
Nylon	Strong	Slightly heavier
Carbon Fiber	Lightweight, efficient	Expensive
Carbon Reinforced	Strong and efficient	Higher cost
Wood	Smooth operation	Rarely used in drones

CW and CCW Propellers

Type	Rotation
CW	Clockwise
CCW	Counter-Clockwise

Quadcopter Example

Front

Motor 1 (CW) Motor 2 (CCW)

Motor 3 (CCW) Motor 4 (CW)

Rear

Installing the wrong propeller direction is one of the most common reasons a drone flips during takeoff.

Quick Beginner Recommendations

Frame	Motor	Propeller	Battery
F330	2212 1000KV	9047	3S
F450	2212 920KV	1045	3S/4S
S500	2216 880KV	1147	4S
650mm	3508 580KV	1345	6S
Agri Drone	6215 170KV	2470	12S

Golden Rule

High KV Motor → Small Propeller

Low KV Motor → Large Propeller

This single rule will help beginners choose compatible motor–propeller combinations and avoid overheating, poor efficiency, and unstable flight.

Drone Battery Selection Table

What is a Drone Battery?

A battery is the **power source** of the drone. It supplies electricity to the flight controller, ESCs, motors, GPS, telemetry, cameras, and other electronics.

For most drones, **LiPo (Lithium Polymer)** batteries are the standard choice because they provide high power with relatively low weight.

Battery Terminology

Term	**Meaning**
S	Number of Cells in Series
mAh	Battery Capacity
C Rating	Maximum Discharge Capability
Voltage	Electrical Potential
Wh	Stored Energy
XT30/XT60/XT90	Battery Connector Types

Cell Count vs Voltage

Battery	Nominal Voltage	Fully Charged Voltage
1S	3.7V	4.2V
2S	7.4V	8.4V
3S	11.1V	12.6V
4S	14.8V	16.8V
5S	18.5V	21.0V
6S	22.2V	25.2V
8S	29.6V	33.6V
10S	37V	42V
12S	44.4V	50.4V
14S	51.8V	58.8V

Battery Capacity Guide

Capacity	Typical Application
300–450mAh	Tiny Whoop
650–850mAh	Micro FPV
1300–1800mAh	5" FPV
2200mAh	F330
5200mAh	F450
10000mAh	S500/650
16000mAh	Delivery Drone
22000mAh	Agriculture Drone
30000mAh	Heavy Lift UAV

Detailed Battery Selection Table

Application	Frame	Motor	Propeller	Battery	Capacity
Tiny Whoop	65mm	0802	31mm	1S	300mAh
Tiny Whoop Pro	75mm	0802	40mm	1S	450mAh
Micro FPV	85mm	1102	2"	2S	450mAh

Toothpick	95mm	1103	2"	2S	650mAh
Micro Freestyle	105mm	1204	2.5"	3S	650mAh
Cinewhoop	120mm	1404	3"	4S	850mAh
Cinewhoop HD	150mm	1505	3.5"	4S	1000mAh
Racing FPV	220mm	2207 2500KV	5"	6S	1300mAh
Racing Pro	220mm	2207 2700KV	5"	6S	1500mAh
Freestyle FPV	225mm	2306 1900KV	5"	6S	1500mAh
Long Range FPV	295mm	2807 1300KV	7"	6S	4000mAh
F330 Beginner	F330	2212 1000KV	9047	3S	2200mAh
F330 Trainer	F330	2212 1000KV	9047	3S	3000mAh
F450 Basic	F450	2212 920KV	1045	3S	5200mAh
F450 GPS Drone	F450	2212 920KV	1045	4S	5200mAh
S500 Drone	S500	2216 880KV	1147	4S	5200mAh
S500 Mapping	S500	2216 880KV	1147	4S	10000mAh
Photography Drone	550mm	2814 700KV	12"	6S	10000mAh
Survey Drone	650mm	3508 580KV	13"	6S	12000mAh

Mapping UAV	650mm	3508 580KV	15"	6S	16000mAh
Inspection Drone	650mm	4008 380KV	15"	6S	22000mAh
Research UAV	650mm	4008 380KV	18"	6S	22000mAh
Delivery Prototype	800mm	5010 300KV	18"	8S	16000mAh
Delivery Drone	900mm	6215 170KV	22"	8S	22000mAh
Heavy Delivery	1000mm	6215 170KV	24"	12S	22000mAh
Agriculture 1L	650mm	3508 580KV	15"	6S	16000mAh
Agriculture 5L	1000mm	6215 170KV	24"	12S	16000mAh
Agriculture 10L	1200mm	7215 150KV	28"	12S	22000mAh
Agriculture 20L	1400mm	8120 120KV	32"	12S	30000mAh
Heavy Lift UAV	1500mm	10020 100KV	34"	14S	32000mAh
Cargo Drone	1800mm	12028 80KV	36"	14S	40000mAh
Industrial UAV	2000mm	15035 60KV	40"	18S	50000mAh

C Rating Selection Table

Formula

$$Maximum\ Current = Capacity(Ah) \times C\ Rating$$

Application	Recommended C Rating
Tiny Whoop	30C–60C
Beginner Drone	25C–35C
GPS Drone	25C–35C
Photography Drone	20C–30C
Mapping Drone	20C–30C
FPV Racing	70C–150C
Freestyle FPV	70C–120C
Delivery Drone	25C–50C
Agriculture Drone	25C–50C

Battery Connector Table

Connector	Current Capacity	Application
JST-PH2.0	<10A	Tiny Whoop
XT30	30A	Micro FPV

XT60	60A	F330/F450/S500
XT90	90A	Mapping & Delivery
AS150	150A+	Agriculture
QS8	200A+	Heavy Lift UAV

Battery Selection by Flight Time Goal

Desired Flight Time	**Suggested Battery**
5–8 min	1300mAh
10–15 min	2200–5200mAh
15–20 min	5200–10000mAh
20–30 min	10000–22000mAh
30–45 min	22000–30000mAh
45–60 min	30000mAh+

Common Battery Selection Mistakes

Mistake	**Result**
Voltage Too High	ESC/Motor Damage
Voltage Too Low	Poor Performance

Capacity Too Small	Short Flight Time
Capacity Too Large	Excess Weight
Low C Rating	Battery Sag
Wrong Connector	Power Issues
Old Battery	Reduced Flight Time
Swollen Battery	Safety Hazard

Quick Beginner Recommendations

Drone Type	**Recommended Battery**
F330	3S 2200–3000mAh
F450	3S/4S 5200mAh
S500	4S 5200–10000mAh
FPV Racing	6S 1300mAh
Long Range FPV	6S 4000mAh
Mapping Drone	6S 16000mAh
Agriculture Drone	12S 16000–30000mAh

Golden Battery Rule

Higher Voltage (S) = More Power
Higher Capacity (mAh) = More Flight Time
Higher C Rating = More Current Delivery
Higher Capacity = More Weight

A good drone designer always balances **power, flight time, payload, and weight** instead of simply choosing the largest battery available.

ESC (Electronic Speed Controller) Selection Chart

What is an ESC?

An **ESC (Electronic Speed Controller)** controls the speed, direction, and braking of a brushless motor based on commands from the flight controller.

Simple Working

Battery

↓

ESC

↓

Motor

Flight Controller

↓

ESC Signal

The flight controller tells the ESC how fast to spin the motor, and the ESC supplies the required power.

ESC Selection Formula

Choose an ESC with at least **20–30% higher current rating** than the motor's maximum current.

$$ESC\ Rating \geq 1.3 \times Motor\ Maximum\ Current$$

Example

Motor Maximum Current = 20A

Required ESC:

20 × 1.3 = 26A

Choose **30A ESC**

ESC Selection by Motor Size

Motor Size	KV Range	Max Current	Recommended ESC
0802	19000–25000KV	3A	5A ESC
1102	10000–19000KV	5A	10A ESC
1103	8000–10000KV	6A	12A ESC
1204	5000–8000KV	8A	15A ESC
1404	3800–4500KV	12A	20A ESC
1505	3600–4000KV	15A	20A ESC
1806	2300–2700KV	18A	25A ESC
2204	2300KV	20A	30A ESC
2205	2300–2600KV	25A	30A ESC
2206	2300–2500KV	30A	35A ESC
2207	1700–2700KV	35A	45A ESC
2306	1700–1900KV	40A	45A ESC
2407	1700KV	45A	55A ESC
2507	1500KV	50A	55A ESC

2807	900–1300KV	55A	60A ESC
3110	700–900KV	60A	80A ESC
3508	580–700KV	35A	50A ESC
4008	380KV	40A	60A ESC
5010	300KV	50A	80A ESC
6215	170KV	60A	80A ESC
7215	150KV	70A	100A ESC
8120	120KV	90A	120A ESC

ESC Selection by Drone Type

Drone Type	**Motor**	**Battery**	**ESC**
Tiny Whoop	0802	1S	5A
Micro FPV	1102	2S	10A
Toothpick	1103	2S	12A
Cinewhoop	1404	4S	20A
Racing FPV	2207	6S	45A

Freestyle FPV	2306	6S	45A
Long Range FPV	2807	6S	55A
F330	2212 1000KV	3S	30A
F450	2212 920KV	3S/4S	30A
S500	2216 880KV	4S	30–40A
Photography Drone	3508 580KV	6S	50A
Mapping Drone	3508 580KV	6S	50A
Inspection Drone	4008 380KV	6S	60A
Delivery Drone	6215 170KV	12S	80A
Agriculture 10L	7215 150KV	12S	100A
Agriculture 20L	8120 120KV	12S	120A

ESC Selection by Battery Voltage

Battery	ESC Voltage Support Required
1S	1–2S ESC
2S	2–3S ESC
3S	2–4S ESC
4S	2–6S ESC
6S	3–6S ESC
8S	6–8S ESC
10S	8–10S ESC
12S	12S Compatible ESC
14S	HV ESC
18S	Industrial HV ESC

Beginner Drone ESC Table

Frame	Motor	Propeller	Battery	ESC
F330	2212 1000KV	9047	3S 2200mAh	30A
F450	2212 920KV	1045	3S 5200mAh	30A
F450 GPS	2212 920KV	1045	4S 5200mAh	30A
S500	2216 880KV	1147	4S 5200mAh	40A
650mm	3508 580KV	1345	6S 10000mAh	50A

ESC Protocols

Protocol	Speed	Application
PWM	Slow	Old Drones
OneShot125	Medium	FPV
OneShot42	Fast	FPV
Multishot	Very Fast	Racing
DShot150	Digital	Modern Drones
DShot300	Faster	FPV
DShot600	High Performance	Racing

DShot1200	Very Fast	Professional FPV

ESC Firmware Types

Firmware	**Application**
SimonK	Old Multirotors
BLHeli	FPV
BLHeli_S	Beginner FPV
BLHeli_32	Advanced FPV
AM32	Open Source ESCs

ESC Types

Type	**Description**
Individual ESC	One ESC per motor
4-in-1 ESC	Four ESCs on one board
HV ESC	High Voltage Systems
Opto ESC	No BEC
BEC ESC	Provides 5V output

Common ESC Problems

Problem	Cause
ESC Overheating	Too small ESC
Motor Stuttering	Wrong timing/protocol
ESC Burnout	Excess current
Desync	Incompatible settings
Random Shutdown	Low voltage
Unequal Motor Speeds	Calibration issue

ESC Selection Mistakes

Mistake	Result
20A ESC on 35A Motor	ESC Burns
Wrong Voltage Rating	ESC Failure
Poor Cooling	Overheating
Cheap ESC for Heavy Lift	Reliability Issues
Mixed ESC Models	Uneven Performance

Quick ESC Recommendation Chart

Application	Recommended ESC
Tiny Whoop	5A
Micro FPV	10–15A
Cinewhoop	20A
Beginner F450	30A
S500	40A
Racing FPV	45A
Long Range FPV	55A
Mapping Drone	50–60A
Delivery Drone	80A
Agriculture Drone	100–120A

Golden ESC Rule

Motor Current ↑ → ESC Rating ↑
Battery Voltage ↑ → ESC Voltage Rating ↑
Propeller Size ↑ → Current Draw ↑ → ESC Size ↑

For most beginner drones (F450 + 2212 920KV + 1045 props + 3S/4S battery), a **30A ESC** is the safest and most widely used choice.

Drone Wiring Reference Guide

Basic Drone Wiring Architecture

Complete Wiring Table

Component	Connected To	Purpose
Battery	Power Module	Main Power
Power Module	Pixhawk Power Port	Powers Pixhawk
Power Module	PDB	Power Distribution
PDB	ESCs	Supplies Battery Power
ESC	Motor	Controls Motor Speed
ESC Signal Wire	Pixhawk MAIN OUT	Receives Commands
GPS	GPS Port	Navigation
Compass	I2C Port	Heading Information
Receiver	RC IN	Pilot Commands
Telemetry	TELEM1/TELEM2	Ground Communication
Buzzer	Buzzer Port	Warning Alerts
Safety Switch	Safety Port	Arming Safety

Battery Wiring

Components

Component	Example
Battery	3S 5200mAh
Connector	XT60
Power Module	Pixhawk PM



Functions

Function	Purpose
Voltage Measurement	Battery Monitoring
Current Measurement	Power Consumption
5V Output	Pixhawk Power

ESC Wiring

Each ESC has:

Battery Side

Red Wire (+)

Black Wire (-)

Connected to PDB.

Motor Side

Motor Wire A

Motor Wire B

Motor Wire C

Connected to Brushless Motor.

Signal Side

Signal Wire

Ground Wire

Connected to Pixhawk Output.

Motor Output Connections

X Quadcopter Layout

Front

Motor 1 (CW)

▲

Motor 4(CCW) Motor 2(CCW)

▼

Motor 3(CW)

Rear

Pixhawk Outputs

Pixhawk Output	Motor
MAIN OUT 1	Motor 1
MAIN OUT 2	Motor 2
MAIN OUT 3	Motor 3
MAIN OUT 4	Motor 4

GPS Wiring



Connections

GPS Wire	Pixhawk
GPS Connector	GPS Port
Compass Connector	I2C Port

GPS Placement

GPS Mast

▲

|

10–15 cm Above Frame

|

Drone Frame

Why?

Keeps GPS away from:

- ESCs
- Motors
- Power Wires

Receiver Wiring

FlySky Example

Receiver Pin	Pixhawk
IBUS	RC IN
VCC	5V
GND	GND

ELRS Example

Receiver	Pixhawk
TX	RX
RX	TX
5V	5V
GND	GND

Telemetry Wiring

433 MHz / 915 MHz

Telemetry	Pixhawk
TX	RX
RX	TX
5V	5V
GND	GND

Purpose

- Mission Planner connection
- Live data
- Mission upload
- Flight monitoring



Obstacle Avoidance

Wiring





TFmini LiDAR

TFmini	**Pixhawk**
TX	RX
RX	TX
5V	5V
GND	GND

POWER DISTRIBUTION BOARD (PDB)

Distributes power from a single battery to multiple Electronic Speed Controllers (ESCs) safely and efficiently.

1. PURPOSE

The PDB receives power from the battery and distributes it to all ESCs and other power modules (Flight Controller, VTX, etc.).

ONE BATTERY POWERS:

- ESC 1
- ESC 2
- ESC 3
- ESC 4

2. BENEFITS

- Simplifies wiring
- Provides a common power hub
- Stable power distribution
- Reduces soldering work
- Built-in protection options (fuses, filtering)

3. BASIC CONNECTION DIAGRAM



4. PDB TYPES (EXAMPLES)



4-in-1 PDB (Basic)
Distributes power to 4 ESCs

PDB with BEC
Provides 5V / 12V output for FC, VTX, etc.

PDB with Fuse
Provides short circuit protection for ESCs and system

5. TYPICAL CONNECTIONS ON PDB



6. KEY FEATURES

Input Voltage	2S – 6S LiPo (7.4V – 25.2V)
Continuous Current	Depends on PDB (e.g., 90A, 120A, 200A)
ESC Outputs	4 (Quadcopter) / 6 (Hexacopter) / 8 (Octocopter)
BEC Output	5V / 12V (Optional)
Protection	TVS Diode, Capacitor, Fuse (Optional)
Mounting	30.5mm / 20mm / Custom

7. HOW IT WORKS

1. The battery supplies DC power to the PDB.
2. The PDB distributes the power equally to all connected ESCs.
3. Each ESC uses this power to drive its respective motor.
4. Some PDBs also provide regulated power (5V/12V) to other electronics.

⚠ IMPORTANT NOTES

- Always match PDB current rating with your ESC and motor requirements.
- Use proper wire gauge and quality soldering.
- Ensure correct polarity (+ and –).
- Add a main fuse close to the battery for safety.

Voltage Reference Table

Battery	Full Voltage
1S	4.2V
2S	8.4V
3S	12.6V
4S	16.8V
6S	25.2V

12S	50.4V

Formula

$$V = 4.2 \times Cells$$

Current Reference

ESC Selection Formula

$$ESC \geq 1.3 \times Motor\ Current$$

Example:

Motor Current = 25A

Required ESC

= 25 × 1.3

= 32.5A

Choose 35A or 40A ESC

Wiring Color Reference

Color	**Meaning**
Red	Positive (+)
Black	Negative (-)
Yellow	Signal
White	Signal
Green	Data
Blue	Data
Orange	Signal

Common Wiring Mistakes

Mistake	Result
Reverse Polarity	Burned Components
Wrong GPS Port	GPS Not Detected
Wrong Motor Output	Drone Flips
Loose XT60	Power Failure
GPS Near ESC	Compass Errors
Receiver TX/RX Wrong	No Communication
Telemetry TX-TX	No Data Link
Missing Ground Wire	Unstable Communication

Wiring Pre-Check Checklist

Check	Status
Battery Polarity Correct	✓
XT60 Secure	✓
ESC Connected Properly	✓
Motors Numbered Correctly	✓

GPS Connected	✓
Compass Connected	✓
Receiver Working	✓
Telemetry Connected	✓
No Exposed Wires	✓
Voltage Verified	✓

Golden Wiring Rule

Always Follow This Sequence

Battery

↓

Power Module

↓

Pixhawk

↓

ESC

↓

Motor

GPS

↓

Pixhawk

Receiver

↓

Pixhawk

Telemetry

↓

Pixhawk

Before First Power-Up

1. Remove all propellers.
2. Check polarity with a multimeter.
3. Verify no short circuits.
4. Confirm battery voltage.
5. Test motor directions.
6. Verify GPS and receiver detection.
7. Only then install propellers.

This procedure prevents most beginner wiring mistakes and significantly reduces the risk of damaging electronics or causing a crash.

Pre-Flight Checklist

What is a Pre-Flight Checklist?

A **Pre-Flight Checklist** is a list of inspections and tests performed before every flight to ensure the drone is safe, functional, and ready to fly.

Why is it Important?

Most drone crashes occur because of:

- Loose propellers
- Low battery
- Wrong flight mode
- GPS issues
- Compass errors
- Pilot mistakes

A proper pre-flight check can prevent these problems.

Complete Pre-Flight Checklist

Item	Check	Status
Frame	No cracks or damage	□
Arms	Secure and tight	□
Landing Gear	Not damaged	□
Motors	Spin freely	□
Motor Mount Screws	Tight	□

Propellers	Correctly installed	□
Propeller Nuts	Tightened	□
ESC Wiring	Secure	□
Battery	Fully charged	□
Battery Connector	Firm connection	□
Battery Strap	Tight	□
Flight Controller	Powered correctly	□
GPS	Connected	□
Compass	Connected	□
Receiver	Working	□
Telemetry	Connected	□
Antennas	Secure	□
Camera	Working	□
Mission Uploaded	Verified	□
Weather	Suitable	□
Takeoff Area	Clear	□

Stage 1: Physical Inspection

Frame Inspection

Check:

✓ No cracks

✓ No loose screws

✓ No bent arms

Example

Good:

Frame is rigid and tight.

Bad:

One arm slightly cracked.

Result:

Possible crash during flight.

Motor Inspection

Check :

✓ Smooth rotation

✓ No unusual noise

✓ No wobbling

Example

Good: Motor spins freely.

Bad: Grinding noise present.

Result: Motor bearing damage.

Propeller Inspection

Check:

✓ No cracks

✓ No bends

✓ Correct direction

✓ Tight nuts

Example 1

CW prop on CW motor.

✓ Correct

Example 2

CW prop on CCW motor.

✗ Drone may flip during takeoff.

Stage 2: Electrical Inspection

Battery Check

Verify:

✓ Fully charged

✓ No swelling

✓ No damaged wires

✓ Correct voltage

Battery Voltage Table

Battery	**Full Charge**
3S	12.6V
4S	16.8V
6S	25.2V
12S	50.4V

Example

3S Battery:

11.0V

Not fully charged.

Risk:

Short flight time.

Connector Check

Verify:

✓ XT60 secure

✓ No loose wires

✓ No exposed conductors

ESC Check

Verify:

✓ ESCs initialize correctly

✓ Startup tones heard

✓ No overheating

Stage 3: Flight Controller Check

Pixhawk Check

Verify:

✓ Power LED ON

✓ No error messages

✓ Sensor health good

Example

Mission Planner:

"PreArm Check Passed"

✓ Ready

Accelerometer Check

Verify:

✓ Calibration completed

✓ No sensor errors

Compass Check

Verify:

✓ Compass calibrated

✓ No magnetic interference

Stage 4: Radio Check

Transmitter

Verify:

✓ Fully charged

✓ Correct model selected

✓ Flight mode switches working

Receiver

Verify:

✓ Signal received

✓ Failsafe configured

Radio Calibration

Verify:

✓ Full stick movement detected

✓ Correct channel mapping

Stage 5: GPS Check

GPS Lock

Wait until:

✓ Minimum 10 satellites

✓ HDOP acceptable

✓ Home position recorded

Example 1

Satellites = 14

✓ Good

Example 2

Satellites = 4

✗ Do not fly Auto/RTL

Home Position

Verify:

✓ Correct location recorded

Necessary for:

- RTL
- Auto Missions

Stage 6: Flight Mode Check
Verify each mode works.

Mode	**Test**
Stabilize	✓
Alt Hold	✓
Loiter	✓

RTL	✓
Auto	✓

Stage 7: Mission Check

For Autonomous Missions

Verify:

✓ Waypoints correct

✓ Altitude correct

✓ RTL enabled

✓ Geofence configured

Example

Waypoint Altitude:

50 m

Nearby building:

40 m

✓ Safe

Stage 8: Weather Check

Safe Conditions

Condition	**Recommended**
Wind	<15 km/h
Rain	None
Visibility	Good
Temperature	Moderate

Unsafe Conditions

Condition	Risk
Rain	Electronics damage
Thunderstorm	Loss of control
Strong Wind	Crash risk
Fog	Poor visibility

Stage 9: Flying Area Check

Verify:

✓ Open field

✓ Away from people

✓ Away from power lines

✓ Away from airports

✓ No obstacles nearby

Before Arming Checklist

Check	Status
Props Installed Correctly	□
Battery Connected	□
GPS Lock Acquired	□
Compass Healthy	□
Flight Mode Correct	□

RC Signal Good	□
Home Position Recorded	□
Area Clear	□

Common Beginner Mistakes

Mistake	**Result**
Taking Off Without GPS Lock	RTL Failure
Loose Propellers	Crash
Wrong Prop Direction	Flip on Takeoff
Low Battery	Emergency Landing
Wrong Flight Mode	Unexpected Behavior
Ignoring Compass Errors	Fly-Away Risk
Flying in Strong Wind	Loss of Control
Forgetting Battery Strap	Battery Ejection

Emergency Abort Conditions

Do NOT Fly If:

Condition	**Action**
Compass Error	Recalibrate
GPS Not Working	Fix GPS
Battery Swollen	Replace Battery
Motor Noise	Inspect Motor
Loose Frame	Tighten Screws
ESC Overheating	Diagnose ESC
Radio Signal Weak	Fix Receiver

Professional Pilot 60-Second Checklist

Frame ✓

Props ✓

Motors ✓

Battery ✓

ESC ✓

Pixhawk ✓

Receiver ✓

GPS ✓

Compass ✓

Flight Modes ✓

Mission ✓

Weather ✓

Area ✓

Golden Rule

Never Take Off Until:

Battery ✓

GPS ✓

Compass ✓

Receiver ✓

Flight Modes ✓

Props ✓

Area Safe ✓

Weather Safe ✓

Useful Drone Software

Drone software is used for:

- Flight controller setup
- Mission planning
- Autonomous flight
- Simulation
- Computer vision
- AI development
- Mapping
- Telemetry monitoring
- Log analysis
- Drone design

Complete Drone Software Reference Table

Software	Category	Purpose	Beginner Friendly	Cost
Mission Planner	Ground Control Station	ArduPilot configuration and missions	★★★★★	Free
QGroundControl	Ground Control Station	PX4 and ArduPilot control	★★★★★	Free
ArduPilot	Flight Controller Firmware	Autonomous drone firmware	★★★★☆	Free
PX4 Autopilot	Flight Controller Firmware	Research and industrial UAVs	★★★★☆	Free

Betaflight Configurator	FPV Software	FPV racing drone setup	★★★★☆	Free
INAV Configurator	Navigation Software	GPS FPV drones	★★★★☆	Free
MAVProxy	Ground Station	Command-line drone control	★★★☆☆	Free
APM Planner 2.0	Ground Station	Alternative mission planning	★★★☆☆	Free

Mission Planning Software

Software	**Main Use**
Mission Planner	Waypoint missions
QGroundControl	Cross-platform mission planning
MAVProxy	Mission monitoring
UgCS	Professional mission planning
Tower (Android)	Mobile mission planning

Flight Controller Firmware

Firmware	Best For
ArduCopter	Quadcopters
ArduPlane	Fixed Wing UAVs
ArduRover	Ground Robots
PX4	Research UAVs
Betaflight	FPV Racing
INAV	GPS FPV Drones

Drone Simulation Software

Software	Purpose
RealFlight Evolution	RC Flight Training
FPV SkyDive	FPV Practice
VelociDrone	FPV Racing
Liftoff FPV Simulator	FPV Training
Gazebo Sim	Robotics Simulation
Microsoft AirSim	AI Drone Simulation

1. References

1. ArduPilot Documentation
2. PX4 Autopilot Documentation
3. Mission Planner Documentation
4. QGroundControl Documentation
5. MAVLink Protocol Documentation
6. Dronecode Foundation
7. Federal Aviation Administration (FAA) Drone Resources
8. DGCA India Drone Rules & Digital Sky Platform
9. OpenCV Documentation
10. TensorFlow Documentation
11. NVIDIA Jetson Developer Resources
12. Raspberry Pi Documentation
13. Holybro Documentation
14. CubePilot Documentation
15. Betaflight Documentation

2. AI Image Credits Page

Since the images were generated using ChatGPT AI,

Image Credits

Many illustrations, diagrams, infographics, and visual representations used in this book were generated or enhanced using Artificial Intelligence (AI) tools, including OpenAI's ChatGPT image-generation capabilities.

These images were created specifically for educational purposes to help explain drone concepts, components, systems, and workflows.

All content has been reviewed and arranged by the author for educational use.

Author:
Mokshith Sharma T P